

LOADER ATTACHMENTS FOR COMPACT WHEEL TRACTORS

HIGH PRODUCTION ATTACHMENTS WITH SKID STEER QUICK ATTACH MOUNT

SIFTING BUCKET



Designed to collect rocks and debris, allowing soil to sift through. Rake design allows for fast clean-up, ground leveling and gathering materials away from buildings and obstructions. Leave the dirt and pay less at the land fill!

Specifications	108603
Width (overall)	55.3"
Height (overall)	21.5"
Length (overall)	23.5"
Tine Spacing (between tines)	2.0"
No. of Tines	18
Tine Rod Diameter	1.13"
Weight (lbs)	300#

4 IN 1 BUCKETS



60" and 72" models available. Functions as a loader bucket, clam, grapple, dozer, box scraper, and bottom dump bucket. Has strong hinges and pins to distribute load. The bottom dump buckets allows the operator to dump into high side board trucks.

Specifications	108196	108198
Width (overall)	60"	72"
Height (overall)	27"	27"
Length w/o Teeth (overall)	28"	28"
Front Length w/o Teeth	15"	15"
Rear Length	14"	14"
Grapple Opening	28"	28"
Weight (lbs)	380#	430#

HYDRAULIC DIGGER



The D450 hydraulic digger is the most trouble free digger on the market. The unit features an in line sealed planetary gear reduction drive design. This clean, effective system ensures long trouble free usage. Digger comes with Q.A. brackets w/cradle.

Specifications	D450
Min. Hyd. Flow	5 G.P.M.
Max. Hyd. Flow	10 G.P.M.
Max. Auger Diameter	12"
Output Shaft	2" Round
Auger Diameters	6" 9" & 12"
Wt. of Digger & QA Brkt	264#





LOADER ATTACHMENTS FOR COMPACT WHEEL TRACTORS

BRUSH GRAPPLES



Aggressive grapple made of high strength steel for maximum performance and durability. Cylinder guard design protects cylinder while preventing build-up of debris. Great for cleaning up and transporting branches, brush, and limbs.

Specifications	108597	108598	108415
Width (overall)	48"	54"	72"
Height (overall)	25.5"	25.5"	25.63"
Length (overall)	30.5"	30.5"	30.5"
Tine Spacing	5.7"	5.7"	5.7"
Grapple Opening	29"	29"	29"
Clamp Force (lbs)	1,100	1,100	1,100
Weight (lbs)	300#	315#	435#

ROOT RAKES



The aggressive tine shanks root out objects below ground level. The wide grapple opening allows for gathering a large amount of brush and debris. The hydraulically operated grapple locks the material in place and stabilizes it for transport.

Specifications	109982	109984
Width (overall)	60"	72"
Height (overall)	28.1"	28.1"
Length(overall)	19.5"	19.5"
Tine Spacing	12"	12"
Grapple Width	57.1"	57.1"
Grapple Opening	32.5"	32.5"
Weight (lbs)	413#	448#

PALLET FORKS



High strength lightweight frame for large 2300 pound pay loads. Open guard for excellent visibility. Patented load retention ring. Class II ITA forks with positioning lock pin.

Specifications	107283/	107283/
	106220	106222
Frame Width	45"	45"
Frame Height	28"	28"
Fork Thickness	1"	1"
Fork Width	3"	3"
Fork Length	42"	48"
Wt. Frame & Forks	252#	285#

Specifications Subject To Change Without Notice