

For Tractors 90 - 160 Horsepower

"T" SERIES



These **"T" Series Tillers** were designed for high horsepower tractors to produce a finished seedbed in a single pass. For crops such as vegetables, timing is everything. The basic plow, disc, cultivator tilling operation requires too many passes, wasted fuel, and causes excessive compaction. At a depth of 10 inches, the saber tines produce a uniform mixture of loose, textured soil that holds moisture and reduces erosion. There is no better tool for preparation of seedbeds and incorporating crop residue.

FEATURES:

- ❑ Cat. 2, 3-point hitch
- ❑ 10" Approximate tilling depth
- ❑ 4 Speed gearbox - 2 speeds @ 540 RPM & 2 speeds @ 1000 RPM
- ❑ For tractors up to a maximum of 160 HP
- ❑ Strong, smooth running, all gear final drive
- ❑ Slip clutch driveshaft to protect tractor and tiller drive system
- ❑ Curved, saber style heat treated, long wearing tines
- ❑ 6 Tines mounted on each rotor plate for maximum tilling action
- ❑ Tines staggered in scroll design for easy soil penetration
- ❑ Large, oil bath, long wearing rotor bearings
- ❑ Powder coated, baked-on paint to reduce corrosion
- ❑ Side mounted skids for depth control
- ❑ Retractable parking stand

SPECIFICATIONS:

MODEL NO.	TILLING WIDTH	OVERALL WIDTH	NO. OF TINES	APPROX. HORSEPOWER	WT.
T230	90"	97"	60	90 to 100 HP	2140#
T280	110"	117"	66	100 to 120 HP	2205#
T305	120"	127"	72	120 to 160 HP	2275#