

Featuring "No Tools" Blade Changing System

"SLE" SERIES



**QUICK CHANGE
Y BLADE**



**QUICK CHANGE
DUCKSFOOT BLADE**

FEATURES:

- ❑ Cat. 1, A.S.A.E. quick hitch compatible for easy attaching to tractor
- ❑ Designed for tractors that have 540 rpm PTO speed
- ❑ Low profile design for clearing obstructions
- ❑ Available with side slicing Y blades for light brush or grass finishing
- ❑ Ducksfoot blades
- ❑ Center mount or offset 9 inches to right
- ❑ Pivoting 3-point hitch back brace for added strength and to easily offset hitch
- ❑ 45 Horsepower, 540 rpm gearbox
- ❑ Rotor speed - 2340 rpm with blade tip speed of 8267 feet per minute
- ❑ 3 Belt final drive with automatic belt tightening idler to provide maximum power to the blades
- ❑ Internal "saw tooth" cutter bar to reduce the size of the shredded material
- ❑ 5" Diameter rear roller
- ❑ Two adjustable parking stands to allow easy "hook-up" to quick hitch tractor
- ❑ Safety chain shield in front and rubber rear deflector

This Gearmore mower series was developed for mowing weeds and light brush with side slicing Y blades. All models are also available with finish mowing cupped "ducksfoot" blades for mowing grass. Standard features include ASAE quick attach 3-point hitch, low profile design, center mount or offset, adjustable rear roller and many more.

These flail mowers were designed to achieve fine shredding on cover crops, parks, golf courses, pastures, and light weed abatement.

SPECIFICATIONS:

MODEL NO.	MOWING WIDTH	OVERALL WIDTH	NO. OF KNIVES	MIN. H.P. REQUIRED	WEIGHT
SLE-120	48"	54"	24	20	415#
SLE-160	63"	69"	30	28	525#
SLE-190	75"	81"	36	35	620#