

Medium Duty 300 Series

ROTARY MOWERS

Our **300 Series Mowers** feature a smooth, double top deck to insure water run off. The double internal chamber produces better suction and distributes cuttings more evenly. Other features include large 85 horsepower gearbox, 1/4" thick side plates, 10 gauge top deck, and flexible floating ASAE Category 1 quick hitch, which allows for easy tractor hook-up. These mowers, developed with added strength throughout, allows shredding up to 2 inch diameter brush.

Stocked color charcoal gray - other colors available



SPECIFICATIONS:

Hitch: Cat. 1, ASAE Quick Hitch
 Gearbox: 85 H.P., 540 RPM
 Deck Material: 10 Gauge (1/8" Approx.)
 Side Plates: 1/4" Thick, 9" High
 Side Skids: Full Length
 Tailwheel: 4" x 16" Laminated
 Cutting Height: 1 1/2" to 9"
 Blade Size: 1/2" x 4"
 Blade Material: Heat Treated Steel
 Blade Bolt: 1 1/4" Diameter
 Driveshaft: Slip Clutch Protection
 Safety Chains: Optional, but strongly recommended - front & rear

FEATURES:

- ❑ Cuts up to 2" diameter material
- ❑ Flexible floating hitch follows the contour of the terrain
- ❑ Two internal channels for main deck support
- ❑ Heavy round dished spindle pan
- ❑ Reinforced gearbox mounting plate
- ❑ Integral PTO shaft storage bracket to keep shaft clean for installing on the tractor PTO shaft
- ❑ Shielded series 5 PTO shaft with slip clutch protection
- ❑ Grade 5 plated hardware
- ❑ Powder coated charcoal paint

SPECIFICATIONS:

MODEL NO.	CUTTING WIDTH	OVERALL WIDTH	OVERALL LENGTH	BLADE TIP SPEED - FPM	WEIGHT
RC300-60	60"	65"	109"	12,465	815#
RC300-72	72"	77"	122"	14,955	1015#
RC300-84	84"	89"	134"	17,450	1195#

WARNING: If operating mower near roads and/or where people are present, you must equip mower with safety shielding. OSHA AgStandard #1928.27