

3-Point Hitch And Pull Type Models

ROTARY MOWER - 10 FOOT



These 10 foot wide rotary mowers are available in 3-point lift type or trailer pull type. For stability, both models are fitted with dual wheels supported with large 21" diameter laminated tires. The dual spindles are powered by 90 horsepower gearboxes. For added protection, a constant velocity driveline is provided. Designed for those tough mowing jobs and insures years of trouble free usage.

FEATURES:

- 2 - 90 H.P., 540 R.P.M. outboard gearboxes
- 125 H.P., 540 R.P.M. splitter gearbox
- 2" x 3" Tubular deck reinforcement
- Slip clutch gearbox protection
- 16,233 FPM blade tip speed
- 1/2" x 4" Swinging blades
- Cutting height - 1 1/2" to 12"
- Chain shielding - front and rear
- Up to 2" brush diameter
- Minimum PTO H.P. - 50
- 1/4" x 10" Side plates
- 7 Gauge deck (3/16")
- Round stump jumper
- Replaceable skid shoes
- Hitch type - Cat. II & III ASAE quick hitch or pull type

SPECIFICATIONS:

MODEL NUMBER	TYPE	CUTTING WIDTH	OVERALL WIDTH	OVERALL LENGTH	MIN. PTO HORSEPOWER	WT.
270-120-L-SL-CB	3-Point	120"	10' - 4"	9' - 6"	60 H.P.	2250#
270-120-P-SL-CB	Pull Type	120"	10' - 4"	19' - 6"	60 H.P.	2725#