

## Rear Blades For Up To 30 & 50 Horsepower Tractors

**5, 6, & 7 FOOT**



**CAT I  
A. S. A. E.  
QUICK  
HITCH  
COMPATIBLE**

These **Gearmore Rear Blades** are the answer for compact tractor earth-moving requirements. They are the most versatile rear blades on the market today, as all of the standard features normally found only on large expensive rear blades, are standard on the Gearmore Rear Blade. Tilt, angle, offset, and reverse are easy to adjust so that any grading or ditching operation may be accomplished. Parking stand is now standard equipment.

### SPECIFICATIONS:

Tractor Horsepower:	Up to 30 Horsepower	Blade Tilt:	14° to 25° Up or Down
Main Beam:	4" x 4" Steel tubing	Blade Offset:	6" Right or Left
Moldboard:	1/4" x 13" High	Cutting Edge:	1/2" x 6" Reversible
3-Point Hitch:	Category 1	Weights:	Model GB5, 5' - 260#
King Pin:	2" Solid Round		Model GB6, 6' - 285#
Blade Angle:	Up to 45° Right or Left		Model GB7, 7' - 300#

**6, & 7 FOOT**



**CAT I  
A. S. A. E.  
QUICK  
HITCH  
COMPATIBLE**

These **Gearmore Rear Blades** are the answer to your mid-size tractor earth-moving requirements. These blades feature "Beam Swing" offset, which allows the heavy 4" x 4" beam to swing right or left to obtain maximum offset. Tilt, angle, offset, and reverse positions are easy to adjust so that any grading or ditching operation can be done. Parking stand is now standard equipment.

### SPECIFICATIONS:

Tractor Horsepower:	Up to 50 Horsepower	Blade Tilt:	14° to 25° Up or Down
Main Beam:	4" x 4" Steel tubing	Blade Offset:	Up to 35" Right or Left
Moldboard:	1/4" x 16" High	Cutting Edge:	1/2" x 6" Reversible
3-Point Hitch:	Category 1	Weights:	Model GB60, 6' - 360#
King Pin:	2" Solid Round		Model GB70, 7' - 380#
Blade Angle:	Up to 45° Right or Left		