

For Tractors 50 - 90 Horsepower

"S" SERIES



These "S" Series tillers were designed for high usage in agricultural and industrial applications. At a depth of 8 inches, the saber tines produce a uniform mixture of loose, textured soil that holds moisture and reduces erosion. There is no better tool for preparation of seedbeds.



The S255 tiller is now available with a smooth rear roller to bury wood chips and then to slightly compact and smooth out the orchard floor.

FEATURES:

- Cat. 2 fixed center mount
- A.S.A.E. quick hitch compatible
- 90 Horsepower, 4-speed gearbox
- 4 Speeds - 540 RPM
- All gear final drive
- Slip clutch driveshaft
- 6 Tines mounted on each rotor plate
- Tines staggered for easy penetration
- Torque tubing frame to absorb shock loads
- Adjustable skids for depth control

OPTIONS:

- Rear Roller, 2 Speed - 1000 RPM gears

SPECIFICATIONS:

MODEL NO.	TILLING WIDTH	OVERALL WIDTH	NO. OF TINES	APPROX. H.P.	WT.
S160	62"	66"	36	50 HP	1190#
S180	71"	75"	42	60 HP	1255#
S205	81"	85"	48	70 HP	1350#
S230	91"	95"	54	80 HP	1430#
S255	102"	106"	60	90 HP	1490#