

Center Mount, Offset Mechanical or Hydraulic

"SFG" SERIES

Our new SFG Series of flail mower/shredders feature fixed center mount, manual or hydraulic side shift. The narrow shredders are fixed center mount. The two largest shredders are manual offset, return to center with optional hydraulic offset. Two style of blades can be purchased, hammer knives or double Y blades. These blades are also interchangeable on the same shredders. The low profile design of the machine aids when working in tight areas. These are popular mowers in vineyards, berries, roadsides, weed abatement, rental yards, etc.



Model SFG155 w/Optional Rake Teeth & Roller Scraper

FEATURES:

- Cat. I ASAE quick hitch, 540 RPM tractors
- Fixed center mount hitch, except SFG185/200
- 70 HP gearbox with built-in overrunning clutch
- Low profile belt housing, 23" high for clearance
- Hammer knives shreds brush & prunings up to 2" dia.
- Double Y Blades mow weeds & light brush up to 1" dia.
- Cutting height adjusts from 1" to 4" above ground
- Rotor speed - 2200 RPM
- Two rows of heat treated re-cutter blades
- Rear hatch adjusts for various types of mowing
- Rear hatch slotted for rake teeth
- Balanced 5 1/2" rotor tubing
- 5 1/2" Diameter rear roller adjusts vertically and horizontally

- 4 Belt final drive with automatic spring tension idler to provide maximum power to the rotor
- Series 6 PTO driveshaft
- Front mounted safety chains
- Rear rubber deflector

OPTION: Rake Teeth



HAMMER KNIFE



DOUBLE Y BLADE

SPECIFICATIONS:

MODEL NO.	WORKING WIDTH	OVERALL WIDTH	MAX. OFFSET*	NO. OF HAMMERS	NO. OF Y BLADES	H.P. REQ'D	RAKE SLOTS	WT.
SFG95	38"	43"	-	8	32	20	6	620#
SFG125	49"	55"	-	8	32	25	8	730#
SFG140	55"	61"	-	10	40	30	9	770#
SFG155	61"	67"	-	10	40	35	10	840#
SFG185*	73"	78"	44"	12	48	40	12	1005#
SFG200*	79"	84"	48"	14	56	45	13	1100#

* These shredders come with manual offset, hydraulic offset is optional. Offset shown is the maximum offset from centerline of tractor to the right