

Standard Duty 200 Series

ROTARY MOWERS



60" Mower with Optional Chain Shielding Shown

CAT I
A.S.A.E.
QUICK
HITCH
COMPATIBLE

FEATURES:

- Cuts up to 1" diameter material
- Flexible floating hitch follows the contour of the terrain, thus reducing stress on tractor and mower
- Two 2" x 2" full length angles for main deck support
- Heavy round dished spindle pan
- Reinforced gearbox mounting plate
- Integral PTO shaft storage bracket to keep from getting contaminated
- Shielded series 4 PTO shaft
- Grade 5 plated hardware
- Powder coated paint
- Optional - rubber or chain safety shielding
- Unique mower stand to aid in shipping, storage, and display

Our **200 Series Mowers** feature round back design for easy maneuvering in tight corners, around trees, fences, and other obstructions. The rounded rear opening also allows for more even distribution of exiting material. All models now feature higher horsepower gearboxes, which allow for operating safely with higher horsepower tractors.

The flexible floating hitch follows the contour of the terrain without putting stress on the mower and tractor. Also, hitch is designed to A.S.A.E. quick hitch standards for easy hook-up to tractor with a quick hitch system.

The special baked on, powder coated, corrosion resistant paint insures excellent appearance for years.

SPECIFICATIONS:

Hitch:	Cat. I, A.S.A.E. Quick Hitch
Gearbox:	540 RPM
Deck Thickness:	11 Gauge
Deck Depth:	7 1/2"
Side Skids:	Full Length
Tailwheel:	3 3/4" x 15" Laminated
Cutting Height:	1" to 9"
Blade Size:	1/2" x 3"
Blade Pin:	1 1/2" Diameter
Driveshaft:	Shear Pin Protection or Slip Clutch

MODEL NO.	CUTTING WIDTH	GEARBOX H.P.	OVERALL WIDTH	OVERALL LENGTH	BLADE TIP SPEED - FPM	WEIGHT
RC200-48	48"	50 H.P.	52"	85"	13,090	510#
RC200-60	60"	65 H.P.	63"	98"	14,335	585#
RC200-72	72"	65 H.P.	76"	110"	14,955	710#