GEARMORE INC.

YOUR SPREADER HEADQUARTERS

3-Point Spreaders = Pull Type Spreaders = Twin Spinner Spreaders = Pendulum Spreaders = Manure Spreaders = Turf Spreaders = Row Line Spreaders



SPREADER MODELS TO SPREAD FERTILIZER, GYPSUM, LIME, SEEDS, MULCH, AND OTHER FLOWABLE MATERIAL

13477 Benson Ave. - Chino, CA 91710 - Ph: 909/548-4848 - Fax: 909/548-4747

SPREADERS

3-POINT SPREADERS




Our 3-point hitch spreaders feature a strong, corrosion proof PVC hopper. These spinner units have double levers and stainless steel slides which allow for spreading at 180° or 90° to the right or left. They are ideal for even spreading fertilizer, seed, salt, and other flowable materials.

SPECIFICATIONS

MODEL	CAPA	CITY	OVERALL	WT.
NO.	LBS.	CU. FT.	HEIGHT	
PL180	480 lbs.	5.8 cu. ft.	36"	120#
PL300	765 lbs.	9.2 cu. ft.	42"	130#
PL500	1000 lbs.	12.3 cu. ft.	45"	140#

TRAILER SPREADERS



SPECIFICATIONS

MODEL	. CAPACITY		HEIGHT	WIDTH	DEPTH	WT.
NO.	LBS.	CU. FT.				
PTP180-P	480 lbs.	5.8 cu. ft.	51"	41"	59"	175#
PTP300-P	765 lbs.	9.2 cu. ft.	56"	45"	59"	185#

PENDULUM **S**PREADERS

Our line of pendulum spreaders feature exact rate/spread control, quick change spouts, low filling heights and easy maintenance. These spreaders are extremely accurate and the pendulum movement of the spout back and forth insures that the application rate is always identical on both sides. These versatile spreaders are popular for orchards, vineyards, turf, and general farm applications.

SPECIFICATIONS

MODEL	MODEL HITCH		ACITY	OVERALL		WT.
NO.	CAT.	LBS.	CU. FT.	WIDTH	HEIGHT	
PDC400	Cat. 1	925 lbs.	13.6 cu. ft.	46"	47"	225#
PDC500	Cat. 1 & 2	1155 lbs.	17 cu. ft.	54"	36"	290#
PDC600	Cat. 1 & 2	1450 lbs.	20.5 cu. ft.	54"	40"	315#
PDHV800	Cat. 2	2000 lbs.	32 cu. ft.	74''	40"	375#



Specifications Subject To Change Without Notice

SPREADERS

SINGLE SPINNER SPREADERS



Our high capacity 3-point spreader features a stainless steel, single spinner disc with 6 stainless steel vanes. Spreaders have a heavy duty stamped and ribbed frame. All metal hoppers and frames have special phosphated undercoat, then epoxy powder painted and baked at 300 degrees to insure long life. The spreader can be set at 180°, 90° right, or 90° left spreading pattern.

SPECIFICATIONS

MODEL CAPACITY		HEIGHT	WIDTH	DEPTH	WT.	
NO.	LBS.	CU. FT.				
RT-800	1700 lbs.	28 cu. ft.	40"	51"	59"	345#

DOUBLE SPINNER SPREADERS



Our 2200 pound capacity 3-point spreader features dual stainless steel spinner discs, which are extremely accurate with only 6.7% variance across the spread pattern. The spreaders are supplied with manual lever controls when the tractor has a cab. The usual special painting system insures long life.

SPECIFICATIONS

MODEL	CAPACITY		HEIGHT	WIDTH	DEPTH	WT.
NO.	LBS.	CU. FT.				
RE-1000	2200 lbs.	35 cu.ft.	45"	59"	53"	450#

MULCH SPREADERS



SPECIFICATIONS

SIECIFICATIONS									
MODEL	CAP.	MAX.	OVE	RALL	LOADING	WT.			
NO.	HEAPED	PAYLOAD	WIDTH	LENGTH	HEIGHT				
304	4.4 yd.	3000 lbs.	55"	15'	6'	2100#			
406	5.4 yd.	4000 lbs.	62"	16' - 10"	6'	2500#			
506	6.7 yd.	3800 lbs.	62"	18' - 10"	6'	2700#			
606	8 yd.	7800 lbs.	67"	20' - 10"	6' - 6"	3300#			
706	9.3 yd.	7500 lbs.	67"	22' - 10"	6' - 6"	3500#			
588	7.8 yd.	6000 lbs.	85"	16' - 10"	6' - 6"	3200#			
1028	13.5 yd.	10,500 lbs.	85"	22' - 10"	6' - 10"	4200#			

More and more vineyards and orchards are incorporating organic mulch and compost as a means to help reduce chemical usage. The mulch spreader makes large scale use of mulch feasible for any size vineyard or orchard. The machine applies neat, uniform rows of mulch right where you want. Our Mulch Spreaders are easy to adjust the spread pattern to suit your personal requirements. The removable cross conveyor allows for spread down row centers.

Specifications Subject To Change Without Notice

SPREADERS

TURF SPREADERS



Our Seeder/Spreader is a self contained, towable implement that can be operated by almost any vehicle. This unit has a ground driven, cast iron, oil bath gearbox that can be disengaged when transporting. It is ideal for spreading seed, fertilizer, sand, and salt. The large 20" diameter x 10" wide tires make this a "Turf Friendly" implement. The spreader features a cable control that allows the operator to adjust spread rate and turn the spreader on and off from the vehicle seat. This is a popular, low cost spreader for golf courses, parks, sport fields, and turf farms.

SPECIFICATIONS

MODEL	CAP	CAPACITY SPREAD		Ν	WT.		
NO.	LBS.	CU. FT.	WIDTH	HEIGHT	WIDTH	DEPTH	
PTB560	1070 lbs.	14.2 cu. ft.	Max. 52'	51"	65"	96"	310#

MANURE SPREADERS

SPECIFI	CATIONS						
MODEL	NO. OF	CAP.	(OVERALL		TR.	WT.
NO.	HORSES	HEAPED	LENGTH	WIDTH	HEIGHT	SIZE	
22	1 - 2	16.2 cu. ft.	8' - 2"	42"	26.5"	10 HP	250#
27	1 - 4	28 cu. ft.	9' - 3"	46.5"	26.5"	15 HP	405#
37	4 - 6	37.3 cu. ft.	11' - 3"	46.5"	26.5"	18 HP	470#
57	5 - 10	56 cu. ft.	11' - 6"	58"	34"	18 HP	660#
77	11 - 20	72 cu. ft.	13' - 6"	58"	34"	22 HP	740#
97	20 +	109 cu. ft.	13' - 6"	79"	39"	25 HP	1260#



Whether you have one horse or twenty, we make a spreader that's just right for you. Every detail is engineered to save time and protect against breakdowns. From the heavy duty, all steel construction to the top quality powder coating, durable linkage and beater systems, you can be sure that your spreader was built to last. Convenient, time saving options - including the adjustable dollywheel/ jack and the manual endgate - further enhance your investment. We're sure that your spreader will quickly become the most valued piece of equipment in your stable!

TOPDRESS **S**PREADERS



Turf Tiger Cub is user friendly and more versatile than any other equipment of its kind thanks to the exclusive Saber Tooth beater. Turf Tiger Cub spreads all kinds of bulk material such as sand/peat topdressing, infield mixes, compost, grass clippings, synthetic material, lime, and wood chips with precision, power and speed.

The Turf Tiger spreads wet or dry material like no other machine. You have total control of spread pattern and thickness of spread by - belt speed, attachment speed, endgate opening and ground speed. You can choose any or all of 3 quick change spreading attachments. The patent pending Saber Tooth attachment is the most effective for wet and dry material, spreading from 8 to 12 feet. The twin spinners are best for light applications, with spreading widths up to 35 feet. The brush attachment provides precision drop spreading 42" wide.

SPECIFICATIONS

MODEL CAPACITY				WT.			
NO.	STRUCK	HEAPED	WEIGHT	LENGTH	WIDTH	HEIGHT	
3100/3100ED	1.0 cu. yd.	1.8 cu. yd.	3000 lbs.	11'	70"	51"	1140#
3200	1.3 cu. yd.	2.3 cu. yd.	3750 lbs.	13'	70"	51"	1300#
4300	2.2 cu. yd.	3.2 cu. yd.	7500 lbs.	12' - 8"	93'	73"	2180#

Specifications Subject To Change Without Notice