



Taking care of your equipment needs for over 50 years

2021 PRODUCT CATALOG

**NEW
PRODUCTS**

PROVIDING EQUIPMENT SOLUTIONS By supplying implements for all these markets



Vineyard



Orchard



Farm



Ranch



Landscape



Construction

GEARMORE INC.



www.gearmore.com
Sales@gearmore.com



This catalog presents a wide selection of equipment for farms, vineyards, orchards, landscapers, construction and municipalities. We supply 230 different implements in 725 various widths and capacities to fit customers exact requirements.

Gearmore provides quality implements, through servicing tractor dealers. It is Gearmore's continuing goal to develop and provide the finest and most reliable equipment at affordable prices.

Please use this catalog when considering your equipment requirements, then visit your local tractor dealer for more detailed product information and pricing.

Please visit our website (www.gearmore.com) to download the latest version of our catalog. We also have expanded literature pages to download. Plus, you can download a copy of parts/operation manuals for current as well as prior models of our implements.

For detailed literature, features, specifications, videos and spare parts manuals on all our products, please refer to our website www.gearmore.com

PRODUCT INDEXPAGE NO.

| | |
|---|---------|
| Aerators | 2 |
| Backhoes, Thumbs..... | 3 |
| Blades..... | 4 |
| Breakers, Hydraulic..... | 5 |
| Cultivators, Arena, Soil Conditioners..... | 6 - 7 |
| Cultivators, In-Row, | 8 - 11 |
| Diggers, PTO..... | 12 |
| Diggers, Hydraulic | 13 |
| Discs..... | 14 - 18 |
| Dusters..... | 19 |
| Dusters, Row Crop, Trailer..... | 20 |
| Forks, Bale Spear..... | 21 - 23 |
| Harrows, Chain..... | 24 |
| Harrows, Rotary, Quick Hitch | 25 |
| Hedger/Toppers/Skirters..... | 26 - 28 |
| Implements, Compact Tractor..... | 29 |
| Implements, Construction - Includes: | |
| Compaction Wheels, 4-in-1 Bucket, | |
| Sifting Bucket, 3-Point Trencher..... | 30 |
| Implements, Various, Includes: | |
| Ripper Bars, Mixer, 3-Pt. Roller, Pull | |
| Type Rollers, Tooth Bars, and | |
| Skid Steer Plates..... | 31 |
| Loaders, Implements & Hyd. Kits | 32 |
| Mowers/Shredders, Flail..... | 33 - 39 |
| Shredders, Hydraulic & Brush Processor..... | 40 |
| Mowers, Rotary..... | 41, 42 |
| Planters | 43, 44 |
| Rakes, Basket..... | 45 |
| Rakes, Landscape, Ridgers | 46 |
| Rippers..... | 47 - 49 |
| Scrapers, 3-Point, Top & Tilt Kits..... | 50 - 54 |
| Scrapers, Corral | 55 |
| Scrapers, Drag & Grading | 56, 57 |
| Scrapers, Laser, Grader Blade | 58 - 60 |
| Skid Steer Attachments, Disk Mulcher.. | 61 - 63 |
| Sprayers, Boom..... | 64 - 67 |
| Sprayers, Air Blast | 68 |
| Sprayers, Venturi, 3-Point | 69 - 73 |
| Sprayers, Venturi, Trailer..... | 74 - 77 |
| Sprayers, Wrap-A-Round | 78 |
| Sprayers, Row Crop Air Boom | 79 |
| Spreaders, Spinner..... | 80 - 82 |
| Spreaders, Pendulum | 83 |
| Spreaders, Manure..... | 84 |
| Sweepers | 85 |
| Tillers, Incorporators..... | 86 - 90 |
| Top & Tilt Kits | 50 |
| Tree Sawhead | 91 |
| Trailers, Dump..... | 92 |
| Vineyard Implements, Includes: | |
| Vine Trimmers, Leaf Removers, | |
| Prepruners | 93 - 99 |
| Worksaver Implements, Includes: | |
| Grapple Buckets, Post Drivers, Concrete | |
| Mixers, Grader Blades..... | 100 |



LARGEST INVENTORY OF IMPLEMENTS ON THE WEST COAST - "OUR FACILITY HAS OVER 2 ACRES UNDER ROOF, OVER 93,000 SQ. FT., ON 5 ACRES OF LAND."

ASSEMBLY AREA

AERATORS

Advanced Aeration Systems - 3 Pt. & Pull type turf aerators



Reduced runoff

Increased microbial activity

Deeper root growth

Increased fertilizer utilization

Aerated Soil

Air and water move together in the soil

This is a fast, effective, low cost method to keep the soil surface open and minimize compaction without disrupting use of the turf area. As surface compaction is a continuous problem, caused by both use (foot traffic) and maintenance (mowing), venting aeration should be scheduled as often as possible to be effective. AerWay's complete line of **Turf Aerators** feature 5 different tine rotors to handle your exact requirements. The polyethylene built-in ballast tanks, when filled with water, obtain maximum tine penetration. Some of the popular options are: smoothing rear roller, tine spacings from 4 to 7.5 inches.

| Width | Approx. H.P. w/Ballast | 3-Point Weight | 3-Point Wt. w/Ballast | Pull Type Weight | Pull Type Wt. w/Ballast |
|-------|------------------------|----------------|-----------------------|------------------|-------------------------|
| 45" | 20 - 30 | 977 lbs. | 1627 lbs. | 1194 lbs. | 1844 lbs. |
| 60" | 25 - 40 | 1143 lbs. | 2000 lbs. | 1437 lbs. | 2300 lbs. |
| 75" | 30 - 45 | 1223 lbs. | 2263 lbs. | 1587 lbs. | 2627 lbs. |
| 90" | 40 - 65 | 1398 lbs. | 2648 lbs. | 1753 lbs. | 3000 lbs. |

Built By:


AerWay®



Shattertine®



Sportstine®



Finetine®



Coring Tine®



Super Fine Tine®

BACKHOES

Built by Bradco - 3-Pt hitch or 4-pt sub frame mount

| Model # | 365 | 490 | 3509 | 3511 |
|------------------------------|-----------|-----------|-----------|-----------|
| Max. digging depth: | 6' 4" | 8' 5" | 9' 8" | 11' 1" |
| Dig. depth (2') flat bottom: | 6' 4" | 8' 0" | 9' 7" | 11' 0" |
| Dig. depth (8') flat bottom: | N/A | 4' 4" | 8' 3" | 9' 11" |
| Loading height: | 4' 7" | 5' 3" | 6' 10" | 8' 0" |
| Loading reach: | 3' 10" | 4' 10" | 4' 2" | 5' 0" |
| Reach from swing pivot: | 9' 0" | 10' 7" | 12' 9" | 14' 5" |
| Stabilizer spread op. pos: | 9' 3" | 7' 6" | 7' 11" | 7' 11" |
| Stabilizer below grade: | 10" | 10" | 16" | 16" |
| System relief valve setting: | 2250 PSI | 2750 PSI | 2100 PSI | 2100 PSI |
| Digging force bucket cyl: | 2599 lbs. | 2895 lbs. | 4768 lbs. | 4768 lbs. |
| Digging force dipper cyl: | 1358 lbs. | 2358 lbs. | 2162 lbs. | 2567 lbs. |
| Bucket & swing arc rotation: | 180° | 180° | 180° | 180° |



MODEL 365 SHOWN
PTO pump kits available for 365 and 490 backhoes

Our complete line of tractor mounted **Backhoes** were designed with the strength and features of construction backhoes. Available in 3-point hitch or sub-frame mount; makes it easy to install when trenching projects are required. The large operator area allows for easy entry and comfortable operation.


- 180° Dual-cylinder swing with internal hydraulic cushioning provides smooth operation & maximum power where needed
- Built from high-strength T1 steel to minimize weight and increase strength for durability
- Standard swing speed control to adjust swing speed
- Inline filter and check valve insures longer valve life and less maintenance
- High capacity buckets provide more volume per cycle - widths from 8" to 36" depending on size of backhoe

ADJUSTABLE THUMB

Lets your backhoe curl cylinder perform the "Clam" action

The **Adjustable Thumb** is designed to increase the productivity and versatility of your backhoe or mini-excavator. Ideal for landscapers and contractors. Dig and load with the same machine. These rugged built thumbs fit most compact tractor backhoes, 3-point agricultural backhoes, skid steer backhoes, small excavators, and commercial backhoes. Designed to do a wide range of material handling jobs such as: land clearing, demolition work, brush removal, and pipe placement. The thumb is also handy for the loading and unloading of rocks, railroad ties, etc. A qualified welder must complete the installation.

- "Claws" are made of high strength T-1 steel
- 2 Pin adjustable working position for a variety of material
- Folds flat against the dipper boom for storage
- Mounting requires welding unit to backhoe or mini-excavator dipperstick



Working Pos. #1

Storage Position

Working Pos. #2

| Model No: | GAT-50 | GAT-100 | GAT-200 | GAT-300 |
|---|------------|------------|------------|------------|
| For buckets measuring from pivot pin to end of teeth: | Up to 17" | 18" to 22" | 24" to 29" | 35" to 44" |
| Base mounting plate: | 3 1/2"x19" | 4"x18" | 5"x21" | 7"x38" |
| Thumb width: | 4 3/4" | 5 1/2" | 7 1/2" | 12" |
| Weight: | 45# | 60# | 110# | 280# |



CAUTION: When lifting heavy objects, never exceed the lift capacity of the backhoe or mini-excavator

REAR BLADES

"GB" Series - 3-Point hitch 5' to 10' widths

GB5/GB6



GB60/GB70



GB75/GB85



GB800/GB900/GB1000



The **GB5 & GB6 Rear Blades** for up to 30 HP tractors are the answer for compact tractor earth-moving requirements. They are the most versatile rear blades on the market today, as all of the standard features normally found only on large expensive rear blades, are standard on the Gearmore Rear Blade. Tilt, angle, offset, and reverse are easy to adjust so that any grading or ditching operation may be accomplished.

The **GB60 & GB70 Rear Blades** are for any mid-size tractor up to 50 HP. These blades feature "Beam Swing" offset, which allows the heavy 4" x 4" beam to swing right or left to obtain maximum offset.

The **All Manual or Hydraulic Adjustment GB75 & GB85 Rear Blades** are the answer to low cost, medium horsepower (up to 95 HP), earth moving requirements. Change ditching or grading angles by just pulling a pin.

The **Hydraulic GB800, GB900, & GB1000 Rear Blades** are for high horsepower (up to 125 HP) earth-moving requirements. These blades are available in full manual or any combination of manual/hydraulic functions. The heavy duty frame is rugged and reliable, assuring years of trouble-free use.

All GB series rear blades have ½" x 6" reversible cutting edges. The GB5/6 and GB60/70 have a 4" x 4" steel tube main beam with a 2" solid round king pin. The GB75/85 have a 5" x 5" steel tube main beam with a 3" solid round king pin, and the GB800/900/1000 have a 6" x 8" steel tube main beam with a 4" solid round king pin.

| Specs: | 3-Pt. | Angle | Tilt | Offset | Wt. |
|--------|---------------|------------|------------|------------|-------|
| GB5 | Cat. 1 | 45° R or L | 14° to 25° | 6" R or L | 260# |
| GB6 | Cat. 1 | 45° R or L | 14° to 25° | 6" R or L | 275# |
| GB60 | Cat. 1 | 45° R or L | 14° to 25° | 35" R or L | 360# |
| GB70 | Cat. 1 | 45° R or L | 14° to 25° | 35" R or L | 380# |
| GB75 | Cat. 2 Clevis | 50° R or L | 20° | 40" R or L | 770# |
| GB85 | Cat. 2 Clevis | 50° R or L | 20° | 40" R or L | 800# |
| GB800 | Cat. 2 Clevis | 30° R or L | 14° | 30" R or L | 1105# |
| GB900 | Cat. 2 Clevis | 30° R or L | 14° | 30" R or L | 1155# |
| GB1000 | Cat. 2 Clevis | 30° R or L | 14° | 30" R or L | 1215# |

HYDRAULIC BREAKERS

Low Cost - High Production


KEY POINTS:

- Only 2 moving parts
- Noise reduction
- Gas fired
- Durable side plates and housings
- Auto shut-off
- 2 Year warranty
- Large tool diameter
- Shock isolation

Paladin's New Strike Force Breakers provide exceptional performance and reliability for a variety of demolition tasks. From small excavation projects to the toughest demolition jobs, Paladin's Strike Force Breaker series has a smooth, powerful operation for maximum output energy and efficiency. Strike Force Small Mounted Breakers are ideal for mini excavators, skid steer loaders and compact backhoes for jobs that need a high breaking capacity.

FEATURES:

- 2 Popular sizes - 500 or 750 ft./lbs.. of impact energy
- Piston and cylinder designed to transfer high shockwaves
- Unique as breakers have only two moving parts
- Very easy to service and maintain
- 4 Different tool points are available -moil is standard options are - chisel, cone and blunt
- All breakers come standard with 2moil tools and extra seal kit
- Mounting brackets are available for skid steer, mini excavators and compact backhoes



Chisel Cone Blunt Moil



*Breaker in action
skid steer mount*

| | SFB500 | SFB750 |
|---------------------------------|-------------|-------------|
| Working weight | 637 | 747 |
| Impact energy class | 500 | 750 |
| Impact rate (blows/min.) | 640-1470 | 620-1150 |
| Operating pressure (PSI) | 1595-2120 | 1565-2175 |
| Relief pressure (PSI) | 2320-2610 | 2320-2610 |
| Oil flow (gal./min.) | 10.0-21.9 | 11.9-21.9 |
| Tool diameter (inches) | 2.63 | 2.67 |
| Pressure line size (inches) | 3/4 | 3/4 |
| Return line size (inches) | 3/4 | 3/4 |
| Carrier weight excavator (lbs.) | 5070-13,227 | 7054-15,873 |

| Model No. | Description | Ft / Lbs Energy | Wt. |
|-----------|--|-----------------|------|
| SFB500 | Hydr. breaker <u>less</u> mtg. bracket | 500 | 637# |
| SFB750 | Hydr. breaker <u>less</u> mtg. bracket | 750 | 747# |

Built By:

PALADIN

NOTE: Breakers are available up to 12,000 impact energy

CULTIVATORS

One pass system for re-conditioning arenas

Arena-Vator III

SHOWN WITH
OPTIONAL SHANKS

Cat. 1
A.S.A.E.
Quick Hitch
Compatible



The *Arena-Vator III* is a highly versatile tool designed for a variety of arena surfaces. The new frame design will accept scarifier shanks that break up hard ground and can be equipped with a number of accessories to meet individual requirements. The AV-3 is designed to renovate and condition horse arenas and tracks in a single pass. It produces a firm, yet giving surface that provides the securest footing for your horses. Available in 4', 5', 6', 7', & 8' sizes. The standard unit is equipped with two rows of S-tine shanks with reversible points which loosen and cultivate the soil, an adjustable pipe leveler for leveling the soil, and a 12" diameter spiral rod rear roller to gauge the depth and pack the soil to provide a uniform finish.

OPTIONS:

- ~ Scarifier Shanks
- ~ Gauge Wheels
- ~ Hitch to convert 3-point to pull type, 4' and 5' only
- ~ Mesh rear roller in lieu of spiral rod roller

FEATURES:

- Two rows of S-tines 1 1/4" x 3/8" x 22" long with reversible and replaceable points
- Adjustable 4" diameter pipe leveling tube
- 12" Diameter spiral rod rear roller with turnbuckles for easy adjustment
- Cat.1, 3-point hitch on 4', 5', 6', and 7' models
- Cat. 1 & 2, 3-point hitch on 8' model

OPTIONS



Pull Hitch



Mesh Roller



Gauge Wheel

SPECIFICATIONS:

| MODEL NO. | DESCRIPTION | WEIGHT |
|-----------|---------------------------------|----------|
| AV3-4 | 4' Arena-Vator III w/11 S-Tines | 400 lbs. |
| AV3-5 | 5' Arena-Vator III w/13 S-Tines | 480 lbs. |
| AV3-6 | 6' Arena-Vator III w/15 S-Tines | 550 lbs. |
| AV3-7 | 7' Arena-Vator III w/17 S-Tines | 660 lbs. |
| AV3-8 | 8' Arena-Vator III w/19 S-Tines | 745 lbs. |

CULTIVATORS


Soil Conditioners - Tills, levels, & finishes soil in a single pass

This Gearmore implement combines three different operations in order to obtain the maximum in soil conditioning. First the vibrating "S" tines break up the ground, then the spring loaded spike tooth bar levels and breaks up clods. The final operation is the spring loaded 12" diameter crumbler roller, which mulches and finishes leveling the soil. These Soil Conditioners are ideal for vineyards, orchards, nurseries, berries and general field work.



GSC10 With 7" Sweeps

CAT I
A. S. A. E.
QUICK
HITCH
COMPATIBLE



**1 3/8" Reversible
Point or 7" Sweep**

FEATURES:

- 20" High clearance "S" tines to penetrate and till up to 7" deep
- "S" tines are heavy duty 1/2" x 1 3/4" spring steel
- Heat-treated, 3/4" x 11" spikes on 6" centers
- Spring loaded, 12" diameter rolling crumbler with serrated bars angled to finish mulching the soil
- Tapered frame permits traveling through vegetation without damaging it
- Tapered rolling crumbler yokes, on all models, guide material around baskets
- Easy to adjust and operate
- Travel speeds up to 8 miles per hour
- Minimum investment cost and low maintenance
- Total soil mixing also causes faster water penetration to the root zone
- Completely mixes soil, does not fold it over or move it to the side like a disc
- Leaves ground perfectly level, as ridges are knocked down and holes are filled-in



GSC6

SPECIFICATIONS:

| MODEL NO. | WIDTH | "S" TINE BARS | NO. OF "S" TINES | NO. OF TEETH | ROLLING CRUMBLERS | WT. |
|-----------|-------|---------------|------------------|--------------|-------------------|-------|
| GSC4 | 4' | 2 | 7 | 8 | 1 - 4' | 475# |
| GSC5 | 5' | 3 | 9 | 10 | 1 - 5' | 620# |
| GSC6 | 6' | 3 | 11 | 12 | 1 - 6' | 800# |
| GSC7 | 7' | 3 | 13 | 14 | 1 - 7' | 900# |
| GSC8 | 8' | 3 | 15 | 16 | 1 - 8' | 1000# |
| GSC10 | 10' | 3 | 19 | 20 | 2 - 5' | 1300# |
| GSC12 | 12' | 3 | 23 | 24 | 2 - 6' | 1620# |
| GSC15 | 15' | 3 | 29 | 30 | 3 - 5' | 1900# |

Cultivators 4 to 7 feet are Cat. 1 - Cultivators 8 to 15 feet are Cat. 2

CULTIVATORS

Effective implement for weed free vineyard rows



**SHOWN W/ OPTIONAL
POWER HARROW**

Our One Row In-Row Cultivator is a very effective tool for under vine maintenance.

First, the straight shank cuts a furrow in front of the blade shaft to penetrate the soil for the cutting blade. Then the blade undercuts weeds, while at the same time loosens and turns back the soil. The sensor rod hydraulically retracts the cutting blade around the base of the vines without damaging them. Blades have an override system to retract to avoid obstruction.

The blades are excellent for working hard soils at speeds up to 5 miles per hour depending on field conditions.

The Cultivator has a number of unique features: combination front and rear Cat. 1 & 2 quick hitches for mounting of the front or rear of tractors, large adjustable floatation tires, handy joystick controls, and dual screw adjustable parking stands.

FEATURES:

- Dual Cat. I and II ASAE 3-point quick hitches for mounting front or rear on tractors
- Heavy double square tubing frame with telescoping inner tubing
- Hydraulic cylinder for spread row from 6 to 8 feet
- Adjust sensor blade retraction rod
- The blade is 24" (620 mm) long
- Screw jack adjustable gauge wheels with tires
- The gauge wheel extends with the blade assembly for better depth control and stability
- Electro hydraulic joystick controls with button to retract blades to avoid obstructions
- Joystick is mounted with magnetic base for easy positioning from cultivator to tractor

- Cultivators come complete with hydraulic hoses and JIC fittings
- Straight shank with replaceable point for opening the soil for the blade
- Dual adjustable parking stands
- For tractors 40 to 60 horsepower
- Tractor hydraulics require min. 6 G.P.M.

OPTION:

HYDRAULIC DRIVEN POWER HARROW with 3 replaceable blades, retracts with the cutting blade.

Note: Then the tractor requires min. 9.5 G.P.M.

Note: Some tractor hydraulic systems may require a hose for return to sump (zero back pressure)

SPECIFICATIONS:


| MODEL # | FOR ROW WIDTH | MIN. OVERALL WIDTH | MAX. OVERALL WIDTH | WEIGHT |
|----------|---------------|--------------------|--------------------|--------|
| DHS-1000 | 6' to 8' | 68" | 88" | 625# |

Note: Model DHS-1000E same specs except no tilt and joystick

Built By: **SICMA**

CULTIVATORS

Effective tool for organic weed control



Shown with 20" blades,
standard is 24" long blades
with 4 weed lifter brackets

Our two row In-Row Cultivator is a very effective tool for under vine maintenance. First, the notched coulters cut a furrow in front of the blade shaft to penetrate the soil for the cutting blades. The in-row blades undercuts weeds, while at the same time loosens and turns back the soil. The sensor rod hydraulically retracts the cutting blades around the base of the vines without damaging them. Blades have an override system to retract to avoid obstruction. The blades are excellent for working hard soils at speeds up to 5 miles per hour depending on field conditions.

FEATURES:

- Dual Cat. I and II ASAE 3-point quick hitches for mounting front or rear on tractors
- Heavy double square tubing frame with telescoping inner tubing
- Dual hydraulic cylinders for spread widths
- Blades are 24" (620 mm) long and reversible to double the life
- Screw jack adj. dual gauge wheels with tires
- Electro hydraulic joystick controls with button to retract blades to avoid obstructions
- Joystick is mounted with magnetic base for easy positioning from cultivator to tractor
- Adjustable notched coulters blades, 13 ¾" (350 mm) diameter for opening the soil for the blades
- The gauge wheels extend with the blade assembly for better depth control and stability
- Cultivators come complete with hydraulic hoses and JIC fittings
- Tractor minimum hydraulic requirement - 6.6 GPM
- For tractors 50 to 90 horsepower

Note: Some tractor hydraulic systems may require a hose for return to sump (zero back pressure)

SPECIFICATIONS:

| MODEL # | FOR ROW WIDTHS | MIN. OVERALL WIDTHS | MAX. OVERALL WIDTHS | WEIGHT |
|---------|----------------|---------------------|---------------------|--------|
| DHD1000 | 8' to 11' | 8' - 3" | 11' - 6" | 880# |
| DHD1400 | 9' to 12' | 9' - 6" | 12' - 10" | 930# |

Built By: **SICMA**

CULTIVATORS

Featuring self-contained hydraulic system



Shown with optional
notched coulters, straight
shanks standard

Our In Row Cultivator has a self-contained hydraulic system which eliminates over heating of the tractor hydraulics. These Cultivators are very effective tools for under vine maintenance. The Power Harrows are mounted on top of the cutting blades breaks up clods and pulls out weeds. The Harrow's three rotating blades obtain a final mix and levels the soil. The sensor rod hydraulically retracts the cutting blades and harrow around the base of the vines without damaging them. The blades/harrows have a joystick override system to retract to avoid obstructions. The Cultivator has a number of unique features: combination front and rear Cat. 1 & 2 quick hitches for mounting on the front or rear of tractors, self-contained hydraulic system, and handy joystick controls.

Built By: **SICMA**

SPECIFICATIONS:

| MODEL # | FOR ROW WIDTHS | MIN. OVERALL WIDTHS | MAX. OVERALL WIDTHS | WEIGHT |
|---------|----------------|---------------------|---------------------|--------|
| DH21000 | 8' to 11' | 8' - 3" | 11' - 6" | 1010# |

FEATURES:

- Dual Cat. I and II ASAE 3-point quick hitches for mounting front or rear on tractors
- Self-contained hydraulic system with 13 gallon reservoir and 7.8 gallons per minute pump
- Built in oil cooler with fan
- Dual hydraulic cylinders for row widths from 8 to 11 feet
- The blades are 24" (620 mm) long and reversible to double the life
- The blades are fitted with hydraulic tilt cylinders that adjusts from horizontal 20° up and 20° down
- Electro hydraulic joystick controls with button to retract blades to avoid obstructions
- Depth adjustable straight shank with point for opening the soil for the blade
- Cultivators come complete with hydraulic hoses and JIC fittings
- Dual adjustable parking stands
- Unit is powered by tractor P.T.O.
- For tractors 50 to 90 horsepower

OPTION:

- ~ Adjustable notched coultter blades 13 ¾" (350 mm) diameter in lieu of straight shanks

POWER HARROW:

- ~ Hydraulic driven power harrow retracts with the blade
- ~ 3 Replaceable blades - 11.8" (300 mm) diameter

CULTIVATORS

In-Row Tools - For all cultivators



Rotary Hoe - 16\"
Retractable



Rotary Mower - 24\"
Retractable



Power Disc - 3
Blades Retractable



Back Fill Disc - 14\", 2 Blades

The Spedo is an effective tool for under vine maintenance. This in-row blade undercuts weeds, while at the same time loosening and turning back the soil. The cutting blade hydraulically retracts around the base of the vine without damage. The unit was developed for one side weeding only, so as to operate at higher speeds with safe, accurate control.

- Cat. I and II, 3-pt. hitch
- Manual sliding tube to adjust for different row widths
- Hydraulic blade trip retraction system
- The blade is equipped with hydraulic tilt, PTO hydraulic pump, 14J only
- Coulter disc
- Dual gauge wheels with mud scrapers

| Model No: | Description | Row Width | Weight |
|-----------|--|-----------|--------|
| MIP01010J | In-Row Cultivator, blade mount only using tractor hydraulics | 6' to 12' | 700 # |
| MIP01014J | In-Row Cultivator with self contained hydraulic system, add implements | 6' to 12' | 800 # |

Very effective tools for under vine maintenance. The Rotary Hoe undercuts weeds, while at the same time loosening and turning back the soil. The tools hydraulically retract around the base of the vine without damage. Also, standard is a remote control joystick which allows the operator to retract the tools when required. Rear mounted double tool carrier with auto retraction. Features a self contained hydraulic system and oscillating self leveling heads with double effect heads. The joystick controls the working tool retraction override, working tools power ON/OFF.

- Cat. II, 3-point hitch
- Hydraulic sliding tube to adjust for different row widths
- Sensor rod for automatic implement retraction
- Electric control box for operating hydraulic functions and overrides to avoid obstructions
- Dual steel gauge wheels with mud scrapers and independent height control
- Dual rubber depth control wheel
- All required hoses are included
- Requires one tractor rear remote for width control cylinders
- Self contained hydraulic system, PTO driven, 450 R.P.M.
- Oil reservoir 21 gallon, 4 separate pumps, and oil cooler

2 ROW CULTIVATOR



Built By: **SPEDO**

| Model No: | Description | Row Widths | Wt. |
|-----------|---|------------|------|
| MIPN1014J | In-row cultivator w/self contained hydraulic system, add implements | 8' to 11' | 800# |

DIGGERS

3-Point Post Hole Diggers - 4 Models to match your H.P.

**MODEL 720
HEAVY DUTY DIGGER**



**MODEL 500
STANDARD DUTY DIGGER**



**MODEL 300 FOR
SUB-COMPACT TRACTORS**



*Shown with optional
parking stand*

DIG DEEPER, FASTER & SMARTER

The **Work saver Post Hole Diggers** are engineered to allow the operator to dig deeper, faster and smarter. Work saver's line of PTO powered diggers offer time saving convenience with outstanding reliability. Shear bolt protected driveline is coupled to a rugged gearbox featuring tapered roller bearings and spring loaded seals for extended service life. Large 2" output shaft has two bolt auger connection for reliable power transfer. All job matched augers utilize fishtail center points with double flighting on the first.

**MODEL 925
INDUSTRIAL DIGGER**



| Model No: | Horsepower | Cat. | Max. Auger Diameter | Auger Length | Weight |
|-----------|---------------|------|---------------------|--------------|--------|
| 300 | Under 25 H.P. | I | 12" | 30" | 149# |
| 500 | Under 35 H.P. | I | 12" | 42" | 160# |
| 720 | 25 - 65 H.P. | I | 24" | 42" | 206# |
| 925 | 40 - 95 H.P. | I | 30" | 42" | 220# |

Optional down force kit available

FEATURES:

- 3-pt. hitch mounted
- 2" Output shaft
- Replaceable fishtail auger point
- Rugged 540 RPM gearbox
- Shear pin drive
- 3 Boom positions
- Standard duty single flight and heavy duty double flight augers
- Optional parking stand

Built By:

WORKSAVER

The **"X" Series** is the most trouble free hydraulic digger on the market today. These diggers feature an "in-line" sealed planetary gear reduction drive design. This clean, effective system ensures long, trouble free usage. All "X" Series models feature reverse rotation for quick backout when obstructions are encountered. The system's hydraulic relief valve protects the digger from damage when an auger hits large immovable objects.

FEATURES:

- 7 Models to match tractor GPM's from 5 to 60
- All units feature planetary gear reduction, except D450
- High torque motors ensure digging through the toughest of conditions
- Adapter plate mounting on most popular skid steers, backhoes, loaders, etc.
- 3 Models of augers designed to match your soil conditions

| Model No: | D450 | X975 | X1475 | X1975 | X2475 | X4575 | X5075 |
|-----------------------|--------|-------------------|-------------------|-------------------|-------------------|--------|--------|
| Min. Hyd. Flow GPM: | 5 | 6 | 10 | 15 | 20 | 22 | 28 |
| Max. Hyd. Flow GPM: | 10 | 15 | 25 | 30 | 35 | 36 | 40 |
| Max. Auger Diameter: | 12" | 24" | 30" | 36" | 36" | 48" | 48" |
| Output Shaft Options: | 2" Rd. | 2 1/16" 2" Hex | 2 1/16" 2" Hex | 2 1/16" 2" Hex | 2 1/16" 2" Hex | 2" Hex | 2" Hex |


Medium duty, heavy duty and rock augers are available

Auger extensions available in 2" & 2 1/16" round, and 2" hex in lengths of 24", 48", & 72"



ROCK AUGERS - "HDR" STYLE AUGERS

For solid, frozen ground and compacted soils

| "HDR" Auger | Dia. | Tooth Qty. |
|--|------|------------|
|  | 6" | 6 |
| | 9" | 8 |
| | 12" | 12 |
| | 18" | 18 |
| STD. FEATURES | | |
| <ul style="list-style-type: none"> • Bullet style teeth & fabricated boring head • HD Single flight - 3/4" thick bottom flight • 2" Hex collar ONLY • Available in 4' length | | |


STANDARD FEATURES FOR "HDC" STYLE AUGERS:

- HD Cast steel boring head
- Hardened drive-in teeth
- Hardened fishtail point
- HD double fighting
- Collars - 2" round, 2 1/16" round & 2" hex
- Available in 3', 4', 5', & 6' lengths
- Stocked in 4' length

High Quality Construction AUGERS


HEAVY DUTY - "HDC" STYLE AUGERS

For difficult ground conditions

| "HDC" Auger | Dia. | Tooth Qty. |
|---|------|------------|
|  | 6" | 2 |
| | 8" | 4 |
| | 9" | 4 |
| | 10" | 4 |
| | 12" | 4 |
| | 15" | 6 |
| | 16" | 6 |
| | 18" | 6 |
| | 20" | 6 |
| | 24" | 8 |
| | 30" | 10 |
| 36" | 12 | |

MEDIUM DUTY - "HDF" STYLE AUGERS

For light to moderate ground conditions

| "HDF" Auger | Dia. | Tooth Qty. | |
|---|------|---------------------|---|
|  | 6" | 2 | |
| | 8" | 2 | ● Fabricated boring head |
| | 9" | 3 | ● Hardened bolt-on teeth |
| | 10" | 3 | |
| | 12" | 4 | ● Hardened fishtail point |
| | 15" | 5 | |
| | 16" | 5 | ● HD dbl fighting |
| | 18" | 6 | ● Collars-2" rnd., 2" hex, & 2 1/16"rnd |
| | 20" | 6 | |
| | 24" | 8 | ● 3', 4', 5' & 6' lengths available |
| | 30" | 9 | |
| 36" | 11 | ● 4' Length stocked | |

Built By:

McMILLEN®

DISCS, TANDEM

"DH" Series - Compact discs for general useage



Cat. I
A.S.A.E.
Quick Hitch
Compatible

FEATURES:

- Cat. I, 3-point ASAE quick hitch
- Frame and gang beams - 3" x 3" heavy tubing
- 18" Notched front and plain rear blades on 7 1/2" spacing
- Axles are 1" square high carbon steel
- Axle are triple sealed, self-aligning ball bearings
- Gangs adjustable with 7, 14 and 21 degree settings
- Bearing hangers - 3/8" plate reinforced
- Handles for easy gang adjustment

| Model No: | Cut. Width | H.P. Rating | Blade Dia. | No. of Blades | Wt. |
|-----------|------------|-------------|------------|---------------|------|
| DH30-60C | 60" | 35 HP Max. | 18" | 16 | 735# |
| DH30-72C | 72" | 45 HP Max. | 18" | 20 | 815# |
| DH30-84C | 84" | 55 HP Max. | 18" | 24 | 885# |

DISCS, TANDEM

FEATURES:

- Cat. I & II, 3-pt. hitch, ASAE quick hitch
- 3/16" x 22" notched front and plain rear blades
- Front & rear gangs adjustable to 7, 14 or 21 degree settings
- 1 1/8" high carbon square axles
- 7 1/2" long cast spool spacers



**HEAVY DUTY
22" BLADES**

Cat. I & II
A.S.A.E.
Quick Hitch
Compatible

| Model No: | Cut Width | Blade Dia. | No. of Blades | Wt. |
|-----------|-----------|------------|---------------|-------|
| T1622 | 5' - 6" | 22" | 16 | 1100# |
| T2022 | 6' - 6" | 22" | 20 | 1230# |
| T2422 | 7' - 6" | 22" | 24 | 1515# |
| T2822 | 8' - 6" | 22" | 28 | 1660# |

FEATURES:

- Cat. II, 3-point quick hitch
- Heavy duty frame
- 24" Notched front and plain rear blades
- 9" Blade spacing
- 1 1/2" Square gang axles
- Double sealed flange mounted bearings
- Adjustable rear gang
- Steel spacer spools

DISCS, OFFSET



| Model No: | Cutting Width | No. of Blades | Weight |
|-----------|---------------|---------------|--------|
| GO24-60 | 6' - 0" | 16 | 1120# |
| GO24-69 | 6' - 9" | 18 | 1170# |
| GO24-76 | 7' - 6" | 20 | 1405# |
| GO24-83 | 8' - 3" | 22 | 1560# |
| GO24-90 | 9' - 0" | 24 | 1600# |

Built By: **BWImplement**

DISCS, TANDEM

"GV" Narrow Row Series - HD for years of troublefree useage

Narrow row crops like grapes, berries, pole tomatoes, etc., also require heavy duty tillage tools. Our **Narrow Row Tandem Disc** fits those requirements. This disc is excellent for knocking down weeds, leveling and mixing in residue. The 22" diameter notched front blades aid in cutting through hard soils, while the rear plain blades give a smooth finish. Flange mounted, double sealed, shielded bearings. A number of options are available, such as: dirt shield fenders, extension blades, bearing guards, special low position 3-point hitch, and 1" x 3" center shank.



SPECIFICATIONS:

| Model No: | Row Width | No. of Blades | Frame Width | Cutting Width | Weight |
|-----------|-----------|---------------|-------------|---------------|--------|
| GV-5R | 5' (60") | 8 | 48" | 32" to 44" | 1200# |
| GV-6R | 6' (72") | 12 | 57" | 56" to 62" | 1420# |
| GV-8R | 8' (96") | 16 | 75" | 68" to 80" | 1745# |

Our heavier duty series of **Reversible Vineyard Discs** were designed for maximum strength and durability. The frame was built with heavy wall tubing for additional weight in tough soil conditions. The disc has 24" diameter plain blades front and rear. The 3-point hitch is Cat. II quick hitch, trunnion mounted bearings and 1" x 3" center shank. The reversible hitch can easily be remounted on the opposite end of the disc when required.

DISCS, TANDEM

"GRT" Series - Reversible tandem disc

Cat. II
A.S.A.E.
Quick Hitch
Compatible



SPECIFICATIONS:

| Model No: | Cutting Width | No. of Blades | Weight |
|--------------|----------------|---------------|--------|
| GRT24P-HD-16 | 5' 8" to 7' | 16 | 2160# |
| GRT24P-HD-18 | 7' 2" to 8' 6" | 18 | 2260# |
| GRT24P-HD-20 | 7' 2" to 8' 6" | 20 | 2490# |

Built By:

BWImplement

DISCS, WHEEL

Narrow "VWT" Series - Medium duty, pull type tandem discs



| Model No: | Cut. Width | No. of Blades | Weight |
|-----------|---------------|---------------|--------|
| VWT24-16 | 5' 8" - 7' 0" | 16 | 2480# |
| VWT24-18 | 7' 2" - 8' 6" | 18 | 2600# |
| VWT24-20 | 7' 2" - 8' 6" | 20 | 2680# |
| VWT24-22 | 8' 8" - 9' 8" | 22 | 2720# |
| VWT24-24 | 8' 8" - 9' 8" | 24 | 2800# |

FEATURES:

- Frame:** 4" x 4" x 1/4" Structural tubing
- Gang Frame:** Fully adjustable front to rear
- Hitch:** Self leveling, spring cushioned with hand crank
- Bearings & Axles:** 1 1/2" Square axles w/trunnion mount double lip sealed greaseable bearings with wear shield
- Blades:** 24" x 4.5mm notched or plain
- Spools:** 9" Steel spacer spools & cast iron half spools
- Hydraulics:** 3 1/2" x 8" Cylinder
- Shank:** 1" x 3" Center shank with adjustable footpiece
- Wheel & Tire:** 6 Bolt hub and spindle assy with 9.5L x 15" 8 ply tire

DISCS, WHEEL

Wide "GT Series - Medium duty pull type



| Model No: | Cutting Width | No. of Blades | No. of Wheels | Weight |
|-----------|---------------|---------------|---------------|--------|
| GT-24T | 9' 2" | 24 | 4 | 3300# |
| GT-28T | 10' 8" | 28 | 4 | 3700# |
| GT-32T | 12' 2" | 32 | 4 | 4140# |
| GT-36T | 13' 8" | 36 | 4 | 4360# |
| GT-40T | 15' 2" | 40 | 4 | 4800# |
| GT-44T | 16' 8" | 44 | 4 | 5130# |
| GT-48T | 18' 2" | 48 | 4 | 5610# |

FEATURES:

- Frame:** 4" x 4" x 1/4" Structural tubing
- Hitch:** Self leveling, spring cushioned with hand crank
- Gangs & Bearings:** 1 1/2" Square gang axles with greaseable trunnion mounted, double sealed bearings with wear guards
- Gangs:** Adjustable - front 12° to 22° - rear 9° to 21°
- Blades:** 24" x 6mm notched or plain, 9" spacing
- Scrapers:** Standard, adjustable individually or by gang
- Wheels & Tires:** 4 - 6 Bolt hub and spindle assy. 4 - 9.5L x 15" 8-ply tires
- Hydraulics:** 3 1/2" x 8" Cylinder with depth control and hoses
- Shank:** 1" x 3" Center shank
- Rear Hitch:** Standard equipment

Built By: **BWI**implement

DISCS, WHEEL

Offset Pull Type "300" Series - For light & medium tillage conditions

The **Gearmore 300 Series Offset Discs** are ideal for light and medium tillage conditions. We offer sizes from 4'-6" to 9'-9"; for vineyards, berries, narrow row orchards, general field cultivation, etc. The offset design enables maximum penetration and even tillage of soil. Heavy construction with 4" x 3" x 1/4" frame, 1 1/8" axles, 22 inch diameter blades in notched or plain, self leveling hand crank, and double sealed bearings. Built in the West for tough, western conditions.



SPECIFICATIONS:

| Model No: | G301 | G302 | G303 | G304 | G305 | G306 | G307 | G308 |
|----------------|------------|------------|------------|------------|------------|------------|------------|------------|
| Width: | 4' 6" | 5' 3" | 6' 0" | 6' 9" | 7' 6" | 8' 3" | 9' 0" | 9' 9" |
| No. of Blades: | 12 | 14 | 16 | 18 | 20 | 22 | 24 | 26 |
| H. P. Req'd: | 35 - 45 HP | 35 - 45 HP | 40 - 55 HP | 40 - 55 HP | 45 - 60 HP | 50 - 65 HP | 55 - 70 HP | 60 - 75 HP |
| Weight: | 1300# | 1400# | 1500# | 1600# | 1700# | 1800# | 1900# | 2000# |

DISCS, WHEEL

Offset Pull type "500" Series - For general purpose wheel discs

The **Gearmore Low Profile Offset Discs** are of rugged design for deep tilling in all soil conditions. We offer the most popular widths of 6'-9" to 12', for orchard and general tillage operations. The offset design enables maximum penetration and even tillage of soil. Heavy construction with 1 1/2" square gang axles, 24 inch diameter blades in notched or plain, self leveling hand crank and trunnion mounted, sealed bearings. Built in the West for tough, western conditions.



| Model No: | Cutting Width | No. of Blades | Frame | No. of Wheels | HP Req'd | Wt. Per Ft. | Wt. |
|-----------|---------------|---------------|----------------|---------------|--------------|-------------|-------|
| G501 | 6' 9" | 18 | 4" x 4" x 1/4" | 2 | 50 to 70 HP | 360 lbs. | 2430# |
| G502 | 7' 6" | 20 | 4" x 4" x 1/4" | 2 | 55 to 75 HP | 345 lbs. | 2600# |
| G503 | 8' 3" | 22 | 4" x 4" x 1/4" | 2 | 60 to 80 HP | 335 lbs. | 2800# |
| G504 | 9' 0" | 24 | 4" x 4" x 1/4" | 2 | 65 to 85 HP | 345 lbs. | 3100# |
| G505 | 9' 9" | 26 | 4" x 4" x 1/4" | 2 | 70 to 90 HP | 370 lbs. | 3600# |
| G506 | 10' 6" | 28 | 4" x 6" x 1/4" | 4 | 75 to 100 HP | 390 lbs. | 4100# |
| G507 | 12' 0" | 32 | 4" x 6" x 1/4" | 4 | 80 to 120 HP | 400 lbs. | 4800# |

Add "W" to model number for weed abatement applications

Built By: **BWImplement**

DISCS, WHEEL

Offset "700" Series - For finish tilling in all conditions



The **Gearmore Heavy Duty Offset Finishing Discs** are of rugged design for finish tilling in all soil conditions. We offer the most popular widths of 15'-6" to 22'-3", for general tillage operations. The offset design enables maximum penetration and even tillage of soil. Heavy construction with 1½" square gang axles, 26 or 28 inch diameter blades in notched and plain, self leveling hand crank, and trunnion mounted sealed bearings. Built in the West for tough, western conditions.

SPECIFICATIONS:

| Model No: | Cutting Width | No. of Blades | Frame | No. of Wheels | Tractor HP Req'd | Wt. Per Foot | Weight |
|-----------|---------------|---------------|---------|---------------|------------------|--------------|---------|
| G704-9 | 15' 6" | 42 | 6" x 8" | 4 | 80 to 150 HP | 610 lbs. | 9,140# |
| G705-9 | 16' 0" | 44 | 6" x 8" | 4 | 90 to 160 HP | 580 lbs. | 9,220# |
| G711-9-F | 18' 0" | 48 | 6" x 8" | 4 | 130 to 170 HP | 600 lbs. | 10,800# |
| G712-9-F | 20' 9" | 56 | 6" x 8" | 4 | 150 to 185 HP | 605 lbs. | 12,465# |
| G714-9-F | 22' 3" | 60 | 6" x 8" | 4 | 190 to 220 HP | 580 lbs. | 12,700# |
| G716-9-F | 23' 9" | 64 | 6" x 8" | 4 | 200 to 225 HP | 550 lbs. | 13,000# |

"F" stands for folding models - other widths available upon request

DISCS, WHEEL

HD Offset "900" Series - For heavy tillage operations



SPECIFICATIONS:

| Model No: | Cutting Width | No. of Blades | H.P. Req'd | Weight |
|-----------|---------------|---------------|---------------|---------|
| G903 | 14' 2" | 26 | 145 to 235 HP | 12,150# |
| G904 | 15' 3" | 28 | 160 to 250 HP | 12,530# |
| G905 | 16' 4" | 30 | 170 to 265 HP | 13,200# |
| G906 | 17' 5" | 32 | 180 to 280 HP | 13,600# |
| G907 | 18' 6" | 34 | 190 to 285 HP | 14,850# |

FEATURES:

Frame &

Tongue:

4" x 8" Structural tubing with hand crank

Hitch:

Hydraulic adjusted for easy tractor hook-up

Gangs & Bearings:

2 ¼" Square gang axles with greaseable trunnion mounted triple sealed bearings with additional external seals

Gang Beams: Blades:

8" x 8" Structural tubing
32" Diameter x 9.5 mm notched front and plain rear with 13" spacing

Scrapers:

Heavy duty high tensile steel

Wheels:

Dual with 8 bolt hubs and spindles

Tires:

4 - 12L x 15 8 Ply

Built By: **BWImplement**

MODEL G2V

The **Gearmore Mini Duster** is a simple all gear drive unit. The dust is accurately applied with easy to set application rates. A mechanical agitator insures even flow of material. The wind velocity of 150 MPH achieves maximum coverage. This economy duster is just right for use in narrow vineyards, berries, and other pole crops such as snow peas.

FEATURES:

- Requires only 15 PTO horsepower to operate
- All gear drive for low maintenance
- Mechanical agitation for even flow
- High wind velocity for maximum coverage
- Adjustable distribution nozzles



MODEL S420 & S530

Gearmore Dusters combine simple design with quality craftsmanship. The all-gear drive provides maximum performance with low maintenance. Sulfur is accurately applied with easy to set application rates. The model S530, with a large 400 lb. capacity poly hopper and extended fishtail distributors, is preferred by growers with wide row spacings. The model S420 with 300 lb. capacity poly hopper is the perfect machine for vineyards with narrow row spacings.

FEATURES:

- Polyethylene hopper and cover
- Wrap-A-Round tubular steel frame isolates and supports hopper
- All gear drive for low maintenance
- Mechanical agitation for even flow
- Wind velocities up to 180 MPH for maximum coverage
- Manual rate control allows for setting the pounds per acre
- Adjustable fishtail nozzles



SPECIFICATIONS:

| Model No: | Hopper Capacity | Fan Dia. | Wind Velocity | Row Width | Width | Height | Depth | Fishtail Ext. | Width w/ Fishtails | Wt. |
|-----------|-----------------|----------|---------------|-----------|-------|--------|-------|---------------|--------------------|------|
| G2V | 150 lbs. | 12" | 150 MPH | 4' - 6' | 17" | 42" | 24" | D.N.A. | 40" | 150# |
| S420 | 300 lbs. | 15 3/4" | 150 MPH | 6' - 8' | 37" | 48" | 48" | Optional | 37" | 320# |
| S530 | 400 lbs. | 19 3/4" | 180 MPH | 9' - 12' | 37" | 58" | 48" | Yes | 72" | 390# |
| S530N* | 400 lbs. | 19 3/4" | 180 MPH | 6' - 8' | 37" | 58" | 48" | No | 37" | 380# |

* Same narrow fishtails as S420

DUSTERS, ROW CROP

Hydraulic Folding Boom - High speed turbine fan

5 ROW SHOWN WITH
OPTIONAL PARKING
STANDS



DUSTER FEATURES:

- Cat. I & II, 3-point hitch
- Wind velocities up to 180 M.P.H. at manifold
- Manual rate control allows for setting the pounds per acre
- Mechanical agitation for even flow
- Lever control, reachable from tractor seat, allows operator to turn the dust on and off
- Available in 5, 10, & 12 row, hydraulic foldaway booms
- Adjustable nozzles allows for angling to the foliage

Gearmore Row Crop Sulfur Dusters feature all-gear drive provides maximum performance with low maintenance. Dust is accurately applied with easy to set application rates. The large 400 lb. capacity polyethylene hopper allows dusting of many acres between "re-fills".

The booms are available for 5 to 12 rows with adjustable nozzles to insure accurate dust placement on the plant foliage. Our Row Crop Sulfur Dusters have successfully controlled mildew on strawberries, tomatoes, watermelons, pumpkins, cantaloupes, peppers, cucumbers, and many other crops.

Sulfur has been proven to be the most effective way to control powdery mildew.

| Model No: | Description | Boom Length | Maximum Nozzle Centers | Weight |
|-----------------|---------------|-------------|------------------------|--------|
| S530RC-5HF | 5 Row Duster | 31' 2" | 68" | 400# |
| S530RC-10HF | 10 Row Duster | 31' 2" | 40" | 460# |
| S530RC-10HF-3MT | 10 Row Duster | 41' 2" | 48" | 470# |
| S530RC-12HF-3MT | 12 Row Duster | 41' 2" | 40" | 500# |

DUSTER, TRAILER

High Capacity = Less fill-ups

FEATURES:

- High performance, precision balanced, all-steel centrifugal turbine fan
- Swivel distribution nozzles adjust for vines and trees
- Full hopper length, large diameter agitator feeds spiral conveyor in bottom of hopper
- Tongue length and tire width are adjustable
- Wide angle constant velocity driveshaft
- Application rates from 5 to 100 lbs. per acre
- Separate 8 gallon (30 liter) fresh water safety tank



Our **Trailer Duster** now features new attachments as standard equipment. An electro hydraulic cylinder with control box for adjusting from the tractor. Also, a hydraulic motor to control the speed of the full length spiral conveyor and agitation system. This insures uniform, accurate distribution of the dust.

| Model No: | Hopper Capacity | Min. H.P. | Volume of Air | Air Speed | Height | Width | Length | Tires | Wt. |
|-------------|-----------------|-----------|---------------|-----------|--------|------------|--------|--------------|------|
| MAXI600-SPC | 1000 lbs. | 40 HP | 3180 CFM | 420 MPH | 50" | 50" to 68" | 110" | 9.5Lx15-8Ply | 940# |

Bucket & Trash Forks - Make your loader more productive

Bucket Forks are a quick, easy way to turn your loader bucket into a forklift. Mounts in seconds to most loader buckets without tools. Forks are equipped with handles for ease in mounting and spacing adjustments. Both forks now have baked-on powder coated paint for rust-free durability and long lasting glossy finish.

| Model No: | Capacity (lbs.) | Fork Dimension | Weight |
|-----------|-----------------|----------------|--------|
| 1000 | 1000 lbs. | 2" x 3" x 32" | 90# |
| 2000 | 2000 lbs. | 2" x 3" x 36" | 110# |
| 3000 | 3000 lbs. | 2" x 4" x 42" | 190# |
| 4000 | 4000 lbs. | 2" x 4" x 42" | 220# |
| 6000 | 6000 lbs. | 3" x 5" x 48" | 250# |



BUCKET FORKS

If loader buckets are equipped with bolt-on cutting edges, both the forks on this page are available with wide opening, just add **W** to model number.

| Models: | GTF48 | GTF54 | GTF60 | GTF66 | GTF72 |
|------------------------------|--------|-------|--------|-------|-------|
| Bucket Size: | 48" | 54" | 60" | 66" | 72" |
| Width: | 46" | 52" | 58" | 64" | 70" |
| Tines: | 5 | 5 | 6 | 6 | 7 |
| Approx. Space Between Tines: | 8 1/2" | 10" | 8 1/2" | 10" | 9" |
| Weight: | 160# | 170# | 180# | 195# | 210# |



TRASH FORKS

A loader bucket is great for moving soil, but handling trash is a problem. Our **Trash Forks** are an economical and easy mount solution to this problem. This handy tool will make moving tree branches and other debris an easy task.

BALE SPEARS

Clamp-on - Easily converts bucket to bale spears

These **Clamp-on Bucket Bale Spears** are a quick and handy tool to convert your loader bucket into bale spears. The units have a capacity of 3000 pounds and can handle square or round bales.

- 2 Heavy screw-lock clamp brackets w/zinc plated handle/screw assemblies
- 2" Square, 1/4" wall tubing by 20" long tines
- Clamps fit deep into the bucket for added strength
- Clamping brackets placed near bucket side plates for added strength
- Spear length - 41", diameter - 1 5/8"
- Overall length - 56"
- 1 1/4" Opening for bucket cutting edge

| Model No: | Description | Capacity | Weight |
|-----------|---------------------|-----------|--------|
| CBS-3000 | Pair of Bale Spears | 3000 lbs. | 135# |



All Forks and Bale Spears come with sliding handle screw and swivel locking plate. They are zinc coated for easy operation and to prevent rust.

FORKS


3-Point Mounted - Lift without the expense of a forklift

**ADJ. TINE FORKS
MODEL 3548**




Cat. II
A.S.A.E.
Quick Hitch
Compatible

**ADJ. TINE FORKS
MODEL 1500AT**



Cat. I
A.S.A.E.
Quick Hitch
Compatible

**ECONOMY FORKS
MODEL 1200**



Cat. I
A.S.A.E.
Quick Hitch
Compatible

**STD. DUTY FORKS
MDL. 1500 & 2000-3PT**



Cat. I
A.S.A.E.
Quick Hitch
Compatible

| Model No: | Cap. | Fork Width (center to center) | Fork Thickness | Fork Length | Wt. |
|--------------|-----------|-------------------------------|------------------------------|-------------|------|
| 1200 | 1200 lbs. | 26" | 2"x4"x $\frac{3}{16}$ " tube | 41" | 90# |
| 1500 QH | 1500 lbs. | 26" | 1" x 4" solid | 41" | 160# |
| 2000-3PT QH | 2000 lbs. | 26" | 1 $\frac{1}{4}$ " x 4" solid | 41" | 180# |
| 1500AT | 1500 lbs. | 5" to 26" | 1 $\frac{1}{4}$ " x 4" solid | 41" | 290# |
| 3548 Cat. II | 3500 lbs. | 10" to 36" | 1 $\frac{1}{4}$ " x 4" solid | 48" | 315# |

FORKS, BUCKET

Turns your loader bucket into a forklift

The **Gearmore Bucket Forks** allows you to turn your tractor into a forklift in seconds. Our simple safety lock brackets are welded to your bucket. You then curl down the bucket and drive into the forks. Next level the bucket and the forks lock into place.



- Mounts to loader bucket in seconds
- Patented forming process increases the bend and heel thickness by 20%
- Tines made of special boron steel and fully heat treated after bending
- Heavy plate mounting brackets
- Rods made of 4140 ground and polished, high carbon steel
- Extra long tine taper for easier load entry
- Adjustable tine spacing
- Forks have a safety rating of 3 times the stated capacity (except 1200#)



**Safety Lock
System**

| Model No: | 12 UNIV | 25 UNIV | 40 UNIV | 60 LB | 60 UNIV | 80 UNIV | 110 UNIV* |
|-------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------|
| Max. Load Cap. Tine Ct: | 1200 lbs. | 2500 lbs. | 4000 lbs. | 6000 lbs. | 6000 lbs. | 8000 lbs. | 11000 lbs. |
| Bucket Opening up to: | 23" | 32" | 40" | 40" | 49" | 54" | 67" |
| Tine Height**: | 31" | 38" | 46" | 46" | 55" | 61" | 73" |
| Tine Length: | 36" | 36" | 42" | 46" | 46" | 48" | 60" |
| Adj. Width: | 60" | 60" | 72" | 72" | 72" | 72" | 84" |
| Weight: | 225# | 240# | 330# | 400# | 435# | 690# | 960# |
| Rod Size: | 1 $\frac{1}{4}$ " x 5' | 1 $\frac{1}{4}$ " x 5' | 1 $\frac{1}{4}$ " x 6' | 1 $\frac{1}{2}$ " x 6' | 1 $\frac{1}{2}$ " x 6' | 1 $\frac{3}{4}$ " x 6' | 2" x 7' |
| Tine Size: | 1" x 4" | 1 $\frac{3}{8}$ " x 4" | 1 $\frac{3}{8}$ " x 4" | 1 $\frac{3}{4}$ " x 4" | 1 $\frac{3}{4}$ " x 4" | 2" x 5" | 2" x 6" |
| No. of Brackets: | 3 | 3 | 4 | 4 | 4 | 4 | 4 |

* By adding a 3rd tine, capacity is 16,500 lbs. and by adding a 4th tine, capacity is 22,000 lbs.

** Deduct 2" to calculate center of rod bushing height.

Pallet Forks - Available in pin-on, JD & skid steer quick attach

These handy **Fork Attachments** can make your tractor/loader into a low cost forklift. Models include John Deere and pin-on pallet forks. The forks feature lockable tines and slotted rails. The solid tines are made of Boron Steel and then are heat treated.

- Load capacities of 2250 & 3750 lb.
- Fits compact and utility loaders
- Forks are constructed of Boron steel and heat treated
- Adjustable and lockable rail style forks
- Equipped with high visibility load guard



WARNING: The loader mounted fork attachments are specifically designed to engage and load palletized materials. Do not use forks to handle large loads, such as bales, posts, etc., and avoid carrying loose or shiftable loads, as they can fall or roll back onto operator causing serious injury or death.

| Models: | ULF-2242 Pin-On | ULF-3548 Pin-On | JLF-2242 JD QA |
|----------------|---|--|--|
| Lift Cap: | 2250 lbs. | 3750 lbs. | 2250 lbs. |
| Fork Length: | 42" | 48" | 42" |
| Tine Size: | 1 1/4" x 3" Solid | 1 1/4" x 4 1/2" Solid | 1 1/4" x 3" Solid |
| Loader Mounts: | Compact loaders between 28 1/4" ID & 47 1/4" OD w/3/4" or 1" pins | Loader frames between 32" ID & 48" OD with 1" or 1 1/8" pins | Fits JD compact loaders w/quick change attach. carrier |
| Weight: | 280# | 385# | 280# |

Available For Universal, John Deere & Global / Euro Quick Attach

The new heavy duty frames are designed to handle both the 3750 and 5500 lb. capacity forks. The 10 gauge brickguard offers outstanding strength and smooth surface for protection and less load damage. Also, the convenient non-skid step offers easy operator access, except 2300 lb. capacity. The tine end visibility is excellent.



| Code No: | Description | Capacity | Tine Length | Wt. |
|----------------|------------------------|-----------|-------------|------|
| 107283/106220 | SSL QA Compact | 2300 lbs. | 42" | 270# |
| 107283/106222 | SSL QA Compact | 2300 lbs. | 48" | 285# |
| 17380 / 102028 | SSL QA Fork Assy. | 3750 lbs. | 42" | 450# |
| 17380 / 102030 | SSL QA Fork Assy. | 3750 lbs. | 48" | 480# |
| 101177/102028 | JD QA Fork Assy. | 3750 lbs. | 42" | 410# |
| 101177/102030 | JD QA Fork Assy. | 3750 lbs. | 48" | 440# |
| 17380/102032 | SSL QA Fork Assy. | 5500 lbs. | 42" | 490# |
| 17380/102034 | SSL QA Fork Assy. | 5500 lbs. | 48" | 500# |
| 109065/102034 | Euro Global Fork Assy. | 5500 lbs. | 48" | 465# |

- Available in 2300, 3750 & 5500 lb. cap.
- Fork tines available in 42" & 48" length
- Exclusive load retention hook for securing and positioning pallet loads
- Solid tine positioning w/spring loaded toggle operation
- Easy loading with tapered tines

HARROWS, CHAIN

Drag or Lifiable - Aggressive, light, or minimum positions

**DRAG - AVAILABLE
IN ALL SIZES**

**LIFTABLE - AVAILABLE
IN 4x4, 6x6 & 8x6**

**5/8" TINES DRAG
CHAIN HARROWS**



Cat. I
A.S.A.E.
Quick Hitch
Compatible

FEATURES:

- Tines 1/2" diameter by 4 1/4" long
- No parts to lubricate/adjust
- Offset tines eliminate ridges
- Evenly works ground regardless of terrain
- Cold formed tines eliminate breakage
- Can be operated at speeds up to 8 MPH

NOTE: 4' Lift Harrow Not Cat. I Quick Hitch Compatible

FEATURES:

- 2" Pipe drawbars w/5/8" chain
- Tines 5/8" diameter x 6" long
- Cold formed tines eliminate breakage
- Evenly works ground regardless of terrain
- No parts to lubricate or adjust
- Can be operated at speeds up to 8 MPH

PASTURE RENOVATION & MAINTENANCE

Spreads and incorporates manure, thatches dead growth, aerates soil, increases moisture penetration and renovates pastures by preparing soil for seeding while stimulating existing growth.

DIRT & GRAVEL MAINTENANCE

For ball diamonds, race tracks, dirt and gravel roads, rodeo arenas, etc. Smooths rough spots, fills holes and incorporates moisture.

GRASS & TURF MAINTENANCE

For parks, golf courses, and playing fields. Incorporates seed, dethatch turf, and aerates soil. Pulls out dead material without disturbing new growth.


ALL TILLAGE APPLICATIONS

Prepares firm, level seedbed in combination with drills, cultivators and discs. Can be used to break up crusts and clods. Incorporates herbicides evenly because flexible design assures uniform depth.

| Model # | Type | Description | Wt. |
|----------------|-------|--------------------|------|
| G4-3P-H4x4-1/2 | 3-Pt. | 4' Wide x 4' Deep | 140# |
| D4-4x6-5/8 | Drag | 4' Wide x 6' Deep | 150# |
| D6-6x8-5/8 | Drag | 6' Wide x 8' Deep | 310# |
| G6-3P-6x6-5/8 | 3-Pt. | 6' Wide x 6' Deep | 280# |
| D8-8x8-5/8 | Drag | 8' Wide x 8' Deep | 373# |
| G8-3P-8x6-5/8 | 3-Pt. | 8' Wide x 6' Deep | 351# |
| D10-10x8-5/8 | Drag | 10' Wide x 8' Deep | 490# |
| D12-12x8-5/8 | Drag | 12' Wide x 8' Deep | 634# |

| Drawbars Only | | | Chain Sections | | | |
|---------------|-------------|-----|----------------|-------|-------|------|
| Model # | Width | Wt. | Model # | Width | Depth | Wt. |
| D4 | 4' | 26# | H4X4-1/2 | 4' | 4' | 70# |
| D5 | 5' | 30# | H5X4-1/2 | 5' | 4' | 86# |
| D6 | 6' | 36# | H6X4-1/2 | 6' | 4' | 105# |
| D8 | 8' | 50# | H6X6-1/2 | 6' | 6' | 157# |
| D10 | 10' | 60# | H6X8-1/2 | 6' | 8' | 209# |
| D12 | 12' | 70# | H8X6-1/2 | 8' | 6' | 209# |
| D1D | Adaptor Kit | | H10X4-1/2 | 10' | 4' | 174# |

Flexible Two-Way Design For Optimum Debris Clearance



VARIABLE ACTION FOR EVERY APPLICATION



MINIMUM ACTION
Tines in smoothing position



LIGHT ACTION
Reversed tines angled farther back



AGGRESSIVE ACTION
Tines stand up at 75° angle

HARROWS, ROTARY


3-Point Hitch - Gives arenas smooth, level surfaces

FEATURES:

- Cat. I, 3-point hitch
- 2" x 2" Square tubing wheel with 5 spokes
- 5 ½" High carbon teeth
- Sealed bearing hub
- Heavy 3" x 4" tubing frame
- 8" Bolt-on replaceable teeth
- Angled teeth provide trash clearance



Now with
replaceable teeth



The GRH Series of **Rotary Harrows** was designed to aerate soil and pull weeds. The unique turning action allows the harrow to level soil by redistributing it inward. Excellent tool for moving high spots away from fences and walls. Levels, floats and breaks up clods. The ideal product to use in arenas.

SPECIFICATIONS:

| MODEL NUMBER: | DESCRIPTION | WEIGHT |
|-------------------|-----------------------|--------|
| GRH SERIES | | |
| GRH5B | Rotary Harrow, 5 Foot | 240# |
| GRH6B | Rotary Harrow, 6 Foot | 290# |

Our Cat. I & II **Quick Hitches** were designed to make changing implements easier, safer and faster. Thus eliminating the lifting and moving heavy implements into position for mounting to the tractor. You can safely change implements in seconds.

FEATURES:

- Operator can engage and secure implements more easily
- Reduces chance of personal injury as no need to put yourself between the tractor and the implement, except for attaching driveshafts
- Automatic lock with quick release handles
- Optional hydraulic top link cylinders are available for easier hook-up
- Additional bushing kits for each implement are available

QUICK HITCHES


Fits Cat. 1 or 2 - The quick, safe way to attach implements



| Model No: | Description | Wt. |
|-----------|---|------|
| 862830 | Cat. I - Complete with ⅞" shouldered bushings and swivel yoke | 83# |
| 862845 | Cat. II - Complete with 1 ⅛" mounting pins & adapter bushings - 100 HP Max. | 135# |

HEDGER, TOPPER, SKIRTER

Hedging Orchards - And other hedging requirements



MODEL P1100-O

These unique **COLLARD Hedgers** were designed for half row trimming of orchards and can be used on a number of different crops. The heart of this hedger is the unique lightweight aluminum alloy element that provides a rugged rust-proof framework for the cutting blades.

The units feature two different cutting systems - saw blades or dual swinging knives.

FEATURES:

- Available with 18" diameter S.S. saw blades or swinging knives
- Main trimmer beam has hydraulic up and down with 32" stroke cylinder
- The upper element manually adjusts 12" vertically
- Vertical breakaway system to protect equipment
- Complete hydraulic distributor, hoses, and "JIC" couplers
- Equipped with electro-hydraulic joystick controls for precise trimmer adjustments

SPECIFICATIONS:

| Order Code | Model No. | Vertical Cut | Horizontal Cut | No. of Blades | Hydraulic Requirements | Wt. |
|------------|-----------|--------------|----------------|---------------|------------------------|-------|
| 0134 1350 | P1100-O | 90" | 48" | 9 | 12 GPM@2600 PSI | 1200# |

NOTE: The maximum cutting height is approximately 10 foot.

HEDGER, TOPPER

Designed to hedge & top trees and bush crops



The **COLLARD Hedger/Topper** was designed to hedge, top trees and bush crops. Easy to operate with electric controls. The cutting bar length is 6 feet and additional blades can be added for longer cuts. This unit is great for orchard hedging, topping and fence line maintenance.

FEATURES:

- Dual hydraulic motors for added power
- Standard cutter bar length 6.8 feet
- Vertical reach of 20 feet
- Flat topping height of 13 feet
- Tractor requirement of only 11 G.P.M. at 2140 PSI
- Electro hydraulic controls
- Hedger comes with all hoses, fittings and JIC couplers
- Flail knives are optional

SPECIFICATIONS:

| Model No. | Description | Reach | Topping | Wt. |
|-----------|-----------------------|--------|---------|------|
| TA400 | Hedger/Topper 5 Blade | 20 Ft. | 13 Ft. | 860# |

Built By:

COLLARD®

HEDGER, TOPPER, SKIRTER

Total Pruning System - Allows total control of orchard profile



The **COLLARD Hedger** is a total pruning system for orchards. Features an adjustable pruning system to hedge, top and skirt orchards. Allows growers to maximize production and reduce pruning costs. By reducing heavy crop set limb damage, opens middles for better sunlight, cleans out lower branches to reduce herbicide damage and allows passage of tractors without limb breakage.

- Maximize production and reduce pruning cost with better management of your tree canopy
- Reduce heavy crop set limb breakage
- Clean your lower hangers to reduce herbicide damage
- Open middles for better sunlight - improve harvest conditions
- Hedge when you want
- Allow passage of tractors without limb damage or operator risk

FEATURES:

- 7 cylinder hydraulic system which allows for many different applications
- Electro hydraulic controls
- 18" Diameter S.S. saw blades are standard with optional flail knives for green material
- Requires minimum of 12 GPM @ 3000 PSI
- Designed so that blades throw much of the brush into the rows, instead of dropping into the tree canopy
- Effective trimming for both nut and fruit orchards
- Cut lengths per side of 8, 9.4, 10.7 or 12 feet
- 6 Blades shown - optional 4, 5, 6, 7, 8 & 9 blades per side

This special 3-pt. hitch P.T.O. driven HYDRAULIC POWER PACK was developed as a self-contained power system which eliminates using the tractor hydraulics. The hydraulic oil will stay cooler with no loss of power to the hedger. The Power Pack features 3 hydraulic pumps, one for the hydraulic cylinders and one for each blade transmission housing. The 30 gallon oil reservoir includes return filter with cartridge and oil level gauge. Also included is oil cooler, driveline and hoses. This Power Pack is strongly recommended.



SPECIFICATIONS:

| Order No. | Model No. | Description | Approx. Wt. |
|-----------------|-----------|---------------------------------|-------------|
| 01370800 - 2448 | P2000AH* | Hedger with Power Pack | 2330# |
| 01370400 | P2000A | Hedger using tractor hydraulics | 1600# |

* Recommended for operating long hours in high temperatures.

NOTE: The models above are for hedgers only, advise the number of blades required.

Built By:

COLLARD

SKIRTERS

For Skirting Orchards Manual Adjustment

This COLLARD Skirter trims half rows with 2 high speed stainless steel blades. The heart of this Skirter is the unique lightweight aluminum alloy element that provides a rugged rust proof frame work for the cutting knives. The COLLARD Tree Skirter is a fast, effective way to keep lower branches off the ground. The main reason to skirt trees is to prevent easy access of all types of pests. Another important reason to skirt is to provide clearance for other operations, such as spraying and mowing.

- Skirter is strong but lightweight and easy to operate
- Double tubing socket bracket to mount on tractor frame
- High speed stainless steel blades - 18 7/8" long
- Sliding horizontal tubing extends 20" to right side, manual
- High capacity 10cc hydraulic motor
- Sliding vertical tubing 20" up/down, manual
- Cutting housing is 35" long and angles down manual 0° to 45°
- Blade housing has safety break away system



Model P1000SK

| Order No. | Model No. | Cut. Length | No. of Blades | Hyd. Requirements | Ship Wt. |
|-----------|-----------|-------------|---------------|-------------------|----------|
| 013700950 | P1000SK | 35" | 2 | 8 G.P.M. | 410 lbs. |

SKIRTERS

For skirting orchards hydraulic adjustment

Model P2000SK



This COLLARD Skirter trims two half rows with 6 high speed swinging stainless steel knives. The heart of this Skirter is the unique lightweight aluminum alloy element that provides a rugged rust proof frame work for the cutting knives. The COLLARD Tree Skirter is a fast, effective way to keep lower branches off the ground. The main reason to skirt trees is to prevent easy access of insects and pests of all types. Another important reason to skirt is to provide clearance for other operations, such as spraying and mowing.

- Skirter is strong but lightweight and easy to operate
- Double tubing socket bracket to mount on tractor frame
- High speed S.S. double cutting edge flail knives
- High capacity 15cc hydr. motors with ribbed belts
- Equipped with electro hydraulic joystick controls
- Wide range of adjustments for positioning skirts to each grower requirements
- Up/down 2 hydr. cylinders with 20" stroke, ea. side
- In/out hydr. cylinders with 20" stroke, ea. side
- Three swinging knives per housing with cut of 50"

| Order No. | Model No. | Max. Cut. Length | No. of Blades | Hyd. Requirements | Ship Wt. |
|---------------------------|-----------|------------------|---------------|-------------------|----------|
| 01370900 | P2000SK | * 14'-6" @ 45° | 3 per side | 10 G.P.M. | 680 lbs. |
| * Advise your row spacing | | | | | |

Built By: **COLLARD**®

HIGH PRODUCTION ATTACHMENTS

for compact wheel tractors

SIFTING BUCKET



- Width - 55" - 3/4" rods

4 IN 1 BUCKET



- Widths of 60" and 72"

ROOT RAKES



- Widths of 60", 66" and 72"

BRUSH GRAPPLES



- Widths of 48", 54" and 72"

HYDRAULIC DIGGER



- D450 With Q.A. Bracket
(see page 13 for digger specs)

PALLET FORKS



- Tines - 42" and 48"
(see page 23 for pallet fork specs)

Built By: **PALADIN.**

IMPLEMENTS

Construction - Attachments manufactured by Bradco

COMPACTION WHEELS



- Designed for small excavators & backhoes
- Compactor widths of 12", 18", and 24"
- Rims available in 2, 3, and 4 wheels
- Compaction pads abrasion resistant
- Wheel diameters of 22" and 28"
- Compactor weights of 320 to 980 lbs.
- For machine weights of 2700 to 38,000 lbs.

4-IN-1 BUCKETS



Construction Series shown with optional side cutter & spill guard

- 3 Series in widths of 60", 66", 72", 78", & 84"
- For machine weights - 4,000, 8,000 & 12,000#
- Long floor design improves cutting edge visibility
- "Hose Saver" spring kit standard, except on compact units
- Unique side cutters on construction series only
- Effective loader bucket for clam, dozer, scraper and bottom dump operations

TRENCHERS



Model 612 For Tractors 20 - 45 H.P.



Model 330 For Tractors 15 - 30 H.P.

- 3 Pt. hitch, PTO driven for 15 to 45 HP hydrostatic transmission tractors
- Digging depths from 30" to 60" deep
- Digging widths from 3" to 12" wide
- Large discharge auger places soil away from trench
- Built with the best of heavy duty components

SIFTING/ROCK BUCKETS

66" With Loader Arms



Optional Grapple


- Widths of 66", 75" and 84"
- Brackets to fit loader arms, Skid Steer and quick attach
- Unique tine design is contoured to cradle the debris and rocks
- Rods are 1 1/4" diameter high alloy steel
- Standard buckets come with 3 1/8" spacing between tines, with the option of 2" spacing

Built By:

BRADCO

PA RIPPER BARS

These **Ripper Bars** are excellent for aerating pastures and other ripping applications.



- Cat. I, 3-point hitch
- 5, 6 and 7 Shank sizes
- Rips up to 8" deep
- Shear bolt protection

80-320 ALL-PURPOSE MIXERS

Our economy **Mixer** effectively blends materials including concrete, feed, and fertilizers.



- Cat. I, 540 RPM P.T.O.
- Capacity - 11 cu. ft.
- Mixes 1 ½ sacks of cement
- Double acting cylinder with hose

SC 3-POINT ROLLERS

These **3-Point Hitch Rollers** have excellent maneuverability to smooth and increase the firmness of turn surfaces.



- Available in 60" width with 16" dia. drum
- Or 72" width with 20" dia. drum
- When water is added the 60" weighs 860 pounds, the 72" weighs 1,340 pounds

SC PULL TYPE ROLLERS

Our **Pull Type Rollers** are available with 20" dia. rollers in widths of 60", 72", and 96". When filled with water the rollers are great for packing down loose dirt, newly sown seed and turf.



- Available in roller widths of 60", 72", & 96"
- Heavy duty ¼" thick roller tubing
- 1 7/16" Full length axle with bearings

TB TOOTH BARS

Our bolt-on **Tooth Bars** are designed to make your loader bucket more aggressive.



- Requires no drilling of bucket
- Special set screws to hold tooth bar in place
- Available for inside bucket widths of 40", 46", 52", 58", 64", & 70"

SSL PLATES

SSL Quick Attach Plate with Cat. 1 & 2, 3-Point hitch ears for implements #88020 wt. 210 lbs.



- Also available in weld-on plates only
- Std. SSL mounting plate #86914 - wt. 75#
- Heavy duty SSL mounting plate #88987 - wt. 123 lbs.
- Weld-on plates shipped unpainted

NEW

IMPLEMENTS

Quick Attach - root rakes and buckets

The **Quick Attach Bracket** for compact tractors allows you to change loader attachments in minutes. Just unlatch the quick attach, back out of one implement and drive into another, flip the locking handles and you are ready to go back to work.



- The Quick Attach mounts directly to your loader arm and cylinders in minutes
- No special pins or modification to the loader are necessary
- Available for most popular compact tractor loaders
- Weld-on plates are available to convert standard brackets to Quick Attach



*Root rakes available in widths of 60", 66" & 72"
Available in quick attach only*



Standard, light material and heavy duty buckets in widths of 60", 66" and 72"

IMPLEMENTS

Electro Hydraulic Kit

Gearmore **Electro Hydraulic Components** were developed to obtain a simple, compact way to operate loader mounted hydraulic implements. The mounted electro hydraulic valve is easily operated by a push button switch knob mounted on the tractor loader valve lever. This allows operation of the loader functions and hydraulic implements without moving your hand.



Turns your standard bucket into a versatile grapple bucket

Bolt-on bucket grapples are available in single 48" to 72" and double 60" to 84" buckets



Model # EH-100 Electro Hydraulic Valve components for installation on tractor loaders

- Electro hydraulic valve, operates hydraulic functions up to 13.2 G.P.M.
- Easily installed replacement loader knob with pushbutton electric switch
- Valve mounting bracket and hardware

NOTE: *Not compatible with regenerative valve circuits*

FLAIL MOWERS

"SLE" & "GML" Series - No tools blade changing system on SLE Series

- Cat. I, ASAE quick hitch compatible for easy attaching to tractor
- Low profile design for clearing obstructions
- Available with side slicing Y blades for light brush or grass finishing ducksfoot blades
- Center mount or offset 9 inches to right
- 45 Horsepower, 540 RPM gearbox
- Internal "saw tooth" cutter bar to reduce size of shredded material
- 5" Diameter rear roller
- Safety chain shield in front and rubber rear deflector



"SLE" SERIES

Cat. I
A.S.A.E.
Quick Hitch
Compatible



Quick Change
Y Blade



Quick Change
Ducksfoot Blade

This Gearmore **SLE Series** mower was developed for mowing grass and light weeds with side slicing Y blades. All models are also available with finish mowing cupped "ducksfoot" blades for mowing grass. Standard features include ASAE quick attach 3-point hitch, low profile design, center mount or offset, adjustable rear roller and many more. These flail mowers were designed to achieve fine shredding on cover crops, parks, golf courses, pastures, and light weed abatement.

| Model No: | Mow Width | Overall Width | No. of Knives | Min. H.P. Req'd | Wt. |
|-----------|-----------|---------------|---------------|-----------------|------|
| SLE-120 | 48" | 54" | 22 | 20 H.P. | 415# |
| SLE-160 | 63" | 69" | 30 | 28 H.P. | 525# |
| SLE-190 | 75" | 81" | 36 | 35 H.P. | 620# |

- Fits Cat. I, 3-pt. hitches, 540 R.P.M. tractors
- Mows grass and weeds up to 1/2" with Y blades
- Shreds brush up to 1 1/2" dia. w/swinging hammer blades
- Computer balanced vibration free rotor turns @ 2300 RPM
- 3 Belt drive protects gearbox, driveshaft and rotorshaft
- Front metal flaps provide safety from flying material
- Rear rubber safety flaps

The **Gearmore Flails** are the ultimate in flail mowers. The mowers are heavy built with 40 H.P. gearbox, to give years of trouble free service. Two types of blades are available - hammer and Y blades, both do clean cutting on light brush and grass. High speed 2300 R.P.M. rotor makes for smooth finished cut. The adjustable rear roller ensures even mowing. These flail mowers are just right for use in mowing cover crops, parks, schools, golf courses, pastures, roadsides, etc.



"GML" SERIES



Hammer Knife
Up to 1 1/2" Brush



Y Blade
Up to 1/2" Brush

| Model No: | Mow Width | Overall Width | No. of Hangers | Min. H.P. Req'd | Wt. |
|-----------|-----------|---------------|----------------|-----------------|------|
| GML-41 | 41" | 48" | 18 | 16 H.P. | 580# |
| GML-49 | 49" | 59" | 24 | 20 H.P. | 640# |
| GML-61 | 61" | 68" | 27 | 24 H.P. | 720# |
| GML-69 | 69" | 78" | 33 | 28 H.P. | 770# |
| GML-79 | 79" | 88" | 39 | 35 H.P. | 840# |

FLAIL SHREDDERS

"SFG" Series - Center mount, offset mechanical or hydraulic

Our **SFG Series** of flail mower/shredders feature fixed center mount, manual or hydraulic side shift. The narrow shredders are fixed center mount. The two largest shredders are manual offset, return to center with optional hydraulic offset. Two style of blades can be purchased, hammer knives or double Y blades. These blades are also interchangeable on the same shredders. The low profile design of the machine aids when working in tight areas. These are popular mowers in vineyards, berries, roadsides, weed abatement, rental yards, etc.

Cat. I
A.S.A.E.
Quick Hitch
Compatible

SFG155 SHOWN



Double Y Blade



Hammer Knife

OPTIONS:

- ~ Rake Teeth
- ~ Hydraulic offset SFG185 & 200

- Cat. I, ASAE quick hitch, 540 RPM tractors
- Fixed center mount hitch, except SFG 185/200
- 70 HP gearbox with built-in overrunning clutch
- Low profile belt housing, 23" high for clearance
- Hammer knives shreds brush and prunings up to 2" diameter
- Double Y blades mow weeds and light brush up to 1" diameter
- Cutting height adjusts from 1" to 4" above ground
- Rotor speed - 2200 RPM
- Two rows of heat treated re-cutter blades
- Rear hatch adjusts for various types of mowing
- Rear hatch slotted for rake teeth
- Balanced 5 1/2" rotor tubing
- 5 1/2" Diameter rear roller adjusts vertically and horizontally
- 4 Belt final drive to provide maximum power to the rotor
- Series 6 PTO driveshaft
- Front mounted safety chains

| Model No: | Working Width | Overall Width | Max. Offset* | No. of Hammers | No. of Y Blades | H.P. Req'd | Rake Slots | Wt. |
|-----------|---------------|---------------|--------------|----------------|-----------------|------------|------------|-------|
| SFG95 | 38" | 43" | - | 8 | 32 | 20 H.P. | 6 | 640# |
| SFG125 | 49" | 55" | - | 8 | 32 | 25 H.P. | 8 | 730# |
| SFG140 | 55" | 61" | - | 10 | 40 | 30 H.P. | 9 | 770# |
| SFG155 | 61" | 66" | - | 10 | 40 | 35 H.P. | 10 | 840# |
| SFG185* | 73" | 78" | 51" | 12 | 48 | 40 H.P. | 12 | 1005# |
| SFG200* | 79" | 84" | 54" | 14 | 56 | 45 H.P. | 13 | 1100# |

*These shredders come with manual offset, hydraulic offset is optional. Offset shown is the maximum offset from centerline of tractor to the right.

FLAIL SHREDDERS

"GCF" & "GRF" Series - Front or rear mount

Our **GCF Series Mower/Shredders** are now designed for front or rear tractor mount. To front mount, just re-bolt the A-frame to the back of the shredder. Equipped with a rear deflector which in open position discharges grass and allows tractor speeds up to 6 MPH, and in closed position contains and further shreds brush to a finer mulch. Just right for use in vineyards, berries, and other narrow row crops. Also used by roadsides, parks, rental yards, and general weed abatement.

- Fits Cat. I & II, 3-point, 540 R.P.M. tractors
- HD 72 H.P. gearbox with built-in overrunning clutch
- Hammer knives shred brush & prunings up to 2", and will also mow grass
- Computer balanced vibration free rotor turns at 2000 RPM
- Adjustable A-frame allows offsetting mower 6" to the right
- Front safety chains provide safety from flying material

| Model No: | Mow. Width | Overall Width | No. of Knives | Min. H.P. Req'd | Wt. |
|-----------|------------|---------------|---------------|-----------------|-------|
| GCF41 | 41" | 46" | 9 | 20 H.P. | 680# |
| GCF45 | 45" | 50" | 12 | 25 H.P. | 700# |
| GCF53 | 53" | 58" | 12 | 30 H.P. | 790# |
| GCF61 | 61" | 66" | 15 | 35 H.P. | 920# |
| GCF69 | 69" | 74" | 18 | 40 H.P. | 970# |
| GCF79 | 79" | 84" | 21 | 45 H.P. | 1030# |

The **Gearmore Mower/Shredders** are the ultimate in flail mowing. The 3 lb. drop forged hammer knives will shred up to 3" diameter branches and yet will mow grass. Just right for use in vineyards, orchards, roadsides, parks, pastures and weed abatement. You will find that these heavy duty machines will give many years of low maintenance usage.

- Available in Cat. I or II, 540 R.P.M.
- Reversible front or rear center mount
- Shreds brush or prunings up to 3", constant use 2 1/2"
- Cutting height adjusts from 1" to 4"
- Equipped with an adjustable rear deflector
- Double row drop forged cutter bars increase shredding of material
- Computer balanced vibration free rotor turns at 2000 RPM
- Heavy duty 85 H.P. gearbox with built-in overrunning clutch

| Model No: | Mow Width | Overall Width | No. of Knives | Min. H.P. Req'd | Wt. |
|-----------|-----------|---------------|---------------|-----------------|-------|
| GRF69 | 69" | 78" | 18 | 36 HP | 1190# |
| GRF79 | 79" | 88" | 21 | 45 HP | 1280# |
| GRF89 | 89" | 98" | 24 | 50 HP | 1380# |
| GRF98 | 98" | 108" | 24 | 58 HP | 1520# |

"GCF" SERIES



"GRF" SERIES



**Hammer Knife
Up to 2" Brush**

FLAIL SHREDDERS

"GOF" & "TR" Series - For heavy duty grass and brush shredding

"GOF" SERIES



Hammer Knife

The *Gearmore Mower/Shredders* are the ultimate in flail mowing. The 3 lb. drop forged hammer knives will shred up to 3" diameter branches and yet will mow grass. Equipped with a patented rear deflector which in open position discharges grass and allows tractor speeds up to 6 MPH, and in closed position contains and further shreds brush to a finer mulch. In offset position, the units are ideal for mulching prunings and heavy grass in orchards. Municipalities find these shredders excellent for roadside maintenance.

- Fits Cat. I or II, 3-pt. hitch, 540 R.P.M. tractors
- Adjustable swing hitch allows quick setting for an additional 28" of offset
- Double row of drop forged cutter bars to increase the shredding of material
- Shreds brush/prunings up to 3", constant use 2 ½"

- Computer balanced vibration free rotor turns at 2000 RPM
- HD 85 H.P. gearbox w/built-in overrunning clutch
- 5 Belt drive protects gearbox, driveshaft & rotorshaft, 4 belt on model GOF69-79
- Front mounted safety chains provide protection from flying material
- All models have slotted rear hatches for brush teeth

| Model No. | Mow Width | Overall Width | Max. Offset f/Tractor Center Line | No. of Knives | Min. H.P. Req'd | Wt. |
|-----------|-----------|---------------|-----------------------------------|---------------|-----------------|-------|
| GOF69 | 69" | 78" | 64" | 18 | 40 H.P. | 1190# |
| GOF79 | 79" | 88" | 74" | 21 | 45 H.P. | 1300# |
| GOF89 | 89" | 98" | 84" | 24 | 50 H.P. | 1430# |
| GOF98 | 98" | 108" | 93" | 24 | 65 H.P. | 1560# |

"TR" SERIES



Cat. II
A.S.A.E.
Quick Hitch
Compatible

- Cat. II, 3-point ASAE quick hitch
- Heavy duty 90 HP, 540 RPM gearbox w/overrunning clutch
- Center mount and offsetable 13 inches to the right
- Shreds material up to 2 inches
- Heavy duty Y blades
- Internal re-cutter bar to increase the shredding of material
- 4 - V-belts final drive, 5 belts on 255 and 280
- Closed or lockable open tailboard
- Adjustable foldaway gauge wheels
- Tires are 7:00 x 12 6-ply, tubeless
- Adjustable side skids

OPTIONS:

- ~ Deflector brackets mounted on the underside of the tailboard
- ~ Rear roller in lieu of gauge wheels

| Model No. | Mowing Width | Overall Width | No. of Y Blades | Approx. HP Req'd | Wt. |
|-----------|--------------|---------------|-----------------|------------------|-------|
| TR200 | 79" | 85" | 44 | 65 HP | 1515# |
| TR225 | 88" | 94" | 48 | 70 HP | 1675# |
| TR255 | 100" | 106" | 56 | 75 HP | 1830# |
| TR280 | 110" | 117" | 60 | 80 HP | 1990# |

Our *TR Series Shredders* feature a 90 HP gearbox, center mount with offsetable position, special lockable open tailboard with optional deflector brackets for spreading out shredded material, and adjustable foldaway gauge wheels. The shredders have heavy duty swing Y type blades for heavy grasses and light weeds. These units are excellent to achieve fine shredding of row crop residue, pastures and other types of farm usage.



CAUTION: When operating the shredder with tailboard open, people should not be within 300 feet of the machine

FLAIL SHREDDERS

"GHF-FS" Series - For fine shredding of orchard brush

The new GHF-FS Series was developed for fine shredding of orchard brush. These shredders feature 4 internal re-cutter bars to reduce the brush until it is finely shredded. The rake teeth keep the material inside mower hood to reach a consistency of decomposable mulch. The large 10 inch diameter rotor is mounted with drop forged hammer knives giving optimum shredding performance. These shredders are specially designed for severe conditions of orchard brush, but can also be used in weed abatements, tall grasses, heavy weeds, and cover crops.



Hammer Knife

FEATURES:

- Fits Cat. II 3-point, center mount
- Available for tractors with 540 or 1,000 R.P.M., PTO
- Front or rear tractor mount
- Shreds brush or prunings up to 3", intermittent 4"
- Gearbox maximum horsepower of 200, with built-in overrunning clutch
- Specially designed drop forged hammer knives give optimum performance in brush shredding, mulching prunings, grass cutting and maintenance of cover crops
- Four rows of drop forged cutter bars to increase the shredding of material
- Equipped with large number of rear mounted rake teeth (see below)
- 10" diameter, computer balanced, vibration free rotor turns at 2000 RPM
- 8" diameter, full width gauge roller with bearings
- Hood plate ¼" thick, double plated front and back side plates ½" thick
- Double row of front safety chains

SPECIFICATIONS:

| MODEL # | MOWING WIDTH | OVERALL WIDTH | NO. OF KNIVES | NO. OF RAKES | MIN. HP REQUIRED | WEIGHT |
|-----------|--------------|---------------|---------------|--------------|------------------|--------|
| GHF90-FS | 7' - 6" | 8' | 24 | 18 | 80 HP | 2,670# |
| GHF100-FS | 8' - 4" | 8' - 10" | 26 | 20 | 90 HP | 2,800# |
| GHF120-FS | 10' | 10' - 6" | 30 | 24 | 100 HP | 3,130# |
| GHF140-FS | 12' | 12' - 6" | 36 | 28 | 110 HP | 3,310# |

FLAIL SHREDDERS

"S9C" & "S9B" Series - Low profile S9C & fixed center mount S9B

"S9C" SERIES



This **Flail Mulcher** has a unique hydraulic side shift system that moves horizontally on front and rear mounted heavy steel tubes. These units were designed for high usage with limited maintenance. This is achieved by a number of special features such as - high tensile steel hood, internal hood replaceable "Hardox" wear plates, replaceable drop forged re-cutter bars and large 150 horsepower gearbox. The adjustable rear hatch can be closed for maximum shredding or open for maximum speed up to 6 MPH.

| Model No: | S9C-200 | S9C-225 | S9C-250 |
|------------------|-------------|--------------|--------------|
| Shredding Width: | 79" (6'-7") | 89" (7'-5") | 98" (8'-2") |
| Overall Width: | 85" (7'-1") | 95" (7'-11") | 104" (8'-8") |
| Max. Offset F/C: | 67.5" | 72.5" | 77.5" |
| No. of Knives: | 21 | 24 | 27 |
| Min. H.P. Req'd: | 75 HP | 80 HP | 85 HP |
| Weight: | 1940# | 2120# | 2260# |

"S9B" SERIES



These large **S9B Flail Mulchers** were designed for high usage with limited maintenance. This is achieved by a number of special features such as - high tensile steel hood, internal hood replaceable "Hardox" wear plates, replaceable drop forged re-cutter bars, and oversized 180 horsepower gearbox. The adjustable rear hatch can be closed for maximum shredding or opened for maximum speed up to 6 miles per hour.

| Model No. | S9B-250 | S9B-275 | S9B-300 |
|------------------|--------------|--------------|---------------|
| Shredding Width: | 98" (8'-2") | 108" (9') | 118" (9'-10") |
| Overall Width: | 104" (8'-8") | 114" (9'-6") | 124" (10'-4") |
| No. of Knives: | 27 | 27 | 30 |
| Min. H.P. Req'd: | 85 HP | 90 HP | 95 HP |
| Weight: | 2230# | 2400# | 2580# |

S9C FEATURES:

- Cat. 2, 540 R.P.M. hydraulic offset
- 150 HP gearbox with overrunning clutch
- Hydraulic offset - 28 inches
- Mulches grass and prunings up to 3 ½"
- Working speeds up to 6 miles per hour
- Drop forged hammer knives
- Hood assembly made of high tensile steel
- Replaceable drop forged re-cutter bars to increase material shredding
- Adjustable rear hatch - closed for maximum shredding, open for maximum speed
- Rotor bearings are double self-aligning
- Large 7.6" diameter adjustable rear roller
- Front mounted double row of safety chains and rear mounted rubber guards

OPTION:

- ~ 1000 R.P.M. gearbox

S9B FEATURES:

- Cat. 2, 540 R.P.M. fixed center mount
- Front or rear tractor mount
- 180 HP gearbox with overrunning clutch
- Mulches grass and prunings up to 3 ½"
- Working speeds up to 6 miles per hour
- Drop forged hammer knives
- Hood assembly made of high tensile steel
- Replaceable drop forged re-cutter bars to increase material shredding
- Adjustable rear hatch - closed for max. shredding, open for maximum speed
- Rotor bearings are double self-aligning
- Large 7.6" diameter adjustable rear roller
- Front mounted double row safety chains and rear mounted rubber guards

OPTION:

- ~ 1000 R.P.M. gearbox

FLAIL MULCHERS

For Compact Excavators

These Flail Mulchers are ideal for grasses and brush that are difficult to reach, like edges of roads and riverbanks. These units shred material up to one inch in diameter. The Mulchers are very productive even with the low hydraulic power required. The hood is made of wear resistant steel. The adjustable rear roller is reinforced and the floating mount adapter are standard equipment. These mulchers are strong, yet light weight for better control.

- For excavators weights of 4,000 to 10,000 pounds
- Mulches grass and brush up to 1 inch
- Variable displacement hydraulic motor with relief valve
- Required hydraulic flow – 5 to 18 gallons per minute
- Hydraulic pressure 2,175 to 3,625 PSI
- Floating adapter mount follows the ground contours
- Adjustable rear roller with reinforced bearings
- Front mounted safety chains



- Rear mounted safety rubber flaps
- Available with Y blades
- Less Hoses
- Requires case drain line

| Model No. | Working Width | Overall Width | Depth | No. of Blades | Wt. |
|-----------|---------------|---------------|-------|---------------|------|
| H3-85 | 33" | 38" | 31" | 12 | 400# |
| H3-105 | 41" | 46" | 31" | 18 | 480# |

These forestry mulchers are suitable for forest work as well as the most demanding applications in landscaping and maintaining areas in which prunings, stumps, and wood that must be eliminated. Mulchers have a heavy mounting receiver plate for Skid Steer/Trackloaders.

The powerful hydraulic system on the MINIFORST is compatible with tractors with flow rates of 20 to 45 gallons per minute. The powerful efficient hydraulic M-BOOST™ motor, delivers 40% more torque than standard motors.

- Mounted on standard Skid Steer mounting bracket
- Mulches wood up to 8 inches (20 cm)
- Operating speed up to 3 miles per hour (5km/h)
- Variable displacement hydraulic motor with relief valve
- Required hydraulic flow – 20 to 45 gallons per minute
- Hydraulic pressure 2,175 to 5,000 PSI
- Fixed rotor hammers with dual tungsten carbide tipped tools
- Five rows of heat treated recutter bars for finer mulch

MULCHERS

Hydraulic Driven - Skid Steer Mount



- Hydraulically operated front door when closed produces finer mulch
- "Patented" blade holder, wraps around rotor drum for added strength
- Rear safety chain protection

Note: Available for 3-pt. hitch mounted tractors, PTO driven

| Model No. | Work Width | Overall Width | Depth | No. of Blades | Wt. |
|-----------|------------|---------------|-------|---------------|-------|
| CL150 | 59" | 71" | 39" | 30 | 2325# |
| CL175 | 69" | 81" | 39" | 33 | 2515# |
| CL200 | 79" | 91" | 39" | 36 | 2790# |

Built By:

seppi m

FLAIL MOWER/SHREDDERS

Hydraulic Driven, Skid Steer Mount



FEATURES:

- Shreds brush or prunings up to 1"
- Cutting height adjusts from 1" to 4"
- Unique floating hitch allows shredders to follow the contour of the ground
- Equipped with rear deflector which in open position discharges grass and allows speeds up to 6 M.P.H., and in closed position contains and further shreds brush to a finer mulch, but at a lower speed

This Mower/Shredder Series delivers excellent cutting, mulching and mowing action for material up to 1" in diameter. The mower features an automatic "STOP SAFE" system. If the mower is raised from operating position, the rotor blades "STOP" preventing objects being thrown at operator. The special floating linkage allows the mower/shredder to follow the terrain for even cut. For use in vineyards, berries and other narrow applications. Also, used for roadsides, parks, rental yards, and weed abatement.

- Variable displacement piston motor
- Heavy Y blades
- Both a relief valve and uni-directional valve are standard equipment
- Deck made of high tensile steel S420
- Front guards provide safety from flying material
- Comes complete with hydraulic hoses and quick couplers


Built By: **seppi m**

| Model No: | Mow Width | Total Width | No. of Blades | G.P.M. Required | Wt. |
|------------|-------------|-------------|---------------|-----------------|-------|
| SMWA155-HS | 5'-1" (61") | 5'-6" (66") | 54 | 16 to 39 | 980# |
| SMWA175-HS | 5'-9" (69") | 6'-2" (74") | 66 | 16 to 39 | 1095# |
| SMWA200-HS | 6'-7" (79") | 7'-1" (85") | 78 | 16 to 39 | 1160# |

ORCHARD BRUSH PROCESSOR

One pass processing into a fine mulch

The Gearmore pull type, PTO driven, self-feeding Brush Processor was designed to shred material up to 3" in diameter into a very fine mulch. The brush is fed through two hydraulic driven pick-up feed rotors into the processing chamber. The large 20" diameter rotor with fixed triple tipped tungsten carbide knives shreds the brush against six rows of drop forged re-cutter bars into finer material. This mulch is then forced through a fine mesh heavy steel screen to achieve the desired size.



- For tractors 95 to 140 H.P.
- Pull type brush processor, 1000 RPM P.T.O driven
- Processes brush up to 3" in diameter into a fine decomposable mulch
- 3-Tipped tungsten carbide fixed knives
- Two pick-up feed rotors that can be adjusted independently from 50 to 200 RPM
- 6 Rows of drop forged fixed, carbide tipped re-cutter bars
- Oil cooler with fan

- 5 Belt rotor drive
- Heavy ½" (12 mm) thick plate screen with 1" diamond shaped holes for final processing
- 29 Gallon hydraulic oil reservoir with filter
- Pair of dual rear wheels with dual hydraulic cylinders height adjustment
- Removable fines screen for oil cooler clean out
- Hardox lined ¼" (6 mm) inner hull lining for long life and superior durability
- Other widths available

| Model No: | Work Width | Total Width | Total Depth | Total Height | No. of Knives | Wt. |
|-----------|------------|-------------|-------------|--------------|---------------|-------|
| WBS225-G2 | 89" | 106" | 146" | 71" | 36 | 6400# |

ROTARY MOWERS

Finishing Mowers - Rear discharge, dual gauge wheels

We now have available rear discharge mowers featuring totally open rear deck with belt guards that allow the grass to be safely and smoothly discharged giving your turf that rich, manicured look. Some of the other outstanding features are: Free floating flex hitch, dual tires front and rear, self-tightening belt, and 40 H.P. gearbox.

FEATURES:

- Free floating, flex hitch system
- Heavy duty steel deck, with rear discharge
- Heavy duty cast iron gearbox
- Easy height adjustment
- Turf friendly, 9 x 3.50 - 4 ply solid rubber tires
- Anti-scalp front roller
- Fully baffled deck



| Model No. | Cutting Width | Blade Size | Blade Tip Speed - FPM | Pneumatic Tires | Wt. |
|---|---------------|-----------------|-----------------------|-----------------|------|
| RFM-60 | 60" | 1/4" x 2" x 20" | 17,985 FPM | 4 - 9 x 3.50 | 660# |
| RFM-72 | 72" | 1/4" x 2" x 24" | 18,463 FPM | 4 - 9 x 3.50 | 710# |
| RSFM-72* | 72" | 1/4" x 2" x 24" | 18,463 FPM | 4 - 9 x 3.50 | 720# |
| *Special belt with double V design helps to prevent slippage in rough mowing conditions | | | | | |



MDL. L-48-40-XB

- Cat. I, 3-point hitch
- Adj. cutting heights 1" - 6"
- Bolt-on replaceable side plates
- Round dished spindle pan
- Heat treated 1/2"x3" blades
- Adj. dual rubber tailwheels
- Std. front rubber shielding

ROTARY MOWER

Compact - With dual gauge wheels

Our **Rotary Mower** was developed to obtain maximum strength and stability. The strength was obtained by using the same gearbox, spindle assembly, blades and driveshaft that are used on our larger mowers. The stability was obtained by mounting the mower closer to the tractor with the addition of twin rubber tailwheels.

This combination of strength and stability allows the operator to mow in rough terrain with maximum control of the tractor and mower.

| Model No. | Cutting Width | Overall Width | Overall Depth | Wt. |
|------------|---------------|---------------|---------------|------|
| L-48-40-XB | 48" | 51" | 62" | 400# |

ROTARY MOWERS

Standard Duty - Shear pin or slip clutch

60" MOWER SHOWN WITH OPT. CHAIN SHIELDING



Cat. I
A.S.A.E.
Quick Hitch
Compatible

Our **200 Series Mowers** feature round back design for easy maneuvering in tight corners, around trees, fences, and other obstructions. The flexible floating hitch follows the contour of the terrain without putting stress on the mower and tractor.

FEATURES: Fully Welded Deck

- Cuts up to 1" diameter material
- Shielded series 4 PTO shaft
- Optional - chain safety shielding

FEATURES:

| | |
|-----------------|--------------------------|
| Hitch: | Cat. I, ASAE Q.H. |
| Gearbox: | 540 RPM |
| Deck Thickness: | 11 Gauge |
| Deck Depth: | 7 1/2" |
| Tailwheel: | 3 3/4"x15" Laminated |
| Cut Height: | 1" to 9" |
| Blade Size: | 1/2" x 3" |
| Driveshaft: | Shear Pin or Slip Clutch |

ROTARY MOWERS

Medium Duty - Floating hitch to follow contour of terrain

These **Gearmore Rotary Mowers** are the economical answer for medium duty use in weed and brush mowing. Special built-in features include floating hitch that follows the contour of the terrain, heavy round spindle pan to protect the gearbox, strong 8" I beam side channels for added strength, laminated tailwheel, and slip clutch driveshaft; all engineered to assure years of trouble-free service.

- Floating hitch design follows contour of terrain
- Heavy 8" I beam sides w/ribbed crossmembers
- Slip clutch driveshaft to prevent damage
- Forged heat treated blades and blade pins
- Optional safety shielding, front and rear
- Dual tailwheels for increased stability

| Model No: | Cutting Width | Overall Width | Overall Length | Tail Wheels | Gearbox H.P. | Wt. |
|-----------|---------------|---------------|----------------|-------------|--------------|-------|
| L60-60-HD | 60" | 62" | 86" | 1 | 60 H.P. | 800# |
| L72-60-HD | 72" | 74" | 92" | 2 | 60 H.P. | 1100# |
| L84-80-HD | 84" | 86" | 104" | 2 | 80 H.P. | 1480# |

L72-60HD SHOWN WITH OPT. CHAIN SHIELDING



| | |
|---------------|-------------|
| Side Rails: | 8" I Beams |
| Top Deck: | 3/16" Plate |
| Hitch: | Cat. II |
| Gearbox RPM: | 540 |
| Tailwheels: | Laminated |
| Blade Holder: | Spindle Pan |
| Blade Size: | 1/2" x 4" |
| Driveshaft: | Slip Clutch |



WARNING: *If operating mower near roads and/or where people are present, you must equip mower with deck shielding*

SEED PLANTER

High Density Planters - For planting leafy green produce

This **High Density Salad Seed Mechanical Planter** allows for planting rows as close as 1¼" apart. The polilatex sponge horizontal feed rollers are easy to remove for unloading seeds and cleaning before changing seeds. Tandem toolbars with 32 soil openers are adjustable and removable if wider row widths are required. Four crank adjustment with planting depth gauges for precise raising and lowering of soil openers. Front and rear stainless steel rollers insure a smooth level bed top for mechanical harvesting. One of the many unique features is the positive ground drive. Thus the planter obtains equal seed distribution no matter what the speed of the tractor.



| Model No: | Description | Width | Depth | Wt. |
|---------------|---|---------|-------|-------|
| AI-620-SNT-32 | Salad Seed Planter - 32 Lines, 2" Spacing | 6' - 2" | 6' | 1200# |



Seeding Distributors



Easy Distributor Disassembly



Easy Disassembly of Rollers

SEED PLANTER

Folding Planters - For 3 - 80" or 3 - 88" rows



The **Gearmore Precision Vacuum Planters** are designed for extremely accurate vegetable seed placement. The P.T.O. driven turbine fan or optional hydraulic drive creates a vacuum that draws seeds against the seed plates. Inner and outer singulators remove doubles to insure that individual seeds are secured to the vacuum hole. At the seed release point, vacuum is cut off and the seed is deposited in the furrow. The air compressor then injects a short blast of air to insure the hole is clean for the next seed. Easy to operate and maintain, this durable precision planter efficiently handles the smallest of seeds either raw or coated.



*We design and assemble planters
to your specifications*

VACUUM PLANTERS


Custom Built Planting Systems - The precision vegetable seeder



**STD. 8 ROW VEGETABLE
PLANTER SHOWN**

We custom build planting systems to growers individual requirements, see our website for details.

The **Gearmore Precision Vacuum Planters** are designed for extremely accurate vegetable seed placement. The P.T.O. driven turbine fan or optional hydraulic drive creates a vacuum that draws seeds against the seed plates. Inner and outer singulators remove doubles to insure that individual seeds are secured to the vacuum hole. At the seed release point, vacuum is cut off and the seed is deposited in the furrow. The air compressor then injects a short blast of air to insure the hole is clean for the next seed. Easy to operate and maintain, this durable precision planter efficiently handles the smallest of seeds either raw or coated.



BASKET RAKES

Generation 3 Basket Rakes - Designed for heavy duty useage



**MODEL 2030G3-7 SHOWN
W/OPT. GAUGE WHEELS**



Fluffy, Uniform Windrows



Rake in Transport Position

Twinstar Generation 3 Basket Rakes have 8 new outstanding features that improves the operation over the Generation 2 rakes. Twinstar Basket Rakes produce the cleanest hay on the market. Cleaner hay brings higher returns and provides the highest quality feed to ensure animals receive proper nutrients. Research has documented that basket raked hay contains significantly less contaminants (dirt, rocks, and debris) and has less leaf loss compared to traditional finger wheel and rotary rakes. Twinstar 7-Bar Rakes are available in 27' and 30' raking widths.

VERSATILE TWINSTAR G3 FEATURES:

- Seven function electric/hydraulic valve and control box plus baskets on / off switch
- Independent raising & lowering of left / right baskets or together
- Faster raising and lowering of baskets
- Higher torque basket drive motors are standard equipment
- New time tested solid rubber gauge wheels
- Split hoses with JIC fittings at end of slide tubes for serviceability
- Improved double-shear angle cylinder mounts
- Transport light kit per ASABE / ANSIS279

| Model No: | 2027G3-7 | 2030G3-7 |
|-------------------------|--|--|
| Maximum Raking Width: | Up to 27' | Up to 30' |
| Transport Width: | 10' - 9" | 10' - 9" |
| Overall Length: | 19' - 5" | 20' - 2" |
| Basket Reel Speed: | Maximum 90 RPM | Maximum 90 RPM |
| Rubber Mounted Tines: | Std: 154 per basket-Option: 224 | Std: 175 per basket-Option: 259 |
| Operating Speed: | Up to 10 MPH | Up to 10 MPH |
| Hydraulic Requirements: | 12 GPM @ 2000 PSI Tractor with single hydraulic remotes | 12 GPM @ 2000 PSI Tractor with single hydraulic remotes |
| Tire Size: | (4) LT235/75R15 | (4) LT235/75R15 |
| Approximate Weight: | 5100# | 5600# |

Optional equipment includes: Front and rear gauge wheels (highly recommended), full tines (for heavier crop conditions), 2-5/16" ball hitch, basket angle stop kit, and walking beams.

Built By: **TWINSTAR**

RAKES

Landscape Rakes - For 30 to 60 horsepower tractors

MODEL LRU-7 RAKE SHOWN



Optional equipment:

- ~ Dual caster gauge wheels
- ~ Teeth stiffeners

These *Landscape Rakes* are ideal for general grooming, soil preparation, removing rocks, roots and debris, and spreading crushed rock or top soil. Five forward and reverse angle positions for windrowing material. The reverse positions are great for pushing material into low spots. We have three widths of rakes available for tractors 30 to 60 horsepower.



Optional Dual Caster Gauge Wheels

| Model No. | Width | Horsepower | No. of Teeth | Weight |
|-----------|-------|---------------|--------------|--------|
| LRU-6 | 72" | 30 to 60 H.P. | 36 | 240# |
| LRU-7 | 84" | 30 to 60 H.P. | 42 | 270# |
| LRU-8 | 96" | 30 to 60 H.P. | 48 | 300# |

Features for LRU Series:

- Cat. I, A.S.A.E. quick hitch compatible
- For tractors up to 60 H.P.
- 5/16" x 1" x 15" High carbon steel teeth
- 1" Spacing between teeth
- Five forward and reverse angle settings
- Frame is made of 3/16" x 4" x 4" steel tubing

RIDGERS

Adjustable Gangs - Built for heavy duty use



FEATURES:

- Cat. II, 3-point A.S.A.E. quick hitch
- 4" x 6" x 1/4" Wall x 8' long toolbar
- Gangs adjust for tilt and pitch
- Self aligning trunnion 1 1/2" bearings
- Available in 3 or 4 blade
- Blades on 9" centers with cast iron spacers
- Parking stand
- Optional mud scrapers
- Available with blockers

SPECIFICATIONS:

| Model No. | Description | Required Horsepower | Weight |
|-----------|---|---------------------|--------|
| BE222-3 | 3 Blade Ridger with 22", 24", & 26" Blades | 60 Minimum H.P. | 1000# |
| BE422-4 | 4 Blade Ridger with 22", 24", 26", & 28" Blades | 60 Minimum H.P. | 1080# |

Single Shank - 3 Sizes available for 25, 50, & 75 HP Tractors

The **GR100** is for tractors up to 25 H.P. These rippers are great for cutting narrow trenches for irrigation pipe. The optional 15" furrower shovel digs a smooth trench for water flow.

The **GR200** is for tractors up to 50 H.P. This unit is recommended for breaking up compacted soil to increase root growth and yields.

The **GR300** is for tractors up to 75 H.P. and was designed for heavier duty use. Thus, the ripper can be used for high horsepower tractors. This ripper is recommended when deep ripping is required.



| Model No: | H.P. Rating | Frame Tube Size | Shank Length | Shank Size | Hitch | Shear Bolt Protection | Optional 12" Furrower | Parking Stands | Weight |
|-----------|-------------|-----------------|--------------|------------|---------|-----------------------|-----------------------|----------------|--------|
| GR100 | Up to 25 | 3" x 3" | 19" | 1" x 4" | Cat. I | Yes | Yes | No | 85# |
| GR200 * | Up to 50 | 4" x 4" | 22" | 1" x 6" | Cat. I | Yes | No | Standard | 100# |
| GR300 * | Up to 75 | 4" x 8" | 27" | 1" x 10" | Cat. II | Yes | No | Standard | 240# |

* Also available with hard faced shanks and points.

Tractors have to make many passes through vineyards and orchards. This creates hard pan under the tractor tires. From time to time, it is recommended to rip that area to aerate the soil for better water penetration to increase root growth. The spread width of the ripping shanks can be set to the tractor tire centers and this then shatters the soil over the compacted area up to 18" deep. These rippers have two 4" x 6" beams for added strength. Models available for all popular vineyard row spacings.

- Cat. I & II, 3-point, ASAE quick hitch
- 2 - Adj. shanks for ripping soil up to 18" deep
- Adj. bolt-on shank brackets can be set for different tractor tire tread widths
- Shear bolt design, shanks swing up if hitting obstructions
- Shanks are made of 1" x 6 1/2" x 22" steel
- Main beam 4" x 6" x 1/4" wall tubing
- Replaceable high carbon, heat treated points
- Clevis type hitch bracket
- Parking stand

Option:

- ~ Hard faced shanks & points

TIRE TRACK RIPPER

Breaks up "hard pan" created by tractor tires



| Model No. | Description | For Row Widths | Beam Width | Adj. Shank Centers | Wt. |
|-----------|--------------|----------------|------------|--------------------|------|
| R2-55 | 3-Pt. Ripper | 6' (72") | 55" | 38" to 48" | 320# |
| R2-67 | 3-Pt. Ripper | 7' (84") | 67" | 40" to 60" | 350# |
| R2-72 | 3-Pt. Ripper | 8' (96") | 72" | 48" to 66" | 360# |
| R2-96 | 3-Pt. Ripper | 10' (120") | 96" | 60" to 90" | 390# |

V-RIPPERS

Cat. 1 - 30 to 50 HP - Narrow & wider widths for vineyards or farm use



These *V-Rippers* come in narrow widths for vineyards and berries and wider widths for general farm use. The "V" design main beam and curved shanks reduce horsepower requirements. The deep ripping obtains excellent soil aeration, which allows greater water penetration and absorption. Also increases root growth and penetration. All this adds up to better crops and higher profits.

FEATURES:

- For ripping up to 18" deep
- Heavy 4" x 6" beam construction to insure long life
- 1" x 6" x 22" Shanks
- Shanks adjustable with shear bolt protection
- Replaceable high carbon, heat-treated points

SPECIFICATIONS:

| Model No: | No. of Shanks | Beam Width | Weight |
|-----------|---------------|------------|--------|
| R3-50 | 3 | 50" | 420# |
| R3-60 | 3 | 60" | 435# |
| R3-70 | 3 | 70" | 450# |
| R5-60 | 5 | 60" | 550# |
| R5-70 | 5 | 70" | 570# |

V-RIPPERS

Cat. 2 & 3 - 80 to 195 HP - Deep ripping aids in soil aeration



FEATURES:

- "V" design & curved shanks reduce horsepower requirements
- Adjustable shanks
- Shear bolt protection
- Replaceable high carbon, heat-treated points
- Parking stands that store in frame

SPECIFICATIONS:

| Model No: | No. of Shanks | Toolbar Width | Frame Tube Size | Shank | Shank Size | Hitch | Maximum H.P. | Weight |
|-----------|---------------|---------------|-----------------|-------|----------------|------------|--------------|--------|
| VR3 | 3 | 84" | 4" x 6" | 27" | 1" Parabolic | Cat. 2 | 80 HP | 750 # |
| VR3-HF | 3 | 84" | 4" x 6" | 27" | 1" Parabolic | Cat. 2 | 80 HP | 759# |
| 334 | 3 | 84" | 5" x 7" | 34" | 1 ¼" Parabolic | Cat. 2 & 3 | 85 HP | 850# |
| 334-HF | 3 | 84" | 5" x 7" | 34" | 1 ¼" Parabolic | Cat. 2 & 3 | 85 HP | 865# |
| 534-HF | 5 | 144" | 5" x 7" | 34" | 1 ¼" Parabolic | Cat. 2 & 3 | 140 HP | 1725# |
| 734-HF | 7 | 144" | 5" x 7" | 34" | 1 ¼" Parabolic | Cat. 2 & 3 | 195 HP | 2110# |

"GE" Series - For extreme duty sub-soiling

- Cat. 3 & 4N 3-point A.S.A.E. quick hitch
- Frame - 6" x 8" x 3/8" structural tubing
- "L" style shanks are 1 1/2" thick by 36" long
- 1" Thick "plow steel" lower hitch brackets
- Double dual steel wheels, 8" wide x 30" dia. (Optional on 5 shank rippers)
- Chrome shin guards on shanks - replaceable
- Heavy duty chrome chisel points - replaceable
- 1 1/4" Grade 5 swing shank bolts
- 1 1/4" Grade 2 shear shank bolts

Options:

- ~ SW30 - Set of steel wheels for 5 shank ripper
- ~ WW16 - Set of dual 11L x 16 rubber tires for 5 shank ripper
- ~ WW16-7 - Set of dual 11L x 16 rubber tires in lieu of steel wheels for 7 shank ripper

- Heavy duty tongue assembly
- Frame made of 6"x8"x3/8" thick structural tubing
- "L" style shanks are 1 1/2" thick x 36" long
- Replaceable chrome shin guards on shanks
- 15.5L x 22.5 Tires
- 5" x 18" Hydraulic cylinders with depth stops
- Parking stands, front and rear
- Requires 45 horsepower per shank

Options:

- ~ Rear hitch



CAUTION -

You must lower the rear parking stands and lock in place before uncoupling from the tractor.

MODEL GE36-24 SHOWN



| Model No. | No. of Shanks | Shank Spacing | Frame Width | Weight |
|-----------|---------------|---------------|-------------|--------|
| GE536-24 | 5 | 24" | 8 Feet | 3600# |
| GE536-30 | 5 | 30" | 10 Feet | 3820# |
| GE736-24 | 7 | 24" | 12 Feet | 4920# |
| GE736-30 | 7 | 30" | 15 Feet | 5050# |

RIPPERS

"BE" Series - Pull type, heavy duty tongue



| Model No. | No. of Shanks | Shank Spacing |
|-------------|---------------|---------------|
| BE5PRS36-30 | 5 | 30" |
| BE7PRS36-24 | 7 | 24" |
| BE7PRS36-30 | 7 | 30" |
| BE7PRS36-36 | 7 | 36" |

Built By: **BWI**Implement

BOX SCRAPERS

"BSL" & "BB" Series - All welded top mast, no assembly required

Cat. I
A.S.A.E.
Quick Hitch
Compatible



"BSL" Series

- For compact tractors up to 30 H.P.
- Clevis type hitch brackets
- Side plates are ¼" x 16" x 22"
- Main beam ¼" x 4" x 4" tubing
- Heat treated scarifier shanks w/replaceable points

| Model No. | Cut. Width | No. of Shanks | Weight |
|-----------|------------|---------------|--------|
| BSL-42 | 42" | 3 | 275# |
| BSL-48 | 48" | 4 | 290# |



"BB" Series

- For tractors up to 40 H.P.
- Main beam - ¼" x 4" x 4" tubing
- Heat treated shanks with replaceable points
- 2 Depth settings on scarifier shanks
- Side plates are ¼" x 16" x 24"

| Model No. | Width | No. of Shanks | Weight |
|-----------|-------|---------------|--------|
| BB-48 | 48" | 4 | 315# |
| BB-54 | 54" | 4 | 350# |
| BB-60 | 60" | 5 | 365# |
| BB-66 | 66" | 5 | 390# |
| BB-72 | 72" | 5 | 400# |

*Standard color is black - most tractor colors available
at no additional charge*

TOP & TILT KITS

Valve/Bracket Assy & Cylinders - Box scrapers are more versatile



Valve & Bracket Assembly



Top & Tilt Cylinders

To make box scrapers more versatile, nothing works better than being able to control the tilt and pitch of the implement. Grading jobs are more accurate because you have complete control to develop the slopes you require when landscaping, building roads, etc.

Valve & Bracket Assemblies

- Valves are available in 1, 2, 3 & 4 spool
- Valves handle flows from 15 to 17 GPM (10-13 GPM through the ports) @ 3000 PSI
- Brackets available for most popular models
- Bracket assemblies consist of: rollbar clamp, adjustable arm with valve mounting and safety valve cover

Cylinders

- Special built-in oil flow restrictors which insure smooth operation
- Specially designed to fit your tractor
- Cylinders available in 2", 2 ½" & 3" bore, depending on the tractor size

BOX SCRAPERS

"GBS" Series - Manual & hydraulic shank retracting

Our Box Scrapers feature clean modern design with all welded construction for added strength. Thus, no assembly required.

Whether you want to landscape, terrace, back-fill, scarify, level, or do general clean-up, the Gearmore Box Scrapers will fit your needs.


FEATURES:

- For tractors 20 to 45 horsepower
- Cat. I, A.S.A.E. quick hitch
- 2 Types of shank adjustment: MANUAL or HYDRAULIC
- Special shank pockets for added strength
- Adjustable heat-treated scarifier shanks with replaceable points
- Reversible ½" x 6" cutting edges, front and rear
- A-frame mast - ½" thick x 6" wide
- Standard color is black - most tractor colors are available at no additional charge

GBS SERIES MANUAL SHANK



GBS/H SERIES HYDRAULIC SHANK



SPECIFICATIONS:

| Cutting Width | Overall Width | No. of Shanks | Weights | |
|---------------|---------------|---------------|---------|-------|
| | | | GBS | GBS/H |
| 42" | 42 ½" | 3 | 330# | |
| 48" | 48 ½" | 4 | 355# | 405# |
| 54" | 54 ½" | 4 | 395# | 435# |
| 60" | 60 ½" | 5 | 440# | 480# |
| 66" | 66 ½" | 5 | 490# | 505# |
| 72" | 72 ¾" | 6 | 540# | 575# |
| 76" | 76 ¾" | 6 | 560# | 600# |
| 80" | 80 ¾" | 7 | 600# | 630# |
| 84" | 84 ¾" | 7 | 620# | |

BOX SCRAPERS

Industrial "2G2M" Series - For tractors up to 60 HP manual shanks



FEATURES:

- Cat. I, ASAE Quick hitch
- All welded construction
- Top mast welded around 2 sides of main beam for added strength
- Heavy duty $\frac{1}{2}$ " thick shank pockets welded behind main beam for additional strength
- Easy quick shank adjustment
- Double plated rear moldboard - 22" high
- Box depth is 29"
- Two position, heat-treated shanks with replaceable points
- Main beam is $\frac{3}{8}$ " x 4" x 4"
- Side plates are $\frac{3}{8}$ " x 22" x 33"
- Two cutting edges - $\frac{1}{2}$ " x 6" heat treated, reversible, bolt-on

This series of scrapers feature the same design as our 2G2 Hydraulic Scarifier Scrapers, except with manual adjustable shanks. The major feature of the scrapers is heavy shank pockets which are attached to the rear on the main beam for added strength. The shank locking pins can quickly be changed to obtain shank settings of 2" and 4" deep.

These scrapers are great for ripping, leveling, finish grading, backfilling, and moving the soil to desired locations.

SPECIFICATIONS:


| Model No. | Working Width | Overall Width | No. of Shanks | Weight |
|-----------|---------------|--------------------|---------------|--------|
| 2G2M-66 | 66" | 66 $\frac{3}{4}$ " | 6 | 665# |
| 2G2M-72 | 72" | 72 $\frac{3}{4}$ " | 6 | 685# |
| 2G2M-76 | 76" | 76 $\frac{3}{4}$ " | 6 | 705# |
| 2G2M-84 | 84" | 84 $\frac{3}{4}$ " | 7 | 790# |

BOX SCRAPERS

Industrial "2G" Series - For tractors 20 to 60 HP - hydraulic shanks

The **2G1 Series Scrapers** are designed especially for small compact tractors. Available in widths of 42", 48", 54" & 60" for tractors from 20 to 50 HP, 2 or 4 wheel drive.

The **2G2 Series Scrapers** are ideal for general landscape work such as: terracing, back-filling, scarifying and leveling the soil. Available in widths of 60", 66", 72", 76", & 84" for tractors from 40 to 60 HP, 2 or 4 wheel drive. Now with bushings on 3-point hitch.



Cylinder raises scarifier beam



1 1/2" Dia. scarifier locking pin



"2G1" SERIES

Cat. I
A.S.A.E.
Quick Hitch
Compatible



"2G2" SERIES

- Unique hydraulic scarifier system raises scarifier to high clearance position and lowers beam to working position plus automatically self-locks with heavy hardened pin
- Available in fixed or floating tailboard
- Two position, forged, heat-treated shanks with replaceable points
- 2 1/2" x 6" Reversible heat-treated cutting edges, front and rear
- Non-rotating pins or replaceable bushings at all pivot points
- Heavy plate top mast for added strength
- Cat. I clevis lower hitch brackets


Unique hydraulic scarifier system raises scarifier to high clearance position and lowers beam to working position plus automatically self-locks with heavy hardened pin

| Series | 2G1 Series | | | | 2G2 Series | | | | |
|--|----------------|--------|--------|--------|----------------|--------|--------|--------|--------|
| Model: | 2G1-42 | 2G1-48 | 2G1-54 | 2G1-60 | 2G2-60 | 2G2-66 | 2G2-72 | 2G2-76 | 2G2-84 |
| Working Width: | 42" | 48" | 54" | 60" | 60" | 66" | 72" | 76" | 84" |
| Overall Width: | 42 ½" | 48 ½" | 54 ½" | 60 ½" | 60 ¾" | 66 ¾" | 72 ¾" | 76 ¾" | 84 ¾" |
| No. of Shanks: | 4 | 4 | 5 | 5 | 5 | 6 | 7 | 7 | 8 |
| Approx. Weight: | 410# | 445# | 480# | 520# | 770# | 830# | 860# | 890# | 920# |
| Moldboard Ht: | 18" | | | | 21" | | | | |
| Main Beam: | ¼" x 4" x 4" | | | | ⅜" x 4" x 4" | | | | |
| Side Plates: | ¼" x 18" x 28" | | | | ⅜" x 21" x 33" | | | | |
| Available With Fixed or Floating Tailboard | | | | | | | | | |

BOX SCRAPERS

Industrial "4G" Series - For tractors 50 to 100 HP - hydraulic shanks

The **4G2 Series Scrapers** are designed to handle the demanding work of commercial landscaping and finish grading with its floating tailboard. Available in widths of 72", 76", 80" & 84" for tractors 50 to 80 HP, 2 or 4 wheel drive, A.S.A.E. quick hitch. All equipped with hydraulic scarifiers.




"4G4" SERIES

"4G2" SERIES


"4G5" SERIES

The **4G4 Series Scrapers** are extremely rugged and ideal for construction site clean-up, trench back-filling and demanding material handling. Available in widths of 80", 84" & 88" for tractors 60 to 100 HP, 2 or 4 wheel drive.

The **4G5 Series Scrapers** were developed for grading contractors with high horsepower tractors that demand floating tailboard scrapers. The scraper was designed with 4G4 strength, but the versatility of the floating tailboard. In float position, the cutting of hard material is much greater over fixed tailboard units. Available in widths of 80" & 84" for tractors 65 to 85 HP, 2 or 4 wheel drive.



Cylinder & heavy linkage brackets



Solid steel hook and lock assembly



Top mast wraps around 3 sides

- 2 ½" Cylinders in lieu of 3"
- Floating and fixed tailboard models
- 2 Position, forged, heat-treated shanks w/replaceable points
- Main beam ¾" x 5" x 5" tubing
- Moldboard height of 24"
- Non-rotating pins or replaceable bushings at all pivot points

SPECIFICATIONS:

| Series | 4G2 Series | | | | 4G4 Series | | | 4G5 Series | |
|-----------------|----------------|--------|--------|--------|----------------|--------|--------|----------------|--------|
| Model: | 4G2-72 | 4G2-76 | 4G2-80 | 4G2-84 | 4G4-80 | 4G4-84 | 4G4-88 | 4G5-80 | 4G5-84 |
| Working Width: | 72" | 76" | 80" | 84" | 80" | 84" | 88" | 80" | 84" |
| Overall Width: | 73" | 77" | 81" | 85" | 81" | 85" | 89" | 81" | 85" |
| Approx. Weight: | 1150# | 1190# | 1220# | 1260# | 1340# | 1400# | 1470# | 1350# | 1410# |
| Side Plates: | ½" x 24" x 32" | | | | ½" x 24" x 35" | | | ½" x 24" x 35" | |
| HP Rating: | 50 to 80 H.P. | | | | 60 to 100 H.P. | | | 65 to 85 H.P. | |

SPECIFICATIONS:

| Model No. | Width of Cut | Capacity | Weight |
|--|--------------|------------|--------|
| CS72 | 72" | 36 cu. ft. | 660# |
| CS84 | 84" | 42 cu. ft. | 700# |
| CS96 | 96" | 48 cu. ft. | 740# |
| CS120 | 120" | 60 cu. ft. | 800# |
| ½" x 6" Single reversible high-carbon cutting edge | | | |

"CS" SERIES



FEATURES:

- Designed to move a lot of material fast
- Combination Cat. I and II clevis hitch
- Square tube main beam 4" x 4" x ¼"
- Rear moldboard ¼" thick
- Heavy duty, large capacity, all welded construction
- Features 24" high x 36" deep x ⅜" thick side plates
- Combination Cat. I and II clevis hitch
- Stepped, non-turning, combination Cat. I & II lower link pins

FEATURES:

- Extremely versatile-countless jobs can be done all year round. Level ditches, clean sheds and pens, repair roads, spread gravel, general earth-moving
- Hydraulically operated and controlled from your tractor seat
- Now with removable tongue
- Highly maneuverable
- Cutting edges are ½" x 6" high carbon and reversible
- Scrapers come standard with tires, cylinder, and hoses
- Clevis type hitch

Option:

- ~ Tilt axle assembly

SCRAPERS, DRAG

Compact Drag Scrapers - Pull Type

"CD" SERIES



Specifications:

| | |
|----------------|--|
| Working Width: | 5, 6, and 7 Foot |
| Moldboard: | ¼" x 18" |
| Side Plates: | ⅜" x 18" x 24" |
| Tongue: | Removable ⅜" x 3" x 3" |
| Tires: | Equipped with (2) 5.70-8 Tires |
| Hydraulics: | 2" x 6" Double acting cylinder & hoses |
| Clearance: | Raised: 12" - Cuts: 3" Below grade |
| Approx. HP: | 25 to 50 Horsepower |
| Capacity: | (5') - ⅞ cu. yd., (6') - ½ cu. yd., (7') ⅝ cu. yd. |
| Weight: | (5') - 500#, (6') - 550#, (7') - 600# |

SCRAPERS, DRAG

All Purpose Series - Easy way to carry, grade & spread material

MODEL AP10 SHOWN WITH OPT. DUAL WHEELS & TILT



- For tractors 70 to 120 horsepower
- Working widths of 8, 10, & 12 foot
- 3/8" x 24" x 36" Deep side plate
- Clearance of 23" raised and 5" below grade
- Hydraulically operated from the tractor seat
- Moldboard 1/4" plate, 24" high
- Main cross beam 4" x 4" tubing
- 3" x 8" Double acting cylinder and hoses
- Ribbed implement tires - 9.5L - 15SL
- Bolt-on hitch with swivel ball

Our **Drag Scrapers** are an excellent implement for carrying and spreading all types of material. Landscapers find the scrapers great for general grading and spreading exact depths of top soil. Contractors set the cutting edge to spread different depths of gravel for rebuilding roads and storage yards. Dairy men find the scrapers best for moving you know what. The Drag Scrapers feature a removable 4" x 4" beam tongue that extends to the rear moldboard and is held in place by a 5" x 5" heavy gusseted tube. This feature gives added strength at the point of the most stress.

| Model No. | Width | Capacity | Weight |
|-----------|-------|---------------|--------|
| AP8 | 8' | 1 3/4 cu. yd. | 1360# |
| AP10 | 10' | 2 1/4 cu. yd. | 1450# |
| AP12 | 12' | 3 cu. yd. | 1560# |

Options:

- ~ Tilt Axle w/cylinder & hoses
- ~ Dual Wheels
- ~ Bolt-on Weight Boxes

SCRAPERS, DRAG

High Capacity - Drag and deposit large amounts of material



MODEL HC10 SHOWN

Options:

- ~ Tilt Axle w/cylinder & hoses
- ~ Dual Wheels
- ~ Bolt-on Weight Boxes

| Model No. | Width | Capacity | Weight |
|-----------|-------|---------------|--------|
| HC8 | 8' | 2 1/2 cu. yd. | 1450# |
| HC10 | 10' | 3 1/4 cu. yd. | 1630# |
| HC12 | 12' | 3 3/4 cu. yd. | 1840# |
| HC14 | 14' | 4 1/4 cu. yd. | 2050# |

NOTE: Tractor colors are available upon request - no charge

The **"HC" High Capacity Series of Drag Scrapers** feature heavy, large side plates - 1/2" thick. These side plates are 30" high by 40" deep, thus allowing for dragging and depositing large amounts of material. Like the "AP" series, the beam tongue extends to the rear moldboard and is held in place by a 5" x 5" heavy gusseted tube. The new axle assembly is built with 4" x 2" tubing. The larger dairies and feedlots find these scrapers best for their operations.

- For tractors 70 to 120 horsepower
- Working widths of 8, 10, 12 & 14 foot
- 1/2" x 30" x 40" Deep side plates
- Clearance of 23" raised and 5" below grade
- Hydraulically operated from the tractor seat
- Moldboard 1/4" plate, 30" high
- Internal braces to side plates and moldboard
- Main cross beam 4" x 4" tubing
- 3" x 8" Double acting cylinder and hoses
- Ribbed implement tires - 9.5L x 15
- Bolt-on swivel slotted hitch

SCRAPERS, GRADING

Compact, Industrial & Skid Steer Series - Best for repairing & maintaining roads

The **Gearmore Grading Scrapers** were designed to perform many different tasks, such as: landscaping, road repair, arena maintenance, etc. Many unique features enable the operator to do a number of different tasks, no matter what the soil conditions.

General Landscaping - The deep ripping scarifier shanks will break-up the hardest of soils. Dual cutting blade will allow for the movement of large amounts of material when required. To finish grade, set the shanks in the storage position and lightly grade, to finish your landscaping project.

Repairing Roads - The dual blade flow through action cuts out high spots, fills holes and moves material from the edge of the road toward the center, thus achieving a smooth finished road.

- Quick hitch compatible
- For tractors from 20 to 80 H.P.
- Heavy steel tubing main front beam
- Heavy steel tubing rear support beam
- Heat treated scarifier shanks with replaceable points
- Shanks adjust to ripping & storage positions
- Two ½" x 6" heat treated reversible beveled cutting edges
- Easy to adjust cutting edges with settings of 1 to 1 ½" below side panels (preset at ¼")
- Formed side panels capture and retain material
- ¼" x 2" Replaceable skid plates on side panels



**NOW AVAILABLE
LESS SHANKS**



SPECIFICATIONS:

| Model No. | Hitch Type | Cutting Width | Overall Width | Min. H.P. | Main Beam | Weight |
|-----------|-------------|---------------|---------------|-----------|-----------|--------|
| GS4 | Cat. I | 48" | 52" | 20 H.P. | 3" x 3" | 415# |
| GS5 | Cat. I | 60" | 64" | 25 H.P. | 3" x 3" | 450# |
| GS6 | Cat. I | 72" | 76" | 30 H.P. | 3" x 3" | 505# |
| GSI7-SS | Skid Steer | 84" | 89" | 45 H.P. | 5" x 5" | 820# |
| GSI7 | Cat. I & II | 84" | 89" | 45 H.P. | 5" x 5" | 830# |
| GSI8 | Cat. II | 96" | 101" | 50 H.P. | 5" x 5" | 860# |
| GSI10 | Cat. II | 120" | 125" | 70 H.P. | 5" x 5" | 1020# |
| GSI12 | Cat. II | 144" | 149" | 80 H.P. | 5" x 5" | 1140# |

SCRAPERS, GRADING

Available with or without laser system



FEATURES:

- SSL Quick Attach mounting bracket
- Push pull design pushes and pulls material for fine grading
- Heavy stable platform for fine grading
- Front mounted swivel gauge wheels
- Foam filled tires
- Two cylinders provide cross slope operations
- Two moldboard cutting edges are ½" thick by 6" and reversible
- Side plates have adjustable cutting edges
- Convex mirror allows for material visibility
- Two 1 ½" diameter mast poles
- Grip brackets for easy, safe entry to tractor
- Comes with proportional valve, hoses and fittings

Requirements:

- ~ Auxiliary hydraulic and tractor must be equipped with case drain

THREE DIMENSIONAL PRECISION GRADING MADE EASY

The **PD Series** comes ready to produce precise grading by working seamlessly with the on-site horizontal laser reference alongside highly accurate satellite measurements for the vertical reference points. Level Best also comes ready to use with GPS, total stations or sonic technology.

The **Grading Box System** automatically reads the grade and makes adjustments dozens of times per second. This gives the operator far more comfortable working conditions because it's so smooth, and the precision grade is highly accurate to 0.1 of an inch. The result is a new level of operational ease and accuracy for precision grading even for complex contours.

SPECIFICATIONS:

| MODEL | BOX SIZE | PTO H.P.* | BOX CAPACITY | | WT. |
|--|----------|-----------|--------------|-----------|------------|
| Skid Steer Para-Level Grading Box, Double | | | Front | Rear | |
| PL72 | 6' | 60 + | 11.5 cu. ft. | 7 cu. ft. | 2,020 lbs. |
| PL84 | 7' | 70 + | 13.4 cu. ft. | 8 cu. ft. | 2,070 lbs. |
| PL96 | 8' | 80 + | 15.3 cu. ft. | 9 cu. ft. | 2,155 lbs. |
| * Recommended horsepower under optimal conditions. | | | | | |

Built By: **Level Best®**

SCRAPERS, GRADING

3-Point hitch models for wheel tractors

The mid-sized TS and TD Series Grading Boxes fit a wide range of wheel tractors and are a popular choice for many contractors. They combine flexibility, and outstanding durability over time in construction applications. The grading boxes are precise grading to 1/10 of an inch, and have no equal market.

High performance features include greaseless composite bushings, reversible cutting edges on four sides, and highway grade wheel bearings for extended service life. Grading boxes feature an exclusive hydraulic valve system that make dozens of positional adjustments every second. The result is the smoothest continuous operation available in the market for precision grading. The large box capacity carries material where you need it so you will produce a more precise finish in far less time.



**MODEL TS84
SHOWN**

| Model | Width | Capacity | Tractor Weight | Wt. |
|-----------|-------|----------------------|--------------------|------------|
| TS72/TD72 | 72" | 17.0 ft ³ | 3,000 - 4,500 lbs. | 1210 lbs. |
| TS84/TD84 | 84" | 19.9 ft ³ | 3,500 - 5,300 lbs. | 1,305 lbs. |
| TS96/TD96 | 96" | 22.8 ft ³ | 4,000 - 6,000 lbs. | 1,370 lbs. |

NOTE: TS Models have single mast, TD models have dual masts

Laser Mounted Grading Systems were designed to replace the traditional three person grading crew with a single operator. The units will finish grade elevations to within 1/4 inch. The laser controls are easy to learn and use. As the operator grades, the system's receiver detects laser light from the rotating beacon and transmits a signal to the scraper hydraulic controls. The hydraulic valve uses the signal from the receiver and automatically lowers or raises the grading box to the required grade. Precise finish grade is attained when the "on grade" light remains illuminated.

To make grading scrapers into laser grading scraper 3 components are required:

1. Hydraulic System
2. Laser System
3. Tripod Mounted Rotating Laser Beacon

1. HYDRAULIC PACKAGE

Consists of digitally proportional valve, hoses, fittings, & hardware for the following laser systems:

- Apache - Trimble, Topcon

2. LASER CONTROLS

Consist of control panel, 360° sensor, cables, and manual override.

- Apache - Trimble, Topcon

3. ROTATING LASER BEACONS

Tripod mounted rotating laser beacons - single slope or dual slope.

ROTATING LASER BEACONS

- Tripod mounted rotating laser beacons provide either single or dual/cross slope features
- Automatic or manual programming with remote
- Self leveling and H.I. Alert
- 750 Foot range
- Tripod, Grade Rod, and Detectors suitably matched to application



CCH/GX400



Leica Rugby 680



Apache



Hydraulic Pkg.

Built By:

Level Best®

GRADER BLADE

Precision grading with track loader



The Grading Blade precise grades to within 0.1" of specifications with laser system. This will let you reduce material overage estimates. You can work in windrows with the ability to adjust the working width of your precision grade. The blade also allows you to cut ditches, slice top soil, crow roads and fields. This extreme duty Grading Blade achieves a smooth operating system and legendary Level Best performance.

FEATURES:

- Heavy SSL quick attach mounting bracket
- Mounts to skid steers and track loaders
- Available with or without laser system
- Reinforced moldboard 20" high by 108" long
- Moldboard cutting edge is ¾" thick by 6" and reversible
- Large tubing main frame
- Tubing/pivot beam for gauge wheels
- Front mounted flotation gauge wheels, rotate up to +/- 30 degrees
- Blade side shift +/- 13 inches
- Maximum blade tilt with one cylinder up and one cylinder down - 24.5 degrees
- Grip bracket steps for easy, safe entry to tractor
- Come with all hydraulic hoses and JIC couplers

OPTION:
~ End plates

SPECIFICATIONS:

| MODEL NUMBER | DESCRIPTION | GRADING WIDTH | GRADING DEPTH | BLADE LIFT | MACHINE WEIGHT |
|--------------|--------------|---------------|---------------|------------|----------------|
| GB108 | Grader Blade | 108" (9') | 7.43" | 6.94" | 2,620 lbs. |

Built By:
Level Best®

ATTACHMENTS

Skid Steer Attachments - Skid steer & track loader are more productive

Dozer Blade



- Available in widths of 84" and 96"
- Rated for tractors up to 110 H.P.
- Electro hydraulic controlled angle and tilt
- Heavy moldboard - .31" thick and 28" high
- Replaceable cutting edge and skid shoes

Mulcher



- 60"/72" Cutting width
- Shreds up to 12" diameter trees
- Hydraulic deflector door
- 44/54 Hammers with carbide teeth
- Hydraulic flow of 30 to 60 G.P.M.

QA Grapple Buckets



"Closed Bottom"

- 2 Series of buckets in widths - 60", 66", 72", 76", 82", & 88"
- For machine weights of 8,000 and 11,000 lbs.
- Patented cushioned and sleeved cylinder
- Steel guards to protect cylinders
- Load check valve system

Quick Attach Grapple Brush Buckets



"Skeleton Bottom"

- Widths of 66", 72", 78", 84", & 90"
- For machine weights of 6,500# & 9,500#
- Patented cushioned & sleeved cylinder
- 100,000 PSI yield strength tine material
- Load check valve system

Quick Attach Low Profile Material Buckets



- Widths - 60", 66", 72", 78" & 84"
- Std. 30" length for more severe conditions when break out force is required
- Long length floor - 36" for better visibility, productivity, & cutting grade
- Strong box sections & full wear strips for better bottom protection
- Designed w/20° rollback angle

Tillers



- Breaks up sod and clumps of soil
- Mixes compost and other materials
- Prepares soil for seeding or reseeding; great for small soil stabilization and landscape jobs
- Available as fixed offset with dual direct drive or adjustable offset with chain drive

Built By:

BRADCO

ATTACHMENTS

Skid Steer Attachments - Skid steer & track loader are more productive

Brush Cutters




- Available in 60", 72" & 78" widths
- High speed three blades for brush up to 4" diameter
- Heavy ¼" thick steel deck with formed side plates
- Available in standard or high flow
- New heavy duty motor and drive train

Trencher



- Available in digging depths of 36", 42" & 48"
- Trench digging widths of 6", 8" & 10"
- Equipped w/2 position side shift
- High torque hydraulic motor for maximum digging power
- Replaceable headshaft driven auger for spoil removal

Cold Planer



- High flow and standard flow models are available
- Planing widths of 12", 16", 18", 24", 30" & 40"
- Fully adjustable with electro-hydraulic controls
- Joystick controls for depth, tilt, and side shift
- Drum diameters of 19" & 22" with carbide picks

Root Rake



- Dual use - rip out roots and grapple material
- Widths of 72", 78" & 84"
- 49" Grapple opening
- Dual hydraulic cylinders
- Built for extreme duty use

Brush Shredder



- 66"/72"/78" Cutting width
- Front of deck swings up for cutting down trees
- Knocks down and shreds trees up to 7" in diameter
- 4 Reversible ¾" thick blades
- Optional carbide teeth stump grinder

Backhoe



- Available in digging depths of 8 ½' thru 12'
- Bucket sizes of 12", 16", 18", 20", 24" & 36"
- Dual cylinder swing provides max. power where needed
- Cushioned swing brings backhoe to gentle stop
- Operates with hydraulic systems of 9 to 12 G.P.M.

Built By:

BRADCO

DISK MULCHER

Developed for extreme duty forestry applications



AGGRESSIVE FELLING AND PROCESSING

FELL UP TO
14 INCHES

PROCESS UP TO
8 INCHES

STUMP GRIND
TO GRADE

FEATURES:

- Heavy SSL quick attach mounting bracket
- Flow required - 30 to 45 G.P.M. at 3,300 PSI minimum (case drain required)
- Rated operating capacity - 2,600 lbs. minimum
- Ultra-efficient drive system with fast start
- MulchPower™ gauge for maximum energy
- Bearing housing never needs to be greased
- Debris shovel keeps teeth out of the dirt
- High quality QUADCO teeth are interchangeable, allows for simple service and rotation
- Solid steel teeth disk weighs over 900 pounds

The FD60 High-Flow Disk Mulcher maximizes up-time, minimizes service intervals, and can withstand aggressive use in a variety of conditions. The FD60 was designed as a solution to common issues of jamming and unpredictability that other forestry disk mulchers face. Forestry disk mulcher skid steer attachments are used for forestry applications because they combine felling trees, mulching them, and stump grinding into one fast process. This product is equipped with Paladin's MulchPower Gauge™, allowing operators to see when maximum rotational energy is stored in the disk so they can take down trees with full strength, as well as many other features to increase tool life and productivity.

NOTE: *Highly recommend impact resistant shield/front window to protect operator*

SPECIFICATIONS:

| CODE NUMBER | MODEL NUMBER | DESCRIPTION | CUTTING WIDTH | NO. OF TEETH | MACHINE WEIGHT |
|-----------------------------------|--------------|--------------|---------------|--------------|----------------|
| 125260 | FD60 | Disk Mulcher | 60" | 44 | 2410# |
| Comes standard with 3/4" couplers | | | | | |

Built By: **PALADIN**

SPRAYERS

Spot, ATV, Utility, Skid - From 15 to 40 gallon capacity

LG-40-SS

LG-13-P

LG-29-P

Spot Series 15, 25 & 40 Gallon

- Corrosion resistant polyethylene tank
- Full length drain sump
- 5" Fill lid with tether
- Larger hose wrap horns for hose storage
- Both gallon & liter fluid volume indicator on tank
- 12 Volt (demand) diaphragm pump
- Maximum horizontal throw - 30 ft.
- Maximum vertical throw - 18 ft.
- Ready for Roundup

| Model No. | Gallons | G.P.M. | PSI | Handgun | Hose | Wt. |
|-----------|---------|---------|--------|-------------|------|-----|
| LG-13-P | 15 Gal. | 2.1 GPM | 60 PSI | Lever | 15' | 30# |
| LG-29-P | 25 Gal. | 2.1 GPM | 60 PSI | Lever | 15' | 35# |
| LG-40-SS | 40 Gal. | 3.8 GPM | 45 PSI | Pistol Grip | 25' | 90# |

SPRAYER

40 Gallon, 3-point

Our 40 gallon **3-Point Sprayer** applies pesticides, herbicides, insecticides or fungicides. The sprayer attaches in minutes to a Category I, 3-point hitch. The sprayer is equipped with a 4 nozzle spray boom allowing 120" of spray coverage. The 3 section boom features break-away hinges for transport or striking objects such as trees, while spraying.

FEATURES:

- 12 Volt High-Flo pump, 2.1 GPM, 60 P.S.I.
- Break-away hinges on boom
- Fold behind 3 section boom
- Deluxe pistol grip handgun
- 15 Feet of hose

SPECIFICATIONS:

| Model No. | Hitch | Gallons | G.P.M. | Pump | Wt. |
|---------------|--------|---------|---------|------|-----|
| LG-40-3PT-12V | Cat. 1 | 40 | 2.1 GPM | 12V | 80# |

Trailer Mounted - With Honda engine

Our compact trailer sprayer is excellent for all types of spraying applications. These units feature a Honda 3 H.P. engine, 50 gallon polyethylene tank, and large flotation tires. The special twin piston diaphragm pump produces high pressure and gallons per minute, for spray boom and handgun operations.

The sprayer was designed so it can be towed by ATV's and other small vehicles.

FEATURES:

- 50 Gallon capacity polyethylene tank with hatch cover and strainer screen
- Honda 3 horsepower engine
- Two piston diaphragm pump produces 5.3 G.P.M. with pressure up to 275 P.S.I.
- High pressure jet agitation
- Flotation tires 18 x 8.50 - 8 ply
- Adjustable pressure control valve, line strainer and pressure gauge



SHOWN WITH OPTIONAL
BOOM, HANDGUN & HOSE

OPTIONS:

- ~ 5 & 10 Foot stainless steel boom - vertical or horizontal positions
- ~ Handgun and 25 feet of hose

| Model No. | Description | Gallons | Width | Length | Height | Wt |
|-----------|-----------------|---------|-------|--------|--------|------|
| ET50H | Trailer Sprayer | 50 | 36" | 75" | 35" | 175# |

FEATURES:

- Cat. 1, 3-point
- Capacity of 50, 100 & 150 Gallon
- Telescopic square tubing frame
- Each head is equipped with two anti-drip spray nozzles 110° flat fan tips
- Spring break away protection to prevent damage to crop
- Includes hoses and shut-off valves
- Sprayer features on next page

Our **Berm Sprayers** are available in capacities of 50, 100 and 150 gallon. The booms can be quickly adjusted from 6 to 10 foot rows. The wind proof spray heads have flexible polyethylene brushes.

The handy rear rails allow for easy mounting of vertical booms, horizontal booms and hose reels.

SPECIFICATIONS:

| Model No. | Tank Capacity | Pump GPM/PSI | Spray Heads | Spread | WT. |
|-----------|---------------|--------------|-------------|--------------|------|
| GC200-BB | 50 Gallon | 6 / 360 | 2 | 6 to 10 feet | 225# |
| GC400-BB | 100 Gallon | 11 / 360 | 2 | 6 to 10 feet | 240# |
| GC600-BB | 150 Gallon | 11 / 360 | 2 | 6 to 10 feet | 275# |

SPRAYERS

Cat. 1, 3-point hitch berm sprayer



150 GALLON SPRAYER
SHOWN

SPRAYERS

Two Sprayer Series - Economy and Deluxe

You will achieve total versatility and economical performance from our two series of **3-Point Hitch Sprayers**. The rear rails on both series allows for easy mounting of a number of bolt-on attachments such as a vertical boom, horizontal booms, hose reels, and handguns. The sprayers feature reinforced polyethylene tanks suspended from a tubular steel frame to isolate the tanks. Also featured are piston diaphragm pumps and a hand wash tank for convenience and safety.



*150 Gallon Shown
With Folding Boom*

"GC" SERIES

FEATURES:

- Category I, 3-point hitch
- Polyethylene tanks with liquid level gauge
- Tank capacities of 50, 100, & 150 gallon
- High pressure piston diaphragm pumps
- Pressure regulator valve and gauge
- Large suction filter
- High pressure jet agitation
- Separate clean water tank for safety
- Rear mounted rails for mounting booms

SPECIFICATIONS:

| Model No. | Tank Capacity | Pump GPM / PSI | Width | Height | Depth | Wt. |
|-----------|---------------|----------------|-------|--------|-------|------|
| GC200 | 50 Gal. | 6/360 | 39" | 46" | 23" | 175# |
| GC400 | 100 Gal. | 11 / 360 | 44" | 44" | 36" | 190# |
| GC600 | 150 Gal. | 11 / 360 | 44" | 56" | 36" | 225# |

"GDL" SERIES



FEATURES:

- Category I, 3-point hitch on 50 gallon, Category I & II hitch on 100, 150, and 200 gallon
- Tanks are made of reinforced polyethylene with smooth lines that are gentle to plants
- High pressure 3 piston diaphragm pump
- Pressure regulator valve with manual controls
- Clean water 12 gallon tank for flushing chemical residue, 6 gallon on 50 gallon sprayer
- High pressure jet agitation
- Clean water 4 gallon tank for hand washing
- Optional - manual or hydraulic booms

SPECIFICATIONS:

| Model No. | Tank Capacity | Pump GPM / PSI | Width | Height | Depth | Wt. |
|-----------|---------------|----------------|-------|--------|-------|------|
| GDL200 | 50 Gallon | 11 / 580 | 38" | 38" | 20" | 325# |
| GDL400 | 100 Gallon | 14 / 580 | 48" | 45" | 30" | 350# |
| GDL600 | 150 Gallon | 14 / 580 | 48" | 52" | 30" | 400# |
| GDL800 | 200 Gallon | 14 / 580 | 61" | 55" | 39" | 425# |

Boom / Handgun - High pressure pump for handgun & boom spraying

The **200 Gallon Sprayer** has a high volume and high pressure pump, best for multiple handgun use and with 20 and 28 foot booms. The simple design makes the sprayer easy to use. Recessed pump location allows close coupling to tractor and reduces angle of driveshaft. Tank is suspended from a heavy tubular frame to isolate it from vibration and stress.

- Mechanical agitation with stainless steel propeller and shaft
- Diaphragm pump produces 23 GPM @ 780 PSI
- Cat. I or II, 3-pt. hitch 540 R.P.M., PTO driven
- Controls are reachable from tractor seat allowing operator to switch liquid from off to right or left spraying
- Optional - hydraulic foldaway spray booms in 20' & 28' widths

| Model No. | Tank Capacity | Pump Type | Pump GPM | Pump Pressure | Wt. |
|-----------|---------------|-----------|----------|---------------|------|
| GN200D-23 | 200 Gal. | Diaphragm | 23 | 780 PSI | 450# |

- 8 H.P. Honda engine
- Reinforced polyethylene tank w/2 hatches
- 3 Piston diaphragm pump, produces 14 GPM at maximum pressure
- Pressure regulator w/manual controls reachable from seat
- Trailer tire size is 20 x 10.00- 6 ply

| Model No. | Type | Width | Length | Height | Wt. |
|-----------|---------|-------|--------|--------|------|
| GPE800 | Trailer | 54" | 102" | 48" | 490# |

Our sprayer offers the latest design in an **All Purpose Sprayer**. The low profile polyethylene tank has a full length stainless steel agitation system and a large hatch with shower head to easily put wettable powder into suspension. An additional water filling hatch is included to keep chemicals from being splashed while filling. The sprayer can be used as a horizontal boom, hose/reel/handgun sprayer. The applications for this sprayer are endless - municipalities, golf courses, nurseries, farms, ranches, etc.

- 20" Diameter fan with 9 adjustable blades
- Briggs & Stratton 9 HP Vanguard engine
- AR30 dual piston diaphragm pump produces 11 GPM, max. pressure 580 PSI
- Pressure regulator valve, gauge and hoses extend to towing vehicle
- High pressure jet agitation
- Separate clean water tank for hand washing

The Gearmore Compact, self contained Engine Driven Air Blast Sprayers was designed for very narrow rows and muddy conditions. This allows for operating the sprayer with an ATV or sub-compact tractors. The spray nozzles are easy to adjust and can be individually shut off. Controls allow for turning off one side. You can shut off the spray and disengage the fan for handgun spraying. This sprayer is popular in vineyards, berries, nurseries, hemp and other narrow row crops.

| Model No. | Type | Gallons | Fan | Width | Length | Height | WT. |
|-----------|---------|---------|---------------------|-------|-----------|-----------|------|
| ATVM400 | Trailer | 100 | 17,280 cu. ft./min. | 37" | 85" - 93" | 51" - 54" | 485# |

**MODEL GN200D-23
WITH 28' HYDRAULIC BOOM**



TRAILER SPRAYER



AIR BLAST SPRAYER









SPRAYERS, AIR BLAST

Value & Standard Series - For effective chemical spraying



Our **Value Series Air Blast Sprayers** have outstanding features such as: reinforced smooth lines polyethylene tanks; hot galvanized frame and fan housing to prevent rust; top of the line smooth running 3 piston diaphragm pumps; high speed fans with adjustable blades; gearbox with neutral for handgun and boom operations; built-in fan deflectors to direct the spray where required. The sprayers even have a separate safety fresh water tank for handwashing.

|  |  |  |  |  |  | LBS. |
|---|---|---|---|---|---|------|
| Model - Gal. | Inch | R.P.M. | C.F.M. | No. | HP | Wt. |
| APL-G200-50 | 24" | 2100 | 19,200 | 8 | 20 HP | 300# |
| APL-G400-100 | 24" | 2100 | 19,200 | 8 | 25 HP | 375# |

- Cat. I, 3-point hitch
- Tanks made of reinforced polyethylene with smooth lines - gentle to plants
- 3 Piston diaphragm pump 14 GPM, maximum pressure 580 PSI
- One speed gearbox with neutral for handgun and boom operations
- Stainless steel nozzle manifold
- High pressure jet agitation
- Adjustable top and bottom wings to direct air and spray only to the foliage
- Clean water 4 gallon tank for hand washing









Our **Standard Series Air Blast Sprayers** are ideal for small to medium sized vineyards, orchards, berries, etc. The sprayers feature reinforced polyethylene tanks with smooth lines that are gentle to the plants. The tanks are suspended from heavy duty tubular steel frames to isolate it from vibration and stress. The gearboxes have a neutral position which shuts off the fan during handgun or boom work. The sprayers are easy to operate and have all the features required for easy maintenance and long life.

**ADD "V" TO MODEL
FOR VOLUTE SPRAYER**

- Cat. I & II, 3-point hitch
- 3 Diaphragm piston pump, 14 GPM @ 580 P.S.I.
- One speed gearbox with neutral
- High pressure jet agitation
- Stainless steel manifolds with anti-drip nozzles
- Clean water 12 gallon tank for flushing chemical residue
- Clean water 4 gallon tank for hand washing



|  |  |  |  |  |  | LBS. |
|---|---|---|---|---|---|------|
| Model - Gal. | Inch | R.P.M. | C.F.M. | No. | HP | Wt. |
| APL400 - 100 Gal. | 28" | 2100 | 25,000 | 10 | 30 - 40 | 500# |
| APL600 - 150 Gal. | 28" | 2100 | 25,000 | 10 | 40 - 50 | 550# |

Venturi Air Sprayers - For berries/open fields and hoop houses

These sprayers were designed with unique distribution heads for berries. The narrow width allows for operating in the tight row spacings. The hoop house model has a cannon which sprays the "pole row". The open field distribution head has 6 double nozzles for spraying two half rows. Both distribution heads produce fog sized droplets that achieve total plant coverage.

FEATURES:

- Cat. 1, 3-pt. hitch, PTO 540 R.P.M.
- High performance, precision balanced all steel centrifugal fan
- Special molded polyethylene fan housing
- Translucent heavy walled polyethylene tank with lid, sump and strainer basket
- Built-in overrunning clutch to protect the tractor and sprayer drive train
- Compact, rounded tank design permits traveling through vegetation without damaging it
- Simple, efficient "Dial-A-Rate", 15 position metering disc
- Agitation by liquid sparging tube & air from fan
- Low pressure spraying system - 15 to 40 PSI spraying pressure means less maintenance for pumps and nozzles
- Capable of application rates of 20 to 200 gallons per acre, depending on row width
- Reachable controls from tractor seat, allows operator to switch liquid from off to right, left, or both sides spraying
- Built-in 6 gallon fresh water safety tank

DISTRIBUTION HEADS:

Open Field Berries - Order 12 nozzle distribution head no T6M2D

Hoop House Berries - Order 12 nozzle distribution head no. T.6M+1C, which includes upper cannon assembly, shutter valve extension and 12 nozzle plugs

SPECIFICATIONS (Sprayer Only):

| Model No: | Gallons | Volume of Air | Width | H.P. Req'd | Weight |
|-------------|------------|---------------|-------|------------|--------|
| P42N1-300-G | 75 Gallons | 2350 | 38" | 18 H.P. | 400# |
| P45N1-300-G | 75 Gallons | 3180 | 38" | 32 H.P. | 410# |



SPRAYERS

Venturi Air Sprayers - Fog sized droplets ensure total plant coverage

These *Venturi Air Sprayers* feature the 8 nozzle distribution head for vineyard rows up to 10 foot width.



**P45 SHOWN WITH
8 NOZZLE HEAD**



**FRONT
VIEW**



These unique *Venturi Air Sprayers* feature the latest technology in concentrate spraying. Thus, growers achieve the following benefits: spray atomization of droplets are smaller and more uniform, less fill-ups, even distribution of concentrated spray, complete foliage coverage, better product utilization, less chemical waste and soil/water contamination. All Venturi Air Sprayers shown on the following pages have these same advantages.

FEATURES:

- Cat. I, 3-point hitch, P.T.O. 540 RPM
- High performance, precision balanced all steel centrifugal fan
- Translucent heavy walled polyethylene tank with lid, sump and strainer basket
- Compact, rounded tank design permits traveling through vegetation without damaging it
- Simple, efficient "Dial-A-Rate", 15 position metering disc
- Agitation by liquid sparging tube and air from the fan
- Low pressure spraying system - 15 to 40 PSI spraying pressure means less maintenance for pumps and nozzles
- Power band fan speed-up is automatically adjusted by spring loaded idler
- Broad range of Venturi distribution heads that produce 50 micron droplets and are specially designed to match a variety of foliage profiles
- Capable of application rates of 20 to 200 gallons per acre, depending on row width
- Built-in 6 gallon fresh water safety tank

SPECIFICATIONS:

| Model No. | Gallons | Volume of Air | Width | H.P. Required | Wt. |
|-------------|-------------|---------------|-------|---------------|------|
| P42N1-300-G | 75 Gallons | 2350 C.F.M. | 38" | 18 H.P. | 430# |
| P42N1-400-G | 100 Gallons | 2350 C.F.M. | 44" | 18 H.P. | 450# |
| P45N1-300-G | 75 Gallons | 3180 C.F.M. | 38" | 32 H.P. | 435# |
| P45N1-400-G | 100 Gallons | 3180 C.F.M. | 44" | 32 H.P. | 455# |

Cuts Spraying Time in Half - Sprays two complete rows in one pass



The ***Venturi 2 Row Sprayer*** covers two complete rows at one time so your spraying time is cut in half; reducing your labor, fuel, wear and tear on your tractor/sprayer, and since you are traveling every other row, you will have less soil compaction. Plant coverage is greatly increased because the spray enters the foliage from opposite directions at the same time. Thus, chemical drift is greatly reduced as the spray is held in the foliage longer. These sprayers are available with many different types of distribution heads, however the most productive is the unit shown above. The over the row nozzles are adjustable for 6 to 10 foot rows. The extensions have hydraulic cylinders for folding away when required

FEATURES:

- Cat. I & II, 3-point hitch, P.T.O. 540 RPM
- High performance, precision balanced all steel centrifugal fan
- Special molded polyethylene fan housing
- Translucent heavy walled polyethylene tank with lid, sump and strainer basket
- Compact, rounded tank design permits traveling through vegetation without damaging it
- Simple, efficient "Dial-A-Rate", 15 position metering disc
- Agitation by liquid sparging tube and air from the fan
- Low pressure spraying system - 15 to 40 PSI spraying pressure means less maintenance for pumps and nozzles
- Reachable controls from tractor seat, allows operator to switch liquid from off to right, left or both sides spraying
- Built-in 6 gallon fresh water safety tank

SPECIFICATIONS:

| Model No. | Gallons | Volume of Air | Width | H.P. Required | Wt. |
|-------------|-------------|---------------|-------|---------------|------|
| P50N1-400-G | 100 Gallons | 4444 | 44" | 45 H.P. | 500# |
| P50S1-400-G | 100 Gallons | 4875 | 44" | 52 H.P. | 500# |
| P50N1-600-G | 150 Gallons | 4444 | 57" | 45 H.P. | 540# |
| P50S1-600-G | 150 Gallons | 4875 | 57" | 52 H.P. | 540# |

SPRAYERS

Venturi Air Sprayers - One sprayer, three different applications



The development of this sprayer was for horizontal spraying up to 90 feet. The system features 4 upper cannons, one central cannon and 4 lower nozzles. This cannon sprayer is popular in areas of limited tractor roads and is used in nurseries and crops like melons.



This sprayer has special tall tree cannons that will give complete coverage on trees up to 50 feet in height. The unit was designed for spraying walnuts, avocados, and other tall tree orchards. The sprayer is also excellent for applying foliar feed.

This model features fishtail type distribution heads for orchards with trees up to 35 feet in height. The fishtails are fitted with special manifolds with a total of 64 orifice outlets. This feature produces a fine mist spray to obtain total plant coverage. Also, growers have found that the sprayer is the most economical way to apply foliar feed.



FEATURES:


- Cat. II, 3-point hitch, P.T.O. 540 RPM
- Translucent heavy walled polyethylene tank with lid, sump and strainer basket
- Built-in overrunning clutch to protect the tractor and sprayer drive train
- Simple, efficient "Dial-A-Rate", 15 position metering disc
- Agitation by liquid sparging tube and air from the fan
- Low pressure spraying system - 15 to 40 PSI
- Electro valve controls to switch liquid from off to right, left or both sides spraying
- Built-in 6 gallon fresh water safety tank

SPECIFICATIONS:

| Model No. | Gallons | Volume of Air | Width | H.P. Required | Wt. |
|-------------|-------------|---------------|-------|---------------|------|
| P55E1-600-G | 150 Gallons | 9123 C.F.M. | 57" | 70 H.P. | 550# |

Venturi Air Sprayers - For orchards that require top to bottom coverage

These unique *Venturi Air Sprayers* feature our most powerful high speed turbine fans and are the latest technology in fine mist spraying. Thus, growers achieve the following benefits: Spray atomization of droplets are smaller and more uniform, less fill-ups, even distribution of concentrated spray, complete foliage coverage, better product utilization, less chemical waste and soil/water contamination. This 6 vent distribution head is also available on our 300 and 500 gallon trailer models.



This sprayer produces a perfect curtain of fine fog sized droplets through special 6 vent distribution heads with a total of 96 orifice liquid outlets.



FEATURES:

- Cat. II, 3-point hitch, P.T.O. 540 RPM
- High performance, precision balanced all steel centrifugal fan
- Translucent heavy walled polyethylene tank with lid, sump and strainer basket
- Compact, rounded tank design permits traveling through vegetation without damaging it
- Simple, efficient "Dial-A-Rate" 15 position metering discs
- Agitation by liquid sparging tube and air from fan
- Low pressure spraying system - 15 to 40 PSI spraying pressure means less maintenance for pumps and nozzles
- Reachable controls from tractor seat, allows operator to switch liquid from off to right, left or both sides spraying
- Built-in 6 gallon fresh water safety tank

SPECIFICATIONS:

| Model No. | Gallons | Cat. | Volume of Air | Width | H.P. Req'd | Wt. |
|---------------|---------|------|---------------|-------|------------|------|
| P55E1-600E-6V | 150 | II | 9,125 C.F.M. | 57" | 70 H.P. | 550# |

SPRAYERS

Venturi Air 3-Pt/Trailer - Designed so driveshaft is always straight in line



300 GAL. WITH OPT. DISTRIBUTION HEAD

These Venturi Air Sprayers feature a special short turning radius design. The fan and distribution head is 3-point hitch mounted. The trailer assembly is attached to the fan assembly with a heavy duty double knuckle joint. The sprayer can "turn on a dime" with no stress or damage as the drive system is always straight. The sprayer shown is equipped with our unique 2 row distribution heads for spraying two complete rows with one pass. This cuts your spraying time in half, reducing labor, fuel, and wear and tear on your tractor/sprayer. These unique 3-point/trailer sprayers are the perfect units for narrow and short head land rows.




Developed especially for vineyards with short head lands.

- Cat. I & II, 3-point hitch, P.T.O. 540 RPM
- Turns as sharp as your tractor
- Parking stands for 3-point and trailer assemblies
- High performance, precision balanced all steel, front mounted centrifugal fan
- Special molded polyethylene fan housing
- Translucent heavy walled polyethylene tank with hinged lid, sump, strainer basket and shower head

- Dual tank lids for safety, one for water and one for adding chemicals
- Simple efficient "Dial-A-Rate", 15 position metering disc
- Centrifugal pump - 37 G.P.M.
- The 200 gallon has one pump, 300 gallon has 2 pumps
- Dual agitation systems, liquid and air
- Low pressure spraying system - 15 to 40 PSI spraying pressure means less maintenance for pumps and nozzles
- Power band fan speed-up is automatically adjusted by spring loaded idler
- Electro-valve controls allows operator to switch liquid to right, left or both sides spraying
- 8 Gallon fresh water safety tank

| Model No. | Gallons | Volume of Air | Width | Length | Tire Size | H.P. Required | Wt. |
|------------|-------------|---------------|-------|--------|---------------|---------------|------|
| L50N1-800 | 200 Gallons | 4444 C.F.M. | 43" | 9' | 9.5Lx15-8 Ply | 48 H.P. | 855# |
| L50S2-1200 | 300 Gallons | 5000 C.F.M. | 54" | 9' | 11Lx15-8 Ply | 52 H.P. | 960# |

200 Gallon Trailer - For low horsepower tractors spraying narrow rows



FEATURES:

- Trailer mounted, P.T.O. 540 R.P.M.
- Translucent heavy walled polyethylene tank with hinged lid, sump, strainer basket and shower head
- Unique polyethylene belly mounted air tubing to the distributor heads
- Dual tank lids for safety, one for water and one for adding chemicals
- Compact, rounded tank design permits traveling through vegetation without damaging it
- Adjustable tread width, facilitates matching sprayer tread with tractor tread
- Tongue with clevis hitch has length adjustment
- Simple, efficient "Dial-A-Rate", 15 position metering disc
- Dual agitation systems, liquid and air
- Low pressure spraying system - 15 to 40 PSI spraying pressure means less maintenance for pumps and nozzles
- Built-in overrunning clutch to protect the tractor and sprayer drive train
- Power band fan speed-up is automatically adjusted by spring loaded idler
- Electro-valve controls to allow operator to switch liquid from off to right, left, or both sides spraying
- Built-in 8 gallon fresh water safety tank



Our **200 Gallon Trailer Mounted Sprayer** was developed for low horsepower tractors doing narrow row spraying. Tractors with P.T.O. horsepower of as low as 36 will handle this sprayer. The 48 inch overall sprayer width allows for operating in the narrowest of rows. Growers achieve the following additional benefits - spray atomization of droplets are smaller and more uniform, less fill-ups, even distribution of concentrated spray, complete foliage coverage, better product utilization, less chemical waste and soil/water contamination.

SPECIFICATIONS:

| Model No. | Gallons | Volume of Air | Width | Length | Tire Size | H.P. Required | Wt. |
|-----------|------------|---------------|-------|----------|---------------|---------------|------|
| T45N1-800 | 200 Gallon | 3180 C.F.M. | 48" | 10' - 5" | 9.5Lx15-8 Ply | 36 H.P. | 910# |

SPRAYERS

Venturi Air, 200 & 300 Gallon - For high production, accurate spraying



The **Gearmore T50S 2 Row Venturi Air Sprayer** covers two complete rows at one time so your spraying time is cut in half; reducing your labor, fuel, wear and tear on your tractor/sprayer, and since you are traveling every other row you will have less soil compaction. Plant coverage is greatly increased because the spray enters the foliage from opposite directions at the same time. Thus, chemical drift is greatly reduced as the spray is held in the foliage longer. The Venturi low volume spraying system also achieves these additional benefits: spray atomization of droplets are smaller and more uniform, even distribution of concentrated spray, better product utilization, less chemical waste and soil/water contamination and best of all less fill-ups.

2 ROW BOOM FEATURES:

- For 6 to 10 foot rows
- Total of 4 distribution heads with 4 Venturi nozzles on each head with individual shut off valves, rotating calibration discs and anti-drip valves
- Rear mounted height adjustable frame
- Two hydraulic cylinders with hoses for opening and closing horizontal booms

FEATURES:

- Molded polyethylene 200 or 300 gallon tank
- Sprayer operates with a low pressure centrifugal pump which produces 37 GPM at the normal operating pressure of 15 to 40 PSI
- Dual centrifugal pumps - 37 GPM for spraying and 37 GPM for agitation on 300 gallon only
- Air speed is 415 MPH at nozzles
- Wheels are adjustable up or down, front or rear, in or out to obtain the best balance
- Electro-valve system controls spray off or on, both sides spray, right or left only
- Separate water and chemical filling hatches keep chemical from being splashed out while filling
- No gearbox for fan speed-up, only a simple power band pulley system with overrunning clutch
- High speed turbine fan turns at 4320 RPM with air delivery of 4885 cu. ft. per minute
- Separate safety clean water 8 gallon tank for handwashing

SPECIFICATIONS:

| Model #: | Gallons | Volume of Air | Width | Length | Tire Size | H.P. Req'd | Wt. |
|------------|---------|---------------|------------|--------|---------------|------------|-------|
| T50S2-800 | 200 | 4885 C.F.M. | 42" to 50" | 10'-5" | 9.5Lx15-8 Ply | 48 | 910# |
| T50S2-1200 | 300 | 4885 C.F.M. | 54" to 74" | 11'-7" | 11Lx15-8 Ply | 52 | 1020# |

Dimensions are less 2 row distribution head

SPRAYERS

Venturi Air - Total plant coverage at lowest cost per acre

These unique *Venturi Air Sprayers* feature our most powerful high speed turbine fans and are the latest technology in spraying. Thus, growers achieve the following benefits: spray atomization of droplets are smaller and more uniform, less fill-ups, even distribution of concentrated spray, complete foliage coverage, better product utilization, less chemical waste and soil/water contamination.



The cannon Venturi Air Sprayer operating in 45 foot high walnut orchard at 50 gallons per acre.



- High performance, precision balanced all steel, front mounted, centrifugal fan
- Translucent heavy walled polyethylene tank with hinged lid, sump, strainer basket and shower head
- Dual centrifugal pumps - 37 GPM for spraying and 37 GPM for agitation
- Dual agitation systems, liquid and air
- Low pressure spraying system - 15 to 40 PSI spraying pressure means less maintenance for pumps and nozzles
- The Venturi Air distribution heads produce 50 micron droplets and are specially designed to match a variety of foliage profiles
- Electro-valve controls to allow operator to switch liquid from off to right, left, or both sides spraying
- Built-in 8 gallon fresh water safety tank

10 Different distribution heads to choose from for multiple crops

SPECIFICATIONS:

| Model No. | Gallons | Volume of Air | Min. Width | Length | Tire Size | H.P. Req'd | WT. |
|------------|----------|---------------|------------|--------|-----------------|------------|-------|
| T55E2-1200 | 300 Gal. | 9123 C.F.M. | 55" | 12' | 11Lx15-8 Ply | 64 H.P. | 1020# |
| T55E2-1500 | 400 Gal. | 9123 C.F.M. | 66" | 14' | 11Lx15-8 Ply | 70 H.P. | 1240# |
| T55E2-2000 | 500 Gal. | 9123 C.F.M. | 71" | 14' | 12.5Lx15-10 Ply | 74 H.P. | 1320# |

**"10 YEAR WARRANTY ON
POLYETHYLENE TRAILER TANKS"**



Centrifugal pump powers rotating liquid agitation system to insure product mix



**OUR 12 NOZZLE CANNON
HEAD WILL SPRAY UP TO
50 FOOT TREES**

SPRAYERS

With Wrap-A-Round Booms - For high production, accurate spraying

**500 GALLON SPRAYER
SHOWN WITH "D" BOOM**



*We custom build booms
and electro / hydraulic
controls to grower's
requirements*

Now available is a complete series of high strength **Wrap-A-Round Spray Booms**.

The booms feature extra strong framing with heavier support tubings to the sprayer frame.

The five hydraulic cylinders give total control on height adjustment, swing up for in row obstructions, and fold away for transport. The width adjustment is manual, optional electro cylinders operated from the tractor seat are available. These booms are available to spray two complete rows or two complete rows and two half rows. Boom controls require 5 rear remotes or Gearmore's optional electro over hydraulic kits. The booms are designed to fit the popular 300 and 500 gallon Venturi Air Sprayer.

- Sprayer features same as previous page
- Booms swing hydraulically from operational to closed position
- Booms fold forward for transport and lock
- Height adjustment is hydraulic
- Boom bottoms can be fitted with single or double 4 + 4 nozzles or fishtails
- Boom tops can be fitted with 4 + 4 nozzles, cannons, fishtails, or neither head



| Boom Model No. | Sprayer Model No. | Gals. | No. of Rows | Nozzle Assy's | Row Space | Crop Max. Ht. | Boom Clearance | Nozzle Positions | Bottom Nozzles | Top Nozzles |
|-----------------------------|-------------------|-------|------------------|---------------|-----------|---------------|----------------|----------------------|---------------------------------------|-------------|
| TS56MB55M12 "A" Boom | T55E2-1200 | 300 | 2-Full 2-Half | 6 | 7.5'-10' | 7 ft. | 8 ½ ft. | Bottom Only | 4 Outlet Head | None |
| TS56MC55D12 "A" Boom | T55E2-2000 | 500 | 2-Full 2-Half | 6 | 9.5'-13' | 8 ft. | 9 ½ ft. | Bottom Only | 4 Outlet Head | None |
| TS54M4CC55D12 "B" Boom | T55E2-2000 | 500 | 2-Full | 8 | 9.5'-13' | 8 ft. | 9 ½ ft. | Top & Bottom | 4 Outlet Head | Cannons |
| TS512MC55D12 "D" Boom | T55E2-2000 | 500 | 2-Full 2-Half | 12 | 9.5'-13' | 8 ft. | 9 ½ ft. | Top & Bottom | 4 Outlet Head Bottom & Top | |
| TS52V4V6V55D12 Hedge Row | T55E2-2000 | 500 | 2-Full | 12 | 9.5'-13' | 8 ft. | 9 ½ ft. | Top, Center & Bottom | Fishtail Head Bottom, Center & Top | |

Venturi Air Boom - Achieve total plant coverage on field crops



**27' Boom
SPRAYER SHOWN**

FEATURES:

- Nozzles break down spray to fog size (50 microns) droplets which penetrate in and around all areas of each plant
- Air movement allows chemical to completely cover vegetation, especially the underside of leaves
- Volume as low as 5 gallons per acre results in fewer refilling stops and more acres covered per day
- Spray drift is reduced by 50% to 75%.
- Boom has breakaway and hydraulic fold away features to prevent damage and for transport
- Boom raises and lowers hydraulically for different crop heights, independent of the sprayer
- Boom nozzles are completely adjustable in width and angle for maximum coverage
- Chemicals only come in contact with plastic, rubber, and stainless steel parts



40' Boom Sprayer Shown

Special booms built upon request

- Tank:** Translucent polyethylene 150 gal. with hatch & strainer basket
- Agitation:** Adjustable liquid bypass, and air from fan when required
- Drive:** 540 RPM P.T.O. driven with belt drive to fan and pump with overrunning clutch
- Nozzles:** "No drip" system on each nozzle and individual liquid shut-off by hand, replaceable stainless steel discs and screens
- Controls:** Electro-valve controls allows operator to switch liquid from off to right, left or center
- Filtration System:** 3 Stages - at filler, at pump, and at nozzles
- Fan:** Centrifugal type w/PVC housing
- Pump:** Centrifugal with maximum 37 GPM
- Sight Gauges:** In tank and tubing
- Pressure Gauge:** 0 to 80 P.S.I. in liquid case to reduce vibration and extend life

| Models: | Boom Width | Rows | No. of Nozzles | Boom Design | Tank Cap. | Fan Dia. | Fan (RPM) | Volume of Air | Air Speed at Foliage | Controls | Min. Tr. HP | Wt. |
|---------------|------------|------|----------------|-------------------|-----------|----------|-----------|---------------|----------------------|---------------|-------------|-------|
| P45N-400-23 | 23' | 5 | 2+2=20 | Galvanized Tubing | 100 Gal. | 17.75" | 4000 | 3180 | 10-50 MPH | Liquid | 32 H.P. | 700# |
| P50S-600-27 | 27' | 8 | 2+2=32 | Galvanized Tubing | 150 Gal. | 19.75" | 4320 | 4875 | 10-50 MPH | Electro Valve | 52 H.P. | 1230# |
| P55E1-600-40S | 40' | 7 | 2+3+2=49 | Galvanized Tubing | 150 Gal. | 21.75" | 3900 | 9123 | 10-50 MPH | Electro Valve | 64 H.P. | 1800# |
| P55E1-600-40 | 40' | 12 | 2+2=48 | Galvanized Tubing | 150 Gal. | 21.75" | 3900 | 9123 | 10-50 MPH | Electro Valve | 64 H.P. | 1800# |

SPREADERS

3-Pt./Trailer Spinner Spreaders - 3-Pt, PTO & ground driven w/PVC hoppers

3-PT. SEEDER/SPREADERS



| Model No. | Capacity | | Overall Height | Wt. |
|-----------|-----------|--------------|----------------|------|
| | Lbs. | Cu. Ft. | | |
| PL180 | 480 lbs. | 5.8 cu. ft. | 36" | 120# |
| PL500 | 1000 lbs. | 12.3 cu. ft. | 45" | 140# |

Our **3-Point Hitch Spreaders** feature a strong, corrosion proof PVC hopper. These spinner units have double levers and stainless steel slides which allow for spreading at 180° or 90° to the right or left. They are ideal for even spreading fertilizer, seed, salt, and other flowable materials.

- Cat. I, 3-point hitch, 540 PTO
- Corrosion proof PVC hopper
- Stainless steel spreading disc with 4 stainless steel fins
- Steel oil tight gearbox with grease zerk
- Extended handle for engaging & disengaging
- Choice of 3 spread patterns: full rear, left or right side
- Effective spreading width from 20' to 46'
- Built in rear hitch
- Adjustable uniform rates from 20 to 900 lbs./acre

OPTIONS:

- ~ Larger extended hopper agitator
- ~ One and two row band spreader attachments

TRAILER MOUNTED SEEDER/SPREADERS



Our **Seeder/Spreader** is a self contained, towable implement that can be operated by almost any vehicle. This unit has a ground driven, cast iron, oil bath gearbox that can be disengaged when transporting. It is ideal for spreading seed, fertilizer, sand, and salt. The large 16" diameter x 6.5" wide tires make this a "Turf Friendly" implement. This spreader is a handy tool for farmers, landscapers, and homeowners.

| Model No. | Capacity | | Height | Width | Depth | Wt. |
|-----------|----------|-------------|--------|-------|-------|------|
| | Lbs. | Cu. Ft. | | | | |
| PTP180-P | 480 lbs. | 5.8 cu. ft. | 51" | 41" | 59" | 175# |
| PTP300-P | 765 lbs. | 9.2 cu. ft. | 51" | 41" | 59" | 185# |

- Ground wheel driven
- Corrosion proof PVC hopper
- Cast iron, oil bath gearbox
- Gearbox disengages for transport
- Stainless steel spreading disc with 4 stainless steel fins
- Extended handle for engaging and disengaging material flow
- 16 x 6.5-8 Ply turf tires
- 1 7/8" Ball hitch
- Spreading widths from 20' to 46'
- 3 Spread patterns:
 - ~ full rear
 - ~ left side
 - ~ right side

SPREADERS

Spinner Spreaders - High capacity, 3-pt. PTO driven

Our high capacity **3-Point Spreader** features a stainless steel, single spinner disc with 6 stainless steel vanes. Spreaders have a heavy duty stamped and ribbed frame. All metal hoppers and frames have special phosphated undercoat, then epoxy powder painted and baked at 300 degrees to insure long life. The spreader can be set at 180°, 90° right, or 90° left spreading pattern.

SINGLE SPINNER



FEATURES:

- Cat. II, 3-point hitch
- Low loading height
- Sturdy stamped and ribbed steel frame
- Manual levers control on and off
- 6 Fins spreading disc for even spreading width
- Spreading width from 32' to 59'

SPECIFICATIONS:

| Model No. | Capacity | | Height | Width | Depth | Wt. |
|-----------|-----------|------------|--------|-------|-------|------|
| | Lbs. | Cu. Ft. | | | | |
| RT-800 | 1700 lbs. | 28 cu. ft. | 40" | 59" | 53" | 345# |

Our two **3-Point Spreaders** feature dual stainless steel spinner discs, which are extremely accurate with only 6.7% variance across the spread pattern. The spreaders are supplied with hydraulic controls. The new 41" width model is for narrow row vineyards and other narrow row crops.

DOUBLE SPINNER



FEATURES:

- Cat. I & II, 3-point hitch
- Hydraulic cylinder controls, off and on
- Stainless steel construction
- Two stainless steel disc with 3 vanes each
- Spreading width from 30 to 50 feet
- Easy on and off band spread attachment for exact material placement
- Two row band spreader attachment - 66" wide

Shown With Optional 2 Row Band Spreader Attachment

SPECIFICATIONS:

| Model No. | Capacity | | Height | Width | Depth | Wt. |
|-----------|-----------|------------|--------|-------|-------|------|
| | Lbs. | Cu. Ft. | | | | |
| RE-1000 | 2300 lbs. | 35 cu. ft. | 45" | 59" | 51" | 450# |

SPREADERS

Compost and Pull Type - Composting crops effectively increases yields

COMPOST SPREADER



This unique **Compost Spreader** is able to spread a wide range of materials such as: compost, peat, concentrated manure, lime, gypsum, dried grape pomace and other types of fertilizer. The spreader was designed for two different spreading operations. You can broadcast spread and add the side conveyor for band spreading. Features are built into the spreader to achieve the application of this large group of products. Patented two gearbox system, one to power the spinner and a second gearbox geared to a low R.P.M. for the agitator.

FEATURES:

- Cat. I & II, 3-point hitch, 540 RPM P.T.O.
- Spinner turns at 718 RPM and the agitator turns at 77 RPM
- Hydraulic cylinder for on and off
- For tractors 50 to 150 HP, capacity - 35.3 cu. ft.
- Spread width 20 to 45 ft., up to 12 ft. with band spread attachment
- Agitation blades for light compost

SPECIFICATIONS:

| Model No. | Capacity | Width | Depth | Height | Wt. |
|-----------|-----------|-------|-------|--------|------|
| SCU-N1000 | 2000 lbs. | 48" | 64" | 55" | 780# |

OPTIONS:

- ~ Stainless steel side band attachment
- ~ Stainless steel rear drop discharge

PULL TYPE SEEDER/SPREADER



Our **Seeder/Spreader** is a self contained, towable implement that can be operated by almost any vehicle. This unit has a ground driven, cast iron, gearbox that can be disengaged when transporting. It is ideal for spreading seed, fertilizer, sand, and salt. The large 20" diameter x 10" wide tires make this a "Turf Friendly" implement. The spreader features a cable control that allows the operator to adjust spread rate and turn the spreader on and off from the vehicle seat. This is a popular, low cost spreader for golf courses, parks, sport fields, and turf farms.

FEATURES:

- Remote cable control from vehicle
- Agitators to prevent bridging
- 20 x 10:00 - 8 tires
- Full width or spreading to one side
- Height adjustment on 2" ball hitch

OPTIONS:

- ~ Clevis type hitch
- ~ Secondary chain agitator
- ~ Canvas hopper cover
- ~ Cable control mounting bracket
- ~ Remote hopper vibrator

SPECIFICATIONS:

| Model No. | Capacity | | Spreading Width | Machine | | | Wt. |
|-----------|-----------|--------------|-----------------|---------|-------|-------|------|
| | Lbs. | Cu. Ft. | | Height | Width | Depth | |
| PTB560 | 1070 lbs. | 14.2 cu. ft. | Max. 52' | 51" | 65" | 96" | 310# |

SPREADERS



Pendulum Spreaders - achieves accurate placement of fertilizers and seeds

Our line of **Pendulum Spreaders** feature an advanced mechanism with regulating key which allows for quickly setting the spread pattern. Other features are exact rate/spread control, quick change spouts, low filling heights, and easy maintenance. The model PDC400 has a molded plastic hopper, all other models have formed fiberglass hoppers. The spreading width with the standard spout is 20 to 46 feet. A large variety of spouts are available for standard broadcast, narrow row and wide row vineyards and orchards. Hopper capacities from 925 to 2000 pounds.

MODEL PDC400



MODEL PDV500



The above spouts fit all models

SPECIFICATIONS:

| Model No. | Hitch Category | Capacity | | Overall Width | Overall Height | Wt. |
|-----------|----------------|-----------|--------------|---------------|----------------|------|
| | | Lbs. | Cu. Ft. | | | |
| PDC400 | Cat. I | 925 lbs. | 13.6 cu. ft. | 46" | 47" | 225# |
| PDV500 | Cat. I & II | 1155 lbs. | 17 cu. ft. | 54" | 36" | 290# |
| PDV600 | Cat. I & II | 1450 lbs. | 20.5 cu. ft. | 54" | 40" | 315# |
| PDHV800 | Cat. II | 2000 lbs. | 32 cu. ft. | 74" | 40" | 375# |

SPREADERS, MANURE

Many Unique Features - Best warranties in the industry



Key Conestoga features unavailable from the competition are:

- "Cor-ten" copper bearing steel is used to provide atmospheric corrosion resistance four times that of plain carbon steel, for longer service life
- Conestoga boxes are of all-welded construction, chemically washed, painted with epoxy primer, and finished with a highly corrosion resistant, two-part urethane paint
- All Conestoga spreaders come standard with our own design, STAINLESS STEEL, T-rod apron chain, which provides superior durability and service life
- Beater paddles are a rooster comb design and are bolted on so they can be replaced when wear does occur
- Conestoga spreaders are designed with 12 paddles, more than the competition

Outstanding features allows Conestoga to give the best warranties in the industry:

- "10 Years" on the spreader box
- "Lifetime" on the poly floor
- "3 years" for defect in material and workmanship
- C25 & C50 ground drive come with upper beaters

| Model No. | C-25 | C-50 | C-50 PTO | C-80 PTO | C-125 PTO | C-175 PTO |
|---------------------|----------------------|------------|------------|------------|------------|-------------|
| Capacity: | 20 cu. ft. | 38 cu. ft. | 38 cu. ft. | 58 cu. ft. | 85 cu. ft. | 115 cu. ft. |
| No. of Horses: | 1 - 5 | 4 - 6 | 4 - 6 | 5 - 10 | 10 - 25 | 20 + |
| Minimum Horsepower: | 2 Wheel Ground Drive | | 15 H.P. | 18 H.P. | 35 H.P. | 40 H.P. |
| Overall Length: | 118" | 142" | 142" | 168" | 198" | 212" |
| Overall Width: | 49.75" | 60" | 57" | 65" | 76" | 80" |
| Loading Height: | 28" | 33" | 33" | 36" | 43" | 45" |
| Weight: | 600 lbs. | 825 lbs. | 825 lbs. | 950 lbs. | 1,700 lbs. | 1,900 lbs. |

Built By:

CONESTOGA

Contact Us For Complete Catalog - Many more models available

Rear Mount



Rear Mount Sweepers mount to rear 3-point of compact and industrial tractors. Mechanical or hydraulic brush drive. Manual and hydraulic angle change 30° left/right available. Sweeps forward and windrows debris outside of rear tires on paved and turf areas. Pulling action cleans thatch without damaging grass. Brush rotation can be reversed for operation backing up. Brush widths from 4 ft. to 8 ft.

Pick-Up Sweeper



The Standard Pick-up Brooms clean up in construction, municipal and industrial applications. The 26" diameter brushes come in poly, wire or half of each. Options available are: sprinkler system and gutter brush. The Cold Planer Special has special compacted dense wafer brushes the width of the cold planer cut. These wafers do not flex as much as the balance of the brush, thus it cleans out the milled grooves.

Compact Front Mount



Compact Front Mount Sweepers mount to commercial turf mowers, compact utility tractors and industrial loaders. Available in a hydraulic or mechanical brush drive, with manual or hydraulic angle change 30° left/right. Keep your tractor and sweeper busy all year sweeping snow, dirt, thatch, and leaves. Brush widths from 4 ft. to 8 ft.

Angle Sweeper



Angle Sweepers mount to skid steer loaders and is available for mounting on utility tractor loaders. Hydraulic brush drive, with manual or hydraulic angle change 30° left/right available. Single or dual motor configurations are available. Brush is equipped with a quick change core for easy brush change. Heavy duty design with quick attach mounting. Brush widths from 5 ft. to 8 ft.

Built By: **SWEEPSTER**

ROTARY TILLERS

"B" Series - For compact tractors 15 - 35 horsepower



These compact **"B" Series** tillers are quality constructed units that are built to last. The adjustable skid shoes control the cutting depth while the rear tailboard controls the soil mix. The tiller is equipped with a slip clutch to protect the tiller and tractor. Ideal for preparing seedbeds, renovating pastures, and other tillage uses. The tiller provides uniform mix throughout the cultivated depth.

- Cat. I, 3-point hitch
- 7" Approximate tilling depth
- One speed gearbox, 540 RPM
- 80# Heavy duty roller chain
- Slip clutch driveshaft protects tractor & tiller drive system
- Curved saber style, heat treated, long wearing tines
- 6 Tines mounted on each rotor plate for maximum tilling action
- Tines staggered in scroll design for easy soil penetration
- Side mounted skids for depth control

| Model No. | Tilling Width | Overall Width | No. of Tines | Approx. H.P. | Wt. |
|-----------|---------------|---------------|--------------|--------------|------|
| B100 | 40" | 44" | 30 | 20 HP | 300# |
| B120 | 48" | 52" | 36 | 25 HP | 335# |

ROTARY TILLERS

"C" Series - For compact tractors 20 to 45 HP



Our **"C" Series** has a number of special features that are standard, such as; slip clutch, all gear final drive, 6 tines per rotor plate, and heavy A.S.A.E. quick hitch A-frame. Excellent tiller for vegetable growers, landscapers, nurseries, vineyards, and general maintenance operations.

- Strong, smooth running, all gear final drive
- Slip clutch driveshaft to protect tractor and tiller drive system
- Curved saber style, heat treated, long wearing tines
- 6 Tines mounted on each rotor plate for maximum tilling action
- Tines staggered in scroll design for easy soil penetration
- Powder coated, baked-on paint to reduce corrosion
- Cat. I, 3-point hitch
- 8" Approximate tilling depth
- One speed gearbox, 540 RPM

| Model No. | Tilling Width | Overall Width | No. of Tines | Approx. H.P. | Wt. |
|-----------|---------------|---------------|--------------|--------------|------|
| C85 | 34" | 38" | 24 | 20 HP | 450# |
| C105 | 42" | 46" | 30 | 25 HP | 485# |
| C125 | 50" | 54" | 36 | 30 HP | 510# |
| C145 | 56" | 60" | 42 | 35 HP | 545# |
| C165 | 65" | 69" | 48 | 40 HP | 590# |
| C185 | 72" | 76" | 54 | 45 HP | 640# |

ROTARY TILLERS

"E" Series - For tractors 20 to 50 horsepower

Reverse Rotation E Series in 60" and 72" tilling widths. The counter rotation greatly aids in operating in hard ground. The reverse rotation achieves more depth and pulverizes the soil, plus buries clods, stones and debris. Ideal for preparation of seedbeds, renovation of pastures, orchards, vineyards and mulching-in cover crops and stubble. Provides uniform mixture through-out cultivated depth. Produces loose textured soil that holds moisture, reduces erosion.



Reverse Rotation

| Model No. | Tilling Width | Overall Width | No. of Tines | Approx. H.P. | Wt. |
|-----------------------|---------------|---------------|--------------|--------------|------|
| E48 | 48" | 53" | 36 | 20-35 HP | 600# |
| E60 | 60" | 65" | 42 | 25-40 HP | 690# |
| E72 | 72" | 77" | 54 | 35-45 HP | 780# |
| E84 | 84" | 89" | 66 | 50-70 HP | 805# |
| E60R* | 60" | 65" | 42 | 40-45 HP | 710# |
| E72R* | 72" | 77" | 54 | 45-50 HP | 800# |
| *R - Reverse Rotation | | | | | |

These medium duty **"N" Series** tillers feature a smooth running, all gear drive system. Powered through a heavy 70 horsepower gearbox to an all gear final drive. The tilling action provides a uniform mixture throughout the cultivated depth. Producing loose textured soil that holds moisture and reduces erosion. These are the ideal tillers for farm, vineyard, orchards, landscapers, nurseries, etc.

- Cat. I & II, 3-point hitch
- 8" Approximate tilling depth
- One speed gearbox, 540 RPM
- Strong, smooth running, all gear final drive
- Slip clutch driveshaft to protect tractor and tiller drive system
- Curved saber style, heat treated, long wearing tines
- Tines staggered in scroll design for easy soil penetration
- Powder coated, baked-on paint to reduce corrosion
- Side mounted skids for depth control



- Connects to 3-point, Cat. I, 540 R.P.M. tractors - 7' Cat I & II
- All gear, final drive
- Rugged construction for long life
- Heat treated, long wearing tines
- 6 - L shaped tines per flange
- Adjustable skids for depth control
- Torque tube frame to absorb shock loads
- Driveshaft with slip clutch
- Up to 70 H.P. - E84 only

ROTARY TILLERS

"N" Series - For tractors 40 to 70 horsepower



Cat. I & II
A.S.A.E.
Quick Hitch
Compatible

| Model No. | Tilling Width | Overall Width | No. of Tines | Approx. H.P. | Wt. |
|-----------|---------------|---------------|--------------|--------------|-------|
| N130 | 51" | 57" | 30 | 40 HP | 780# |
| N155 | 61" | 67" | 36 | 50 HP | 895# |
| N180 | 71" | 77" | 42 | 60 HP | 970# |
| N205 | 81" | 87" | 48 | 70 HP | 1045# |

ROTARY TILLERS

"S" Series - For tractors 50 to 90 horsepower



These **"S" Series Tillers** were designed for high usage in agricultural and industrial applications. At a depth of 8 inches, the saber tines produce a uniform mixture of loose, textured soil that holds moisture and reduces erosion. These tillers are extremely well built, with 4 speed gearbox, all gear final drive and slip clutch driveshaft for heavy duty use. There is no better tool for preparation of seedbeds.

| Model No. | Tilling Width | Overall Width | No. of Tines | Approx. H.P. | Wt. |
|-----------|---------------|---------------|--------------|--------------|-------|
| S160-CT | 63" | 68" | 36 | 50 HP | 1066# |
| S180-CT | 73" | 78" | 42 | 60 HP | 1255# |
| S205-CT | 83" | 89" | 48 | 70 HP | 1350# |
| S230-CT | 92" | 99" | 54 | 80 HP | 1430# |
| S255-CT | 102" | 107" | 60 | 90 HP | 1490# |

CT in model number stands for Tungsten Coated Tines

- Cat. II fixed center mount
- 90 HP, 4 speed gearbox
- 4-speeds at 540 RPM
- All gear final drive
- Slip clutch driveshaft
- 6 Tines on each rotor plate - staggered
- Torque tubing frame to absorb shock loads
- Adjustable skids for depth control

OPTION:

- ~ 2 Speed 1000 RPM gears

ROTARY TILLERS

"T" Series - For tractors 90 to 160 horsepower



Standard On All S & T Series Tillers:

- New super alloy tungsten carbide tines
- Bonded coating placed on the area of normal tine wear
- The "Rockwell" hardness of 70, which is the maximum hardness for tine wear
- Guaranteed to double the life over standard tines with normal life of 3 to 4 times longer wearing.
- 10" Approximate tilling depth
- 4 Speed gearbox - 2 speeds @ 540 RPM & 2 speeds @ 1000 RPM
- Strong, smooth running, all gear final drive

These **"T" Series Tillers** were designed for high horsepower tractors to produce a finished seedbed in a single pass. For crops such as vegetables, timing is everything. The basic plow, disc, cultivator tilling operation requires too many passes, wasted fuel, and causes excessive compaction. At a depth of 10 inches, the saber tines produce a uniform mixture of loose, textured soil that holds moisture and reduces erosion. There is no better tool for preparation of seedbeds and incorporating crop residue.

- Curved, saber style heat treated, long wearing tines
- Slip clutch driveshaft to protect tractor and tiller drive system
- Side mounted skids for depth control
- 6 Tines mounted on each rotor plate for maximum tilling action
- Large, oil bath, long wearing rotor bearings
- Cat. II, 3-point hitch

| Model No. | Tilling Width | Overall Width | No. of Tines | Approx. H.P. | Wt. |
|-----------|---------------|---------------|--------------|--------------|-------|
| T230-CT | 90" | 97" | 54 | 90-100 | 2140# |
| T280-CT | 110" | 117" | 66 | 100-120 | 2205# |
| T305-CT | 120" | 127" | 72 | 120-160 | 2275# |
| T355-CT | 140" | 147" | 84 | 120-160 | 2415# |

INCORPORATORS - S SERIES

Rotary Tillers With Rollers - For vineyards and orchards

An important application for this tiller with rear roller is to bury wood chips by tilling 2 to 3 inches deep. The roller then slightly compacts and smooths out the vineyard and orchard floors. The wood chips will decompose at a faster rate and the rolled out area is then in better condition for the harvesters.

Growers have found many more uses for the **Incorporators**. Such as - tilling out tractor tire tracks, mulching in weeds and general floor maintenance.



MODEL S160RR-CT

| MODEL # | TILLING WIDTH | OVERALL WIDTH | NO. OF TINES | MAXIMUM H.P. | WT. |
|-----------|---------------|---------------|--------------|--------------|-------|
| S160RR-CT | 5'-3" (63") | 5'-9" (69") | 36 | 90 HP | 1900# |
| S180RR-CT | 6'-1" (73") | 6'-6" (78") | 42 | 90 HP | 2090# |
| S205RR-CT | 6'-11" (83") | 7'-5" (89") | 48 | 90 HP | 2290# |

TILLER FEATURES:

- Cat. II, 3-point hitch
- A.S.A.E. quick hitch compatibility for easy hook-up
- 4 Speeds @ 540 RPM & 2 speeds @ 1000 RPM
- Strong, smooth running, all gear final drive
- Slip clutch driveshaft to protect tractor and tiller drive system
- New super alloy tungsten carbide coated tines, with normal life 3 to 4 times longer over standard heat treated tines
- Gearbox supported by full length tubes for added support
- Large, oil bath, long wearing rotor bearings
- Side mounted skids for depth control
- 16" Dia. x 1/4" wall steel tubing roller with adjustable mud scraper
- Turnbuckle height adjustment to obtain exact compaction required
- Roller is 6" wider than side plates to eliminate ridges
- 4 Tailboard turnbuckles to hold the tailboard in place for releasing the exact amount of soil to the roller



MODEL S255RR-CT



Levels, Rolls & Lightly Firms Vineyard Floor



Cleaned, Tilled & Rolled Orchard Floor

| MODEL # | TILLING WIDTH | ROLLER WIDTH | NO. OF TINES | APPROX. H.P. | WT. |
|-----------|----------------|---------------|--------------|--------------|-------|
| S205RR-CT | 6' - 11" (83") | 7' - 5' (89") | 48 | 50 - 70 H.P. | 2290# |
| S230RR-CT | 7' - 8" (92") | 8' - 2" (96") | 54 | 60 - 80 H.P. | 2500# |
| S255RR-CT | 8 1/2' (102") | 9 1/2' (114") | 60 | 70 - 90 H.P. | 2850# |

ROTARY TILLERS

Orchard Incorporators - For year round floor maintenance



An important application for these tillers with rear rollers is to bury wood chips by tilling 2 to 3 inches deep. The roller then slightly compacts and smooths out the orchard floor. The wood chips will decompose at a faster rate and the rolled out area is then in better condition for the harvesters. The University of California Cooperative Extension recommended keeping wood chips and shredings in the orchards. They also stated that if well managed, prunings can become a source of organic matter and nutrients in the soil. Growers have found many more uses for the Incorporators. Such as - tilling out tire tracks, mulching in weeds and general floor maintenance.



O.E.M. Tines

Tillers Feature Bonded Tungsten Coated Tines

REAR ROLLER FEATURES:

- 18" Diameter x ¼" thick wall steel tubing roller with adjustable mud scraper
- Turnbuckle roller adjustment to obtain exact required compaction with no tools needed
- Easy to bolt up to standard T tiller
- Roller is 6" wider than side plates to eliminate ridges
- 2" Diameter solid bearing shaft
- ½" Thick bolt-on plates between tiller and tailboard to contain soil
- 4 Tailboard turnbuckles to hold the tailboard in place for releasing the exact amount of soil to the roller
- Heavy 1" x 3" roller mounting brackets

See page 88 for "T" tiller specifications.

SPECIFICATIONS:

| MODEL # | TILLING WIDTH | ROLLER WIDTH | ROLLER DIAMETER | NO. OF TINES | MINIMUM HORSEPOWER | WEIGHT |
|-----------|---------------|---------------|-----------------|--------------|--------------------|--------|
| T280RR-CT | 9'-2" (110") | 10'-2" (122") | 18" | 66 | 80 | 3075# |
| T305RR-CT | 10' (120") | 11' (132") | 18" | 72 | 90 | 3375# |
| T355RR-CT | 11'-8" (140") | 12'-8" (152") | 18" | 84 | 100 | 4080# |



T Tiller with Full Width Top Mast



Cleaned, Tilled, and Rolled Orchard Floor



Quick change speeds on 4 Speed Gearbox



The L.E.M.® Sawhead module was designed for mounting to many different types of equipment such as: tractors with front loaders, skid steer tractors, compact excavators etc. This Sawhead comes with a heavy 4" square beam for mounting. The body of the Sawhead is made of rust proof anodized material which is light weight, but stronger than steel. This housing module will not deform.



FEATURES:

- 4 - 24" diameter stainless steel saw blades
- Total cutting length of 80"
- 45 cc hydraulic motor requires 24 to 37 GPM, maximum pressure 3000 PSI
- Saw blades turn at a maximum of 2600 RPM
- The body of the saw blades is made of rust proof anodized material which is lightweight but stronger than steel
- Equipped with universal hydraulic block for limiting the cutting rotation speed of the blades
- Special centralized greasing system to each saw blade bearing
- The sawheads are also available in 2 or 3 blades

Built By:

COLLARD®

SPECIFICATIONS:

| Order Code: | Model No. | Description | Capacity | Hydraulics | Weight |
|-------------|-----------|--------------------|----------|--------------|----------|
| 5812.9007 | LEM6004 | Sawblade, 4 Blades | 6" max. | 24 to 37 GPM | 555 lbs. |

TRAILERS

Dump Trailers - Capacities of 1 ½ to 8 ton, rear and 3-way dump

1 ½ TON REAR DUMP



2 ½ TON REAR DUMP



4 TON 3-WAY DUMP



5 TON 3-WAY DUMP



Our Gearmore **Dump Trailers** offer 5 sizes and capacities to choose from, in rear and 3-way dump. We offer models in single and tandem axle with rear hinged tailgates on all models for ease in dumping. All our models offer foldaway tongue jacks and swivel clevis type hitches. Any user who needs to "haul and dump" will find these trailers save time and money. Some of the popular uses are golf courses, parks, cemeteries, landscapers, growers and ranchers.

OPTION:

~ Central door with adjustable gate for 5 & 8 ton trailers



| Model: | 1.5T50X72 | 2.5T60X96 | 4T63X99 | 5T63X99 | 8T60X120 |
|-----------------|------------|------------|------------|------------|------------|
| Cap. Wt: | 1.5 Ton | 2.5 Ton | 4 Ton | 5 Ton | 8 Ton |
| Capacity: | 35 cu. ft. | 77 cu. ft. | 2.5 cu.yd. | 2.5 cu.yd. | 3.5 cu.yd. |
| Tire Size: | 18x9.5-8 | 23x10.5-12 | 11L x 15 | 11L x 15 | 11L x 15 |
| # of Tires: | 4 | 4 | 2 | 4 | 4 |
| Weight: | 850# | 1500# | 1825# | 1900# | 2060# |
| Bed Width: | 50" | 60" | 63" | 63" | 60" |
| Bed Length: | 70" | 94" | 99" | 99" | 120" |
| Bed Height: | 21" | 30" | 33" | 33" | 31" |
| Bed Floor: | 12 Gs. | ¾" Plate | ¾" Plate | ¾" Plate | ¾" Plate |
| Overall Width: | 54" | 64" | 68" | 66" | 88" |
| Overall Length: | 8' 6" | 11' 8" | 11' 6" | 11' 6" | 13' 8" |
| Overall Height: | 34" | 52" | 61" | 61" | 61" |
| Dump Angle: | 45° | 45° | 45° | 45° | 45° |
| Side Panels: | 13" High | 14" High | 14" High | 14" High | 16" High |
| Rear Panel: | 14" High | 19" High | 18" High | 18" High | 24" High |
| Front Panel: | 13" High | 19" High | 18" High | 18" High | 24" High |

8 TON REAR DUMP



VINE TRIMMERS


For Vineyards - Fits many different trellis systems

The new **P2200S Universal Vine Trimmer** was developed to be adjustable for a number of different trellis systems. This Vine Trimmer can be set for Vertical Shoot Positioned (VSP), Gable Trellis, California Sprawl and Double Cross arm Trellis Systems.

The heart of the COLLARD trimmers is the unique lightweight aluminum alloy element that provides a rugged, rustproof framework for the cutting blades. The exclusive saber shaped, non-clogging stainless steel blades never need sharpening. Our trimmers eliminate excess vine growth, open canopies for better air circulation and greatly improve spray and dust penetration.


COLLARD designed the first vine trimmers and continues to be the world leader in vine trimmers.

P2200S UNIVERSAL




California Sprawl


| Order Code | Model Number | Vertical Cut | No. of Blades | No. of Hyd. Motors | Row Width Adjustment | Weight |
|------------|------------------|--------------|---------------|--------------------|----------------------|--------|
| 0113 4400 | P2200S/Universal | 63" to 98" | 12 | 6 | 53" to 88" | 1200 # |



**VERTICAL SHOOT
POSITION (VSP)**



**DOUBLE CROSSARM
TRELLIS SYSTEM**



**QUAD TRELLIS
SYSTEM**

- Heavy duty reinforced, modular frame construction
- Total adjustments to fit many different trellis systems
- Adjustable hydraulic motor driven skirts can be set at 45° angle or vertical
- "State of the Art" hydraulic motors to insure long life
- Unique hose track "E" system for hose protection
- Blades turn at 2200 R.P.M., ensures clean cane ends, which dry and seal neatly to reduce the risk of disease
- Equipped with electro-hydraulic joystick controls for precise trimmer adjustments
- High speed stainless steel blades, self cleaning and never need sharpening
- Trimmers come with all hoses, fittings and JIC couplers

Built By:

COLLARD®

VINE TRIMMERS

For Vineyards - Profilmatic® high speed rotary blade trimming



FEATURES - P2200S:

- Heavy duty forklift style frame
- Trims two half rows
- Frame cutting blades adjustable from 4' to 9'
- Equipped with electro-hydraulic joystick controls for precise trimmer adjustment
- Strong, but lightweight and easy to operate
- Vertical breakaway system to protect trimmer and tractor
- High speed stainless steel blades, self cleaning and never need sharpening
- Adjustable angle motor driven skirts
- Blades turn at 2200 RPM ensures clean cane ends which dry and seals neatly to reduce the risk of disease
- Requires hyd. capacity of 5.2 GPM at 2200 PSI
- Machines have a wide range of adjustments for setting trimmers to operator's exact requirements
- Trimmers have both mechanical and hydraulic protection on side and topping blade assemblies
- Hydraulic cylinders are fitted with load/hold check valves for safety in case a hose fails
- Trimmers come with all hoses, fittings and JIC couplers
- Other models are available for half row, one complete row, and two complete rows - split frame trimmer is available for terraced vineyard
- Front mountings are available for most popular tractors

1 half row




1 complete row




2 half rows



2 half rows w/skirts



2 complete rows



| Model No. | Description | Width Adjustment | Cutting Height | Cutting Tops | Weight |
|-----------|---------------------|------------------|----------------|--------------|--------|
| P2200S | Trimmer with Skirts | 49" to 108" | 63" | 30.7" | 790# |

Built By:

COLLARD®



Patented Stainless Steel Blades

VINE TRIMMERS

For Vineyards - Complete range of vine trimmers



Model P1100
Trims Half Rows



Model P3000 LZP
Trims 1 Complete Row



Model P2200
Trims 2 Half Rows



Model P2200S
Trims 2 Half Rows, Plus Skirts



Model P2200TS
Trims 2 Half Rows, Terraced Vineyard



Model P3200X
Trims 2 Complete Rows

DESIGNED FOR TRIMMING

The aerodynamic shape of this profiled body was designed to facilitate more efficient penetration of the Trimmer **PROFILMATIC®** into the canopy, this profile also improves the fluid discharge of cut material.

RIGID BLADE ELEMENT (COLLARD patent)


This extreme duty assembly is nearly indestructible due to the unique design. This unit is without equal and guarantees the reliability of the blade transmission.

PROTECTED TRANSMISSION

Enclosed by a special cover, the transmission is completely protected against debris, dust, rain, etc.

SHOCK ABSORPTION

The leading edge of this section is made of synthetic material, it absorbs possible shocks, recessed screws of connection between the modules, ensures a smoother profile which facilitates the smooth evacuation of cut material.



POWERFUL TRANSMISSION

The **PROFILMATIC®** is even more powerful, ensuring a very high working speed yet reducing the required power input.

Built By:

COLLARD®

LEAF REMOVER

Unique Removal System - With dual rotor heads pulsed air shatters leaves



MODEL E1100FR.V3

DESIGNED TO OPERATE IN MANY DIFFERENT TRELLIS SYSTEMS



Elliptical shaped dual rotor defoliation head

Our "State of the Art" Leaf Remover has 8 new design features which allow for operating in many different trellis systems.

The COLLARD with double flow of low pressure air, produced by the compressor, blows through the leaves by dual rotating nozzles that remove the leaves on both the outside and the interior of the row; achieving selective leaf removal around the grape clusters. Only this technology makes it possible to "leaf" from falling flower heads to the harvest.

Built By:
COLLARD®

SPECIFICATIONS:

| Order Code | Model Number | Description | Hydraulic Requirements | Pressure | Minimum Horsepower | Weight |
|------------|--------------|--------------|------------------------|----------|--------------------|-----------|
| 0411 0300 | E1100FR.V3 | Leaf Remover | 8 G.P.M. | 2400 | 60 H.P. | 1300 lbs. |

FEATURES:

- **ELLIPSE-MULTIROTOR®** dual rotor defoliation head - "patented"
- Reinforced pivot system for 180° right to left position
- Narrower defoliation head for better penetration into the vegetation
- Adjustment system of defoliation head for positioning horizontal to vertical & in between
- Chassis designed to extend the arm supporting the head horizontally to avoid branch damage
- The defoliation heads are completely adjustable to any angle required
- 3-Pt hitch mounted air compressor, PTO driven
- Compressor is fitted with special prefiltration and ventilation kit
- Electric control distributor with ergonomic handle
- Hydraulic adjustment with three cylinders:
 - 1 - up/down independent of defoliation head
 - 1 - in/out independent of defoliation head
 - 1 - pivot
- The stainless steel covered head is effective up to 6 inches away from clusters

MANY OTHER LEAF REMOVERS AVAILABLE - CONTACT US FOR DETAILS

LEAF REMOVERS

Unique Leaf Removal System

These leaf removers feature Ellipse-Multirotor dual rotor defoliation heads "patented". The double flow of low pressure air blows through the leaves on both the outside and interior of the rows achieving selective leaf removal around the grape clusters. This rapid pulsing air literally shatters the leaves from the foliage and rattles the caps free from the berries.



MODEL E2200 F

Our leaf removal system is so effective that it can be used through the whole season from before flowering to harvest.

The COLLARD exposes the clusters to air and sunlight and improves spray penetration. We are able to give all the results like handwork at a fraction of the cost per acre.



MODEL E1100 3P

FEATURES:

- **ELLIPSE-MULTIROTOR** dual rotor defoliation head - "patented"
- Front mount leaf removers available in single or double defoliating heads
- Heads are 27" long with twin rotors for maximum coverage
- Rapid pulses of low pressure (15 PSI) air shakes the leaves to pieces
- The stainless steel defoliating heads are effective up to 6" away from the grape clusters
- Both inner and outer leaves and trash are removed around fruit zone
- Electric oil flow regulator to adjust the nozzle rotation speed
- Tractor requirement is 60 HP minimum with hydraulic capacity of 8 GPM at 2400 PSI
- Air compressor is 3-point hitch mounted with 540 RPM P.T.O.
- Compressor has exhaust silencer and air intake filter
- Electro hydraulic controls are standard
- Leaf trimmers come with all hoses, fittings and JIC couplers
- Comes with storage/parking stand

Built By:

COLLARD®

SPECIFICATIONS:

| Order No. | No. of Heads | Position of Heads | Working Position | Heads Reverse |
|----------------|--------------|-------------------|------------------|---------------|
| E1100 3P-ELLIP | 1 | Rear | In-Row | Yes |
| E2200 F-ELLIP | 2 | Front | In-Row | No |

PREPRUNERS

For Vineyards - To reduce the cost of hand pruning

PCI3000LPR SERIES



The **COLLARD Prepruners** will greatly reduce your pruning costs. Growers state that the finish hand pruning takes only 25% of the time versus total hand pruning costs. The Prepruner cuts the long canes small enough that they fall through the wire which is an aid in clean-up.

The Prepruner features a dual system for opening and closing of the cutting heads, **UNIQUE MAGNETIC SENSORS** and manual hand lever.

These front mounted Prepruners for vertical trellis vine grapes are low maintenance and high production giving the COLLARD units high marks with several leading California growers.



Magnetic sensors - Open and close cutting heads when sensing steel posts



Cutting blades and notched discs for clean cuts and trellis post protection

FEATURES:

- Heavy front mount frame for mounting to tractor
- Cane cutting length of 32.5"
- Dual hydraulic motors to power the cutting blades
- Three hydraulic cylinders - one for up and down, one stroke cylinder for in and out and one stroke cylinder for cross slope
- Cylinders are fitted with anti-fall safety valves
- Simple spring system to adjust the blade pressure
- Comes with heavy duty shipping/storage stand
- Tractor requirements of at least 6.6 GPM at 2030 PSI
- Custom built brackets are required for tractors and harvesters

SPECIFICATIONS:

| Order Number | Cutting Height | Space Between Blades | No. of Blades | Wt. |
|--|----------------|----------------------|---------------|-------|
| 0176 4701 1825 | 32.5" | 4.3" | 8 per side | 1330# |
| Also available with manual retraction only | | | | |

Built By:

COLLARD®

PREPRUNERS

Box Prepruners - For high wire vineyards

PCI3000 Box

The **COLLARD Box Prepruners** were developed for pruning in "High Wire" vineyards. These Box Prepruners are very versatile as the four hydraulic cylinders operate up/down, in/out, and tilt 10° right and left. The operator has full adjustment control with a handy joystick. The one complete row unit features three aluminum cutting housings with each having two 17.7", 236 teeth saw blades. The heavy duty single post main beam allows for easy mounting to the front of tractors.


Also, available are two row prepruners for custom mounting to harvesters and other vehicles.



| Order Code | Model No. | Description | Mount Type | Weight |
|------------|-------------|--|------------|--------|
| 0180 0150 | PCI3000 BOX | Box Prepruner, One Complete Row | Tractor | 1050# |
| 0180 0100 | PCE3200 BOX | Box Prepruner, Two Complete Rows, for custom mounting (no center mast) | Custom | 500# |

FEATURES:

- Designed to prune one complete row
- Three 15cc hydraulic motors to power the saw blades
- Cane cutting heights are hydraulic adjustable from 47" to 86"
- Four hydraulic cylinders - one for up/down, two for in/out, and one for tilting 10° right and left
- Cylinders are fitted with anti-fall safety valves
- Hydraulics controlled with joystick
- The three aluminum cutting housings each have two 17.7" (450mm) 236 teeth saw blades
- Tractor hydraulic requirement of at least 10.5 GPM at 2600 PSI
- Prepruners come with storage stand
- Custom built brackets are required for mounting to front of tractors



Built By:

COLLARD®

IMPLEMENTS

Work saver Implements - Time and labor saving products

Grapple Sifting Buckets



These **Grapple Sifting Buckets** are available in widths of 72 and 84 inch. The unique upper grapple design allows for sweeping up rock, brush and other hard material into the bucket while leaving the dirt behind.

- Universal skid steer mounting bracket
- Dual cylinders - full length grapples
- Removable side plates
- Grapple opening 45" - 2 1/2" opening between sifting bucket rods

Grader Blades



This patented **SSGB-8B Grader** was designed to be used by asphalt, landscape and concrete contractors. The grader has a wide 8', 6-way hydraulically controlled moldboard operated by in-cab remote controls.

- Long main beam w/caster wheels & 18.5"x8.5" tires
- 15" high moldboard with double bevel cutting edges, shear pin protected
- Moldboard rotation left & right, tilt up and down all up to 25°
- Pair of removable end plates

Concrete Mixers



Work saver's **Skid Steer Mount Mixer**, Model SS-590 has direct hydraulic drive. This eliminates chain and sprocket maintenance resulting in more up time on the job-site. Featuring all welded steel drum with internal paddles.

- 11 cu. ft. drum with mixing capacity of 5 cu. ft. of concrete (1 bag mix)
- Flow control valve for easy on-off operation
- Includes hoses with flat faced couplers
- Long based removable parking stands

Post Drivers



These hydraulically operated **Post Drivers** are available in 3-point hitch, loader mount, skid steer mount and in manual or hydraulic adjustment. Maximum post size of 8 3/4" diameter by 10' long.

- Designed to do both wood and steel posts
- Impact at full stroke is 80,000 pounds
- Spring loaded arm holds posts securely for "hands free" operation
- Transport pin secures units for travel and storage

Built By:

WORKSAVER



Implements To Make Your Tractor More Productive



13477 Benson Ave. • Chino, CA 91710

Ph: 909/548-4848 • 800/833-3023

www.gearmore.com