

QC Angle Broom

For skid-steer loaders, backhoe-loaders, and utility loaders.

FEATURES:

- 60", 72", 84" & 96" models available
- no hydraulic line breakage when changing core
- 32" diameter brush for longer life
- mounts to existing mountings/ interchangeable with S/D32 Series tractor/truck and loader mountings
- fold away stands
- modular design - can easily change single into dual or dual into single
- replaceable hex drive system
- quick change core
- new faceted hood design provides maximum strength at the ends of the hood where most stress and damage occur
- universal skid-steer mounting standard, other quick attach optional mounts available
- manual angle change 30° left to 30° right is standard



PALADIN LIGHT CONSTRUCTION



QC Angle Broom

OPTIONS

- optional hydraulic angle with electric valve
- dirt deflector
- 180° hood
- dust suppression system
- single to dual and dual to single conversion
- PTO driven hydraulic systems
- choose from poly, wire, or poly/wire brushes
- tube brush configuration

Specifications	60"	60"	60"	72"	72"	72"	84"	84"	84"	96"	96"
model number	21059	21060	21061	21071	21072	21073	21083	21084	21085	21096	21097
weight (lbs)	793	793	829	852	852	890	915	915	953	982	1022
working width	60"	60"	60"	72"	72"	72"	84"	84"	84"	96"	96"
overall width	70.5"	70.5"	70.5"	82.5"	82.5"	82.5"	94.5"	94.5"	94.5"	106.5"	106.5"
width @ 30° angle	54"	54"	54"	64"	64"	64"	75"	75"	75"	85"	85"
motor size	18" ³	24" ³	18" ³	18" ³	24" ³	18" ³	18" ³	24" ³	18" ³	24" ³	18" ³
motors	single	single	dual	single	single	dual	single	single	dual	single	dual
GPM range	10 to 18	12 to 25	18 to 36	10 to 18	12 to 25	18 to 36	10 to 18	12 to 25	18 to 36	12 to 25	18 to 36

Specifications and design are subject to change without notice and without liability, therefore, whenever applicable specifications are in accordance with SAE standards.



2800 North Zeeb Road
Dexter, MI 48130
United States of America
PH: (800) 456-7100
FX: (734) 996-9014
www.paladinbrands.com