

# PALLET FORKS

## BRACKETS FOR LOADER PIN-ON, JD QUICK ATTACH, & SKID STEER

These handy *Fork Attachments* can make your tractor/loader into a low cost forklift. Models include John Deere and Skid Steer quick attach pallet forks. The forks feature lockable tines and slotted rails. The solid tines are made of Boron Steel and then are heat treated. Two mounting styles are available; direct pin-on and JD quick attach.

#### NPF-3748F Shown



#### FEATURES:

- Load capacities of 2250 and 3750 lb.
- Fits compact and utility loaders
- Forks are constructed of Boron steel and heat treated
- Adjustable and lockable rail style forks
- Equipped with high visibility load guard
- New Skid Steer forks have bolt-on Gearmore logo plate when removed become walk through design

SPECIFICATIONS								
MODEL:	ULF-2242 Pin-On	ULF-3548 Pin-On	JLF-2242 JD QA	NPF-3742F SSL	NPF-3748F SSL			
Lift Cap:	2250 lbs.	3750 lbs.	2250 lbs.	3750 lbs.	3750 lbs.			
Fork Length:	42"	48"	42"	42"	48"			
Tine Size:	1 ¼" x 3" Solid	1 ¼" x 4 ½" Solid	1 ¼" x 3" Solid	1 3⁄8" x 4" Solid	1 3⁄8" x 4" Solid			
Loader Mounts:	Compact loaders between 28 ¼" ID & 47 ¼" OD w/¾" or 1" pins	Loader frames between 32" ID & 48" OD with 1" or 1 1/8" pins	Fits JD compact loaders w/quick change attach. carrier	Fits skid steer quick attach 3750# capacity at 21" load center	Fits skid steer quick attach 3750# capacity at 21" load center			
Weight:	280#	385#	280#	375#	395#			



EARMORE

INE.

WARNING: The loader mounted fork attachments are specifically designed to engage and load palleted materials. Do not use forks to handle large loads, such as bales, posts, etc., and avoid carrying loose or shiftable loads, as they can fall or roll back onto operator causing serious injury or death.



www.gearmore.com • sales@gearmore.com



# **PALLET FORKS**

### Available For Universal, John Deere, and Global/Euro Quick Attach

The new heavy duty frames are designed to handle both the 3750 and 5500 lb. capacity forks. The 10 gauge brickguard offers outstanding strength and smooth surface for protection and less load damage. Also, the convenient non-skid step offers easy operator access, except 2300 lb. capacity. The tine end visibility is excellent.

### **FEATURES:**

- Available in 2300, 3750 & 5500 lb. capacities
- Fork tines available in 42" & 48" length
- Exclusive load retention hook for securing and positioning pallet loads
- Solid tine positioning w/spring loaded toggle operation
- Easy loading with tapered tines

Your Gearmore Dealer

3750 lb. Capacity Shown

> 2300 lb. Capacity Shown

SPECIFICATIONS							
Code No:	Description	Capacity	Tine Length	Wt.			
107283/106220	SSL QA Fork Assy.	2300 lbs.	42"	270#			
107283/106222	SSL QA Fork Assy.	2300 lbs.	48"	285#			
17380 / 102028	SSL QA Fork Assy.	3750 lbs.	42"	450#			
17380 / 102030	SSL QA Fork Assy.	3750 lbs.	48"	480#			
101177/102028	JD QA Fork Assy.	3750 lbs.	42"	410#			
101177/102030	JD QA Fork Assy.	3750 lbs.	48"	440#			
17380/102032	SSL QA Fork Assy.	5500 lbs.	42"	490#			
17380/102034	SSL QA Fork Assy.	5500 lbs.	48"	500#			
109065/1102034	Euro Global Fork Assy.	5500 lbs.	48"	465#			

Specifications Subject To Change Without Notice

13477 Benson Ave. • Chino, CA 91710 • Ph: 909/548-4848 • Fax: 909/548-4747