



# TANDEM DISCS "GT" SERIES

## HEAVY DUTY • PULL TYPE



- FRAMES:** 4" x 4" x ¼" Structural tubing
- HITCH:** Self leveling, spring cushioned with hand crank
- GANGS & BEARINGS:** 1 ½" Square gang axles with greaseable trunnion mounted, double sealed bearings with wear guards
- FRONT GANGS:** Adjustable 12 to 22 degrees
- REAR GANGS:** Adjustable 9 to 21 degrees
- BLADES:** 24" Diameter x 6mm notched front and plain rear blades on 9" spacing
- SCRAPERS:** Standard, adjustable individually or by gang
- WHEELS & TIRES:** 2 - 6 Bolt hub and spindle assembly  
2 - 9.5L x 15" 8-ply tires
- HYDRAULICS:** 3 ½" x 8" Cylinder with depth control and hoses
- REAR HITCH:** Standard equipment



*1 1/2" Triple sealed bearing in cast trunnion mount housing*



*Self leveling, spring cushioned hitch with hand crank*



*Replaceable nylon bearing on wheel mount*

MODEL NO.	NO. OF BLADES	NO. OF WHEELS	CUTTING WIDTH	WT.
GT-24T	24	2	9' - 2"	3300#
GT-28T	28	2	10' - 6"	3700#
GT-32T	32	4	12' - 0"	4140#
GT-36T	36	4	13' - 8"	4360#
GT-40T	40	4	15' - 0"	4800#
GT-44T	44	4	16' - 6"	5130#
GT-48T	48	4	18' - 6"	5610#

- OPTIONS:**  
Furrow Filler w/20" Diameter Blades (Pair)



13477 Benson Ave. • Chino, CA 91710  
Ph: 909/548-4848 • Fax: 909/548-4747

[www.gearmore.com](http://www.gearmore.com) • [sales@gearmore.com](mailto:sales@gearmore.com)