

RIPPING CHISELS

GRC Series - 3 Bar Finishing Chisel



Our 3 bar finishing **Ripper Chisel** is an effective implement for loosening soil up to 15 inches deep. The rigid shank design insures consistent depth. The narrow 12" shank spacing is excellent for breaking up and incorporating of residue. These ripping chisels are the perfect tool for opening up heavy soils for aeration. The main shank bars are on 3 foot centers and shanks are staggered to obtain maximum trash clearance. A large number of cross tubing braces are placed between the shank beams for added strength. The shear bolt shanks allow for higher speeds than most tillage implements.



13477 Benson Ave. • Chino, CA 91710 Ph: 909/548-4848 • Fax: 909/548-4747

GEARMORE INC.

www.gearmore.com • sales@gearmore.com



RIPPING CHISELS

FEATURES

- Cat. III & IV narrow, 3-point quick hitch compatible
- Frame 5" x 5" x 3/8" wall steel tube
- 3 Shank beams on 36" center
- Beam cross braces 2" x 4" x ¹/₄" wall
- 4 Tubing braces to support top mast
- Welded plow steel shank pockets
- 1 ¹/₄" x 30" Long rigid plow steel shanks with shear bolt protection, less points
- Shanks are on 12" centers
- Single gauge wheels 9.5L x 15"

OPTIONS:

- Dual gauge wheels 9.5L x 15"
- ³/₈" x 15" Reversible spike points
- Rear clevis hitch

Your Gearmore Dealer



Heavy 2 Position Gauge Wheels w/Turnbuckle (optional)



Large Reversible Points Held By 2 bolts (optional)



Reversible Hitch Pins Cat. III & IV N

SPECIFICATIONS:

MODEL NO.	WIDTH	DESCRIPTION	NO. OF SHANKS	WEIGHT
GRC-15	15 ft.	Ripper Complete	15	4450#
GRC-17	17 ft.	Ripper Complete	17	4750#
GRC-19	19 ft.	Ripper Complete	19	5050#
GRC-21	21 ft.	Ripper Complete	21	5350#
Other widths available on request				

Specifications Subject To Change Without Notice

13477 Benson Ave. • Chino, CA 91710 • Ph: 909/548-4848 • Fax: 909/548-4747