

VENTURI AIR SPRAYERS

TRAILER MOUNTED 300 & 500 GALLON CAPACITIES

"10 Year Warranty on Polyethylene Trailer Tanks"

These unique Venturi Air Sprayers feature our most powerful high speed turbine fans and are the latest technology in low volume spraying. Thus, growers achieve the following benefits: spray atomization of droplets are smaller and more uniform, less fill-ups, even distribution of concentrated spray, complete foliage coverage, better product utilization, less chemical waste and soil/water contamination.

Our Venturi Air Sprayers are available with many different spray heads to fit exact profile of your crops. All sprayers with your required spray heads are then completely assembled at our warehouse to insure quality.

Many different distribution spray heads are available.

500 Gallon Shown

Optional Floatation Tracks smooths out the ride, floats over wet ground and greatly reduces compaction.



GERRMORE



Sprayer operating with 2 lower and 2 upper orchard distribution heads to insure coverage on the upper half of trees



13477 Benson Ave. Chino, CA 91710 Ph: 909/548-4848 Fax: 909/548-4747

EARMORE INC.

www.gearmore.com • sales@gearmore.com



TRAILER MOUNTED VENTURI AIR SPRAYERS

FEATURES:

- Molded polyethylene 300 and 500 gallon tanks
- Translucent heavy walled tanks with hinged lid, strainer basket and shower head
- High performance precision balanced all steel, front mounted turbine fan
- Dual centrifugal pumps 37 G.P.M. for spraying and 37 G.P.M. for agitation
- Low pressure spraying system 15 to 40 PSI spraying pressure means less maintenance on pumps and nozzles
- Wheels are adjustable up or down, front or rear, or in and out to obtain the best balance and clearance
- Electro valve system controls spray off or on, both sides spray, and right or left only
- No gearbox for fan speed-up, unique simple power band system with built-in overrunning clutch
- Separate safety clean water 8 gallon tank for hand washing
- Dolly wheel adjustable parking stand

Your Gearmore Dealer:



Low pressure centrifugal pump made of anti-corrosive materials requires little maintenance



Rotating yellow calibration discs, adjusts easily to provide accurate and constant regulation of application



Power band fan speed up system with built-in overrunning clutch



Shower head is built into the main strainer basket to easily put wettable powders into suspension



Electro valve controls to operate on, off, left, and right spraying

Wheels adjust up or down, in or out, front or rear to obtain best balance and clearance

SPECIFICATIONS.							
Model No.	Gallons	Volume of Air	Min. Width	Length	Tire Size	H.P. Required	WT.
T55S2-1200	300 Gal.	8240 C.F.M.	55"	12'	11Lx15-8 Ply	60 H.P.	1020#
T55E2-1200	300 Gal.	9123 C.F.M.	57"	12'	11Lx15-8 Ply	74 H.P.	1020#
T55E2-2000	500 Gal.	9123 C.F.M.	71"	14'	12.5Lx15-10 Ply	74 H.P.	1320#

Specifications Subject To Change Without Notice

13477 Benson Ave. • Chino, CA 91710 • Ph: 909/548-4848 • Fax: 909/548-4747

SPECIFICATIONS