

# VENTURI AIR SPRAYERS

### FOG-SIZED DROPLETS INCREASE TOTAL PLANT COVERAGE



This unique sprayer was designed to produce a curtain of fog sized spray up to 90 feet. Our Venturi Air Sprayers feature the latest technology in concentrate spraying. Thus users achieve the following benefits: spray atomization of spray droplets are smaller and more uniform, less fill-ups, even distribution of concentrated spray, complete coverage, better product utilization and less chemical waste and soil/water contamination.

The cannon sprayers have many different applications such as row crop growers who have limited access to many of the rows or just lowering spraying costs by covering wide swaths. Nurseries find the sprayer very effective for the same reasons.

Dairies and feedlots find that these sprayers are a low cost way to control flies and other insects.



Model P55EI shown

13477 Benson Ave. • Chino, CA 91710 Ph: 909/548-4848 • sales@gearmore.com

www.gearmore.com





## 3-POINT HITCH CANNON SPRAYERS

### SPRAYER FEATURES:

- 3-Point hitch, 540 RPM PTO
- Molded polyethylene tank
- Available in 100 or 150 gallon
- High performance, precision balanced all steel centrifugal fan
- Translucent heavy walled spray tank with lids, sump and strainer basket
- Built-in overrunning clutch to protect tractor and sprayer
- Compact, rounded tank design permits traveling through vegetation without damage
- Simple, efficient "Dial-A-Rate", 15 position metering disc
- Agitation by liquid sparging tube and air from fan
- Low pressure spraying system 15 to 40 PSI spraying pressure means less maintenance for pumps and nozzles
- Power band fan speed-up is automatically adjusted by spring loaded idler
- Separate safety clean water 6 gallon tank for hand washing
- Electro-valve controls to operate on and off of spray, P55 only
- Optional electro-valve controls for P45 & P50

### **SPRAY HEAD FEATURES:**

- Horizontal cannons are available in high or low position (High position shown)
- Produces fog size spray droplets
- Pivots manually 180 degrees

SPECIFICATIONS:

• Optional electric swivel 180 degrees from tractor seat



Low pressure centrifugal pump made of anti-corrosive materials requires little maintenance



Rotating yellow calibration discs, adjusts easily to provide accurate and constant regulation of application



Electro valve controls to operate on, off, left, and right spraying - P55 only



Power band fan speed up system with built-in overrunning clutch



Shower head is built into the main strainer basket to easily put wettable powders into suspension



Large 3" dia. glycerin filled gauge, easy to see from tractor seat

#### **VOLUME OF AIR** MODEL NO. **SPRAY DISTANCE** GALLONS WIDTH H.P. REQ'D WT. P45N1-400-G 100 Gallons 44" 32 H.P. 455# 50 feet 3180 C.F.M. P50S1-600-G 70 feet 150 Gallons 4885 C.F.M. 57" 52 H.P. 540# P55E1-600-G 90 feet 9123 C.F.M. 57" 70 H.P. 150 Gallons 550#

#### Specifications Subject To Change Without Notice

13477 Benson Ave. • Chino, CA 91710 • Ph: 909/548-4848 • sales@gearmore.com