

BOX SCRAPERS GBS SERIES

AVAILABLE IN MANUAL, MECHANICAL, OR HYDRAULIC SHANK ADJUSTMENTS

HITCH



Conner

GBS/R SERIES RETRACTABLE SHANK Pull Handle To Adjust

This unique line of Box Scrapers are available in 3 different shank adjustments. The scraper box is all welded construction for added strength.

Whether you want to landscape, terrace, back-fill, scarify, level, or do general clean-up, the Gearmore Box Scrapers will fit your needs.

HYDRAULIC SHANK Pull Valve Handle To Adjust

> 13477 Benson Ave. • Chino, CA 91710 Ph: 909/548-4848 Fax: 909/548-4747



www.gearmore.com • sales@gearmore.com



BOX SCRAPERS

FEATURES:

- A.S.A.E. Cat. I, 3-point hitch*.
- For tractors up to 40 H.P. 4 wheel drive & 50 H.P. 2 wheel drive.
- 3 types of shank adjustments to choose from: MANUAL, MECHANICAL and HYDRAULIC.
- Designed without separate scarifier bar to improve view of cutting edge and reduce machine weight (GBS/R & GBS/H).
- All welded construction.
- Special "set back" shank pockets.
- Positive locking system in both engaged and retracted positions.
- Adjustable heat-treated scarifier shanks with replaceable points.
- $\frac{1}{2}$ " x 6" reversible cutting edges front and rear.
- A-frame mast $-\frac{1}{2}$ " thick x 6" wide.
- Side plates are ¹/₄" thick x 18 ¹/₂" high x 26 ¹/₂" long 72" and up are ³/₈" thick.
- Clevis type hitch points.
- 4" x 4" steel tubing main beam.
- Bushing kit required for quick hitch mounting
- Standard color is black most tractor colors available at no additional charge.

SPECIFICATIONS:

CUTTING WIDTH	OVERALL WIDTH	WEIGHTS		
		GBS	GBS/R	GBS/H
42"	42 1⁄2"	330#	360#	360#
48"	48 1⁄2"	355#	405#	405#
54"	54 1⁄2"	395#	435#	435#
60"	60 ½"	440#	480#	480#
66"	66 1⁄2"	490#	505#	505#
72"	72 3⁄4"	540#	575#	575#
76"	76 3⁄4"	560#	D.N.A.	600#
80"	80 3⁄4"	600#	D.N.A.	630#
84"	84 3⁄4"	620#	D.N.A.	D.N.A.



Special High Strength Shank Pockets

Adjustable Shanks



Side Plates Extended To Contain Soil When Back-Filling

Specifications Subject To Change Without Notice

13477 Benson Ave. • Chino, CA 91710 • Ph: 909/548-4848 • Fax: 909/548-4747