

# **DRAG SCRAPERS**

## **HIGH CAPACITY MODELS**



The "HC" High Capacity Series of Drag Scrapers feature heavy, large side plates - ½" thick. These side plates are 30" high by 40" deep, thus allowing for dragging and depositing large amounts of material. Like the "AP" series, the beam tongue extends to the rear moldboard and is held in place by a 5" x 5" heavy gusseted tube. The new axle assembly is built with 4" x 2" tubing. The larger dairies and feedlots find these scrapers best for their operations.

Now featuring larger tires and fold away tongue jack as standard equipment.

#### SPECIFICATIONS:

MODELS	WIDTH	CAPACITY	WEIGHT
HC8	8'	2 ½ cu. yd.	1450#
HC10	10'	3 1/4 cu. yd.	1630#
HC12	12'	3 ¾ cu. yd.	2100#

### **FEATURES:**

- For tractors 70 to 120 horsepower
- Working widths of 8, 10, & 12 foot
- ½" x 30" x 40" Deep side plate
- Clearance of 23" raised and 5" below grade
- Hydraulically operated from the tractor seat
- Moldboard ¼" plate, 30" high
- Internal braces to side plates and moldboard
- Main cross beam 4" x 4" tubing
- 3" x 8" Double acting cylinder and hoses
- Ribbed implement tires G70 15"
- Bolt-on swivel slotted hitch

#### **OPTIONS:**

- ~ Tilt axle w/cylinder & hoses
- ~ Dual wheels
- Bolt-on weight boxes



13477 Benson Ave. • Chino, CA 91710 Ph: 909/548-4848 • Fax: 909/548-4747

www.gearmore.com • sales@gearmore.com