

3-POINT SPRAYERS "Economy" Series

FEATURING HIGH QUALITY PISTON DIAPHRAGM PUMPS





Sprayer Shown With Folding Boom You will achieve total versatility and performance with our Economy Series of 3-point hitch sprayers. The sprayers feature reinforced polyethylene tanks suspended from a tubular steel, rust resistant zinc plated frame. The sprayer also features quality piston diaphragm pumps and built-in hand wash tank for convenience and safety.

The handy rear rails allow for easy mounting of berm booms, vertical booms, horizontal booms and hose reels.



13477 Benson Ave. • Chino, CA 91710 Ph: 909/548-4848 • Fax: 909/548-4747

www.gearmore.com • sales@gearmore.com



3-POINT SPRAYERS WITH OPTIONAL BOOMS

SPRAYER FEATURES:

- Cat. 1, 3-point hitch
- Tanks are made of reinforced polyethylene with smooth lines that are gentle to plants
- Tanks have large bottom sumps to insure complete drainage
- High pressure jet agitation
- Clean water tank for handwashing
- High performance piston diaphragm pumps
- Pressure gauge regulator valve
- Large suction filter with shut-off valve
- Rear mounted rails for mounting booms and hose reels

BERM BOOMS:

- Telescopic square frame tubing adjusts for 6 to 10 foot rows
- Wind proof spray heads with flexible polypylene brushes
- Each head is equipped with two anti-drip spray nozzles with Teejet 110 degrees, No. 3 flat fan tips
- Spring break away protection to prevent damage to the crop
- Includes hoses and shut-off valves

HORIZONTAL BOOMS:

- Available in 10, 14, 20, and 28 foot
- Powder coated black frame
- Stainless steel liquid tubing
- Anti-drip flat fan nozzles
- Includes hoses and shut-off valves



3 Piston Diaphragm Pump 50 Gallon - 2 Piston



Fresh Water Tank With Spigot

Your Gearmore Dealer:

Model No.	Tank Capacity	Pump GPM/PSI	Width	Height	Depth	WT.
GC200	50 Gallon	6 / 360	39"	46"	23"	175#
GC400	100 Gallon	11 / 580	44"	44"	36"	190#
GC600	150 Gallon	11 / 580	44"	56"	36"	225#

Specifications Subject To Change Without Notice

13477 Benson Ave. • Chino, CA 91710 • Ph: 909/548-4848 • Fax: 909/548-4747