

SLIDE T 180 HARVESTER



The **Slide T 180 Harvester** was developed for picking up all types of high density crops, such as spring mix, spinach, chard, etc. The stainless steel cutting band saw blade cuts off the crop within 1/2 inch of the bed top and the full width belt feeds the packers on the rear platform. Some of the special features are cutting height controlled by a proportional electro-hydraulic sensor that guarantees for a perfect cutting height control without damaging the products; hydraulic belt speed is controlled by manual valve operated by the packers, built-in brush for cleaning, large holder for empty and full boxes, adjustable height for leveling, and four adjustable furrow depth wheels.



Marketed By:



13477 Benson Ave. • Chino, CA 91710 • Ph: 909/548-4848
Fax: 909/548-4747 • www.gearmore.com

Slide T 180 Harvester

FEATURES:

- Cat. II, 3-point hitch
- Cutting width of 71 inches (180 cm)
- PTO driven self contained hydraulic system with oil cooler and reservoir
- Cutting height controlled by a proportional electro-hydraulic sensor that guarantees for a perfect cutting height control without damaging the products
- Parallelogram system made of two independent frames
- Minimum tractor power required - 50 HP, must have creeper speeds or hydrostatic
- The operating speed of the harvester will vary between 3/4 to 2 miles per hour, depending on the crop
- Belt mounted on a stainless steel frame
- Cutting system has a single stainless steel band saw blade
- Cutting band saw blade turns on self-centering pulleys covered with rubber that guarantees for better reliability and life of the blade
- The conveyor belt is built with non-toxic material for handling food
- The harvester will handle crops up to 15.8" (40 cm) tall
- Hydraulic belt speed is controlled by a manual valve
- Brush built-in for cleaning the conveyor belt
- Adjusting side light from the soil level multiplier
- Fold-up foot board on the back
- Large holder for empty and full boxes
- Four adjustable furrow depth wheels with 16 x 6.50 - 8 ply tires

NOTE: Cutting width also available, 55" (140 cm), 59" (150 cm), 63" (160 cm), and 67" (170 cm)



Self-contained hydraulic system with oil cooler and reservoir



Controls to rotate the belt, blade, and stop button



PTO driven dual hydraulic pumps and speed-up gearbox

SPECIFICATIONS:

Model No.	Description	Cutting Width	Overall Width	Overall Length	Overall Height	Tire Spacing	Bed Top Width	Total Weight
180	Slide T Harvester	71"	86.6"	118"	63"	84"	66"	990#