



DUMP TRAILER

1.5 TON CAPACITY, REAR DUMP



Hand Pump Model Shown

Our new 1 ½ Ton Dump Trailers are available in two different dumping systems. One unit has a self contained hand pump tilting system so the trailer dumping can be operated by a number of different vehicles. The second model uses the tractor hydraulics to operate the dumping position. The trailers are constructed of 12 gauge all welded sides and front panels for maximum strength and durability. The unique two-way tailgate opens from the top or bottom.

These trailers are ideal for landscapers, farmers, ranchers, and general usage. The units are designed for off road uses, not to exceed 20 MPH.



13477 Benson Ave. • Chino, CA 91710
Ph: 909/548-4848 • Fax: 909/548-4747

www.gearmore.com • sales@gearmore.com



DUMP TRAILER

FEATURES:

- 1 ½ Ton capacity, 35 cubic feet heaped
- Tandem walking beam axles
- 4 - 18" x 9.5" x 8" floatation tires
- All welded 12 gauge steel on sides and front panel
- Rear tailgate dumps with hinge to open at the top or bottom
- Safety lock-out bracket at dump position
- 3" x 12" Hydraulic cylinder
- Comes with both swivel clevis and 2" ball hitch
- Fold-away tongue stand

| | |
|---------------------------------|----------------|
| Bed Width | 50" |
| Bed Length | 70" |
| Bed Height | 21" |
| Bed Floor | 12 Gauge Steel |
| Overall Width | 54 inches |
| Overall Length | 8' - 6" |
| Overall Height | 34" |
| Dumping Angle | 45° |
| Side Panels | 13" high |
| Front Panel | 13" high |
| Rear Panel | 14" high |
| For off highway use only | |

Your Gearmore Dealer

SPECIFICATIONS:

| Model No. | Dumping | Capacity | Bed Size | Weight |
|-----------|--------------------|----------|-----------|--------|
| 1.5-DT-XB | Hand Pump | 1.5 Ton | 50" x 72" | 865# |
| 1.5T50X70 | Tractor Hydraulics | 1.5 Ton | 50" x 72" | 850# |



Tailgate Hinges From Top or Bottom



Cylinder and Safety Lock Bracket



Tandem Axle and Floatation Tires

Specifications Subject To Change Without Notice

13477 Benson Ave. • Chino, CA 91710 • Ph: 909/548-4848 • Fax: 909/548-4747