



IMPLEMENTS FOR COMPACT WHEEL TRACTORS

HIGH PRODUCTION ATTACHMENTS WITH SKID STEER QUICK ATTACH MOUNT

SIFTING BUCKET



Designed to collect rocks and debris, allowing soil to sift through. Rake design allows for fast clean-up, ground leveling and gathering materials away from buildings and obstructions. Leave the dirt and pay less at the land fill!

| Specifications | 108603 |
|------------------------------|--------|
| Width (overall) | 55.3" |
| Height (overall) | 21.5" |
| Length (overall) | 23.5" |
| Tine Spacing (between tines) | 2.0" |
| No. of Tines | 18 |
| Tine Rod Diameter | 1.13" |
| Weight (lbs) | 300# |

4 IN 1 BUCKETS



60" and 72" models available. Functions as a loader bucket, clam, grapple, dozer, box scraper, and bottom dump bucket. Has strong hinges and pins to distribute load. The bottom dump buckets allows the operator to dump into high side board trucks.

| Specifications | 108196 | 108198 |
|----------------------------|--------|--------|
| Width (overall) | 60" | 72" |
| Height (overall) | 27" | 27" |
| Length w/o Teeth (overall) | 28" | 28" |
| Front Length w/o Teeth | 15" | 15" |
| Rear Length | 14" | 14" |
| Grapple Opening | 28" | 28" |
| Weight (lbs) | 380# | 430# |

HYDRAULIC DIGGER



The D450 hydraulic digger is the most trouble free digger on the market. The unit features an in line sealed planetary gear reduction drive design. This clean, effective system ensures long trouble free usage. Digger comes with Q.A. brackets w/cradle

| Specifications | D450 |
|-------------------------|-------------|
| Min. Hyd. Flow | 5 G.P.M. |
| Max. Hyd. Flow | 10 G.P.M. |
| Max. Auger Diameter | 12" |
| Output Shaft | 2" Round |
| Auger Diameters | 6" 9" & 12" |
| Wt. of Digger & QA Brkt | 264# |



13477 Benson Ave. • Chino, CA 91710
Ph: 909/548-4848 • Fax: 909/548-4747

www.gearmore.com • sales@gearmore.com



IMPLEMENTS

FOR COMPACT WHEEL TRACTORS

High Production Attachments With Skid Steer Quick Attach Mount

BRUSH GRAPPLES



Aggressive grapple made of high strength steel for maximum performance and durability. Cylinder guard design protects cylinder while preventing build-up of debris. Great for cleaning up and transporting branches, brush, and limbs.

| Specifications | 108597 | 108598 | 108415 |
|-------------------|--------|--------|--------|
| Width (overall) | 48" | 54" | 72" |
| Height (overall) | 25.5" | 25.5" | 25.63" |
| Length (overall) | 30.5" | 30.5" | 30.5" |
| Tine Spacing | 5.7" | 5.7" | 5.7" |
| Grapple Opening | 29" | 29" | 29" |
| Clamp Force (lbs) | 1,100 | 1,100 | 1,100 |
| Weight (lbs) | 300# | 315# | 435# |

ROOT RAKES



The aggressive tine shanks root out objects below ground level. The wide grapple opening allows for gathering a large amount of brush and debris. The hydraulically operated grapple lock the material in place and stabilizes it for transport.

| Specifications | 109982 | 109983 | 109984 |
|------------------|--------|---------|--------|
| Width (overall) | 60" | 66" | 72" |
| Height (overall) | 28.1" | 28.1" | 28.1" |
| Length(overall) | 19.5" | 19.5" | 19.5" |
| Tine Spacing | 12" | 9/12/9" | 12" |
| Grapple Width | 57.1" | 57.1" | 57.1" |
| Grapple Opening | 32.5" | 32.5" | 32.5" |
| Weight (lbs) | 413# | 439# | 448# |

PALLET FORKS



High strength lightweight frame for large 2300 pound pay loads. Open guard for excellent visibility. Patented load retention ring. Class II ITA forks with positioning lock pin.

| Specifications | 107283/ 106220 | 107283/ 106222 |
|-------------------|-------------------|-------------------|
| Frame Width | 45" | 45" |
| Frame Height | 28" | 28" |
| Fork Thickness | 1" | 1" |
| Fork Width | 3" | 3" |
| Fork Length | 42" | 48" |
| Wt. Frame & Forks | 252# | 285# |

Specifications Subject To Change Without Notice

13477 Benson Ave. • Chino, CA 91710 • Ph: 909/548-4848 • Fax: 909/548-4747

Form # PA0003-19