

# FORESTRY DISK MULCHER

# **Unique Cutting Teeth Designed For Maximum Production**



### AGGRESSIVE FELLING AND PROCESSING

FELL UP TO 14 INCHES

PROCESS UP TO 8 INCHES

STUMP GRIND
TO GRADE

The FD60 High-Flow Disk Mulcher maximizes uptime, minimizes service intervals, and can withstand aggressive use in a variety of conditions. The FD60 was designed as a solution to common issues of jamming and unpredictability that other forestry disk mulchers face. Forestry disk mulcher skid steer attachments are used for forestry applications because they combine felling trees, mulching them, and stump grinding into one fast process. This product is equipped with Paladin's MulchPower Gauge $^{\rm TM}$ , allowing operators to see when maximum rotational energy is stored in the disk so they can take down trees with full strength, as well as many other features to increase tool life and productivity.



SHIPPED WITH TRANSPORT GUARD

Distributed by:



13477 Benson Ave. • Chino, CA 91710 Ph: 909/548-4848 • Fax: 909/548-4747

www.gearmore.com • sales@gearmore.com



# **FORESTRY DISK MULCHER**

#### **FEATURES:**

- SSL quick attach mounting bracket
- Flow required 30 to 45 G.P.M. at 3,300 PSI minimum (case drain required)
- Rated operating capacity 2,600 lbs. minimum
- Ultra-efficient drive system with fast start
- MulchPower<sup>TM</sup> gauge for maximum energy
- Bearing housing never needs to be greased
- Debris shovel keeps teeth out of the dirt
- Some teeth are mounted on top, bottom and edge of the disk
- High quality QUADCO teeth are interchangeable, allows for simple service and rotation
- Solid steel teeth disk weighs over 900 pounds
- Mulchers come assembled


NOTE: Highly recommend resistant shield/front window to protect operator

Your Gearmore Dealer:





EDGE MOUNTED CARBIDE TEETH



TEETH WITH MOUNT

#### SPECIFICATIONS:

CODE NUMBER	MODEL NUMBER	DESCRIPTION	CUTTING WIDTH	NO. OF TEETH	MACHINE WEIGHT
125260	FD60	Disk Mulcher	60"	44	2410#
Comes standard with 3/4" couplers					