

FLAIL SHREDDERS GHF Series

Designed For Extreme Duty Brush Shredding



This shredder is specially designed for severe conditions. Tall grass and weeds, cover crops, orchard prunings and even citrus brush are no match for this heavy duty machine. The 3 lb. drop forged hammer knives shred branches up to 4" in diameter. The 2000 RPM large diameter rotor makes a fine mulch. Designed to insure years of trouble free usage.

Front or Rear Mount

Ħ

Hammer Knife



13477 Benson Ave. • Chino, CA 91710 Ph: 909/548-4848 • Fax: 909/548-4747

www.gearmore.com • sales@gearmore.com

HAMMER KNIFE SHREDDERS

FEATURES:

- Fits Cat. II 3-pt. hitches, center mount
- Front or rear tractor mount

EARMORE

- Shreds brush or prunings up to 3", intermittent 4"
- Gearbox maximum horsepower of 200, with built-in overrunning clutch
- Specially designed drop forged hammer knives give optimum performance in brush shredding, mulching prunings, grass cutting and maintenance of cover crops
- Double row of drop forged cutter bars to increase the shredding of material
- Equipped with a patented rear deflector which in open position discharges grass and allows tractor speeds up to 6 M.P.H., and in closed position contains and further shreds brush to a finer mulch
- 10" diameter, computer balanced, vibration free rotor turns at 2000 RPM
- Rotorshaft bearings are double self-aligning to insure long life
- 5 belt drive protects gearbox, driveshaft and rotorshaft
- 8" diameter, full width gauge roller with external bearings
- Hood plate ¼" thick, double plated front and back side plates ½" thick
- Double row of front safety chains
- Rubber rear guard

Your Gearmore Dealer



Rotorshaft, Knives and Cutter Bars



Adjustable Rear Deflector



Rear Roller w/External Bearings

SPECIFICATIONS:

MODEL #	MOWING WIDTH	OVERALL WIDTH	NO. OF KNIVES	MIN. HP REQUIRED	WEIGHT
GHF90	90"	98"	24	85 HP	2,670#
GHF100	100"	108"	26	95 HP	2,800#
GHF140	140"	148"	36	105 HP	3,530#

Specifications Subject To Change Without Notice

13477 Benson Ave. • Chino, CA 91710 • Ph: 909/548-4848 • Fax: 909/548-4747