



MOWER / SHREDDERS SLE SERIES

FEATURING "NO TOOLS" BLADE CHANGING SYSTEM



**CAT I
A. S. A. E.
QUICK
HITCH
COMPATIBLE**

OFFSET POSITION

The "SLE" series of Flail Mowers are the most versatile mower on the market today. Some of the unique features are: all models can quickly be separated from center mount to offset. Two types of blades are available; the Y shaped blades for weed and light bush, and the curved duckfoot blade for mowing grass. Best of all, the blades can be changed by hand, no tools necessary!

These flail mowers were designed to achieve fine shredding on cover crops, parks, golf courses, and pastures.



CENTER MOUNT

GEARMORE INC.

13477 Benson Ave. • Chino, CA 91710
Ph: 909/548-4848 • Fax: 909/548-4747

www.gearmore.com • sales@gearmore.com



MOWER / SHREDDERS

FEATURES:

- Cat. 1, A.S.A.E. quick hitch compatible
- 45 H.P. gearbox, 540 RPM
- Center mount with 9" offset to right
- Available with Y blades for light brush or ducksfoot blades for grass
- Designed for tractors that have 540 RPM PTO speed
- Low profile design for clearing obstruction
- Pivoting 3-point hitch back brace for added strength and to easily offset hitch
- Rotor speed - 2340 rpm with blade tip speed of 8984 feet per minute
- 3 Belt final drive with automatic belt tightening idler to provide maximum power to the blades
- Internal "saw tooth" cutter bar to reduce the size of the shredded material
- 5" Diameter adjustable rear roller
- Two adjustable parking stands to allow easy "hook-up" to quick hitch tractor
- Safety chain shielding in front and rubber rear deflector



Low Profile Design To Clear Obstructions



*Quick Change
Y Blade*



*Quick Change
"Ducksfoot" Blade*

Your Gearmore Dealer:

SPECIFICATIONS:

MODEL #	MOWING WIDTH	OVERALL WIDTH	OFFSET FROM CENTER OF TRACTOR	NO. OF KNIVES	MIN. HP REQUIRED	WT.
SLE-120	48"	54"	36"	24	20	415#
SLE-160	63"	69"	43.5"	30	28	525#
SLE-190	75"	81"	49.5"	36	35	620#

Specifications Subject To Change Without Notice

13477 Benson Ave. • Chino, CA 91710 • Ph: 909/548-4848 • Fax: 909/548-4747