

## MINIFORST CL MULCHERS

### HYDRAULIC DRIVEN SKID STEER MOUNT



These forestry mulchers are suitable for forest work as well as the most demanding applications in landscaping and maintaining areas in which prunings, stumps, and wood that must be eliminated. Mulchers have a heavy mounting receiver plate for Skid Steer/Trackloaders.

The powerful hydraulic system on the MINIFORST is compatible with tractors with flow rates of 20 to 45 gallons per minute. The powerful efficient hydraulic M-BOOST™ motor, delivers 40% more torque than standard motors.



Marketed by:



13477 Benson Ave. • Chino, CA 91710 Ph: 909/548-4848 • Fax: 909/548-4747

www.gearmore.com • sales@gearmore.com



# MINIFORST CL MULCHERS

### **FEATURES:**

- Mounted on standard Skid Steer mounting bracket
- Mulches wood up to 8 inches (20 cm)
- Operating speed up to 3 miles per hour (5km/h)
- Variable displacement hydraulic motor with relief valve
- Required hydraulic flow 20 to 45 gallons per minute
- Hydraulic pressure 2,175 to 5,000 PSI
- Fixed rotor hammers with dual tungsten carbide tipped tools
- Five rows of heat treated recutter bars for finer mulch
- Hydraulically operated front door when closed produces finer mulch
- "Patented" blade holder, wraps around rotor drum for added strength
- Hood made of S420 high tensile steel
- Adjustable safety guard frame to aid when cutting down trees and tractor protection
- Replaceable side skids for added depth control
- Belts for final drive
- Pressure gauge
- Rear safety chain protection
- Hydraulic hoses included


**Note:** These Mulchers are also available for Tractors 3-Point hitch mounted. PTO driven



Wrap Around Rotor Blade Holder & Tungsten Carbide Tips



Variable Displacement Motor for Standard/Hi Flow Machines (CTL/SSL)



#### SPECIFICATIONS:

MODEL#	WORKING WIDTH	OVERALL WIDTH	DEPTH	NUMBER OF BLADES	WT.
CL150	59"	71"	39"	30	2325#
CL175	69"	81"	39"	33	2515#
CL200	79"	91"	39"	36	2790#

Specifications Subject To Change Without Notice