



ROTARY TILLERS

"T" SERIES FOR 90 - 160 HP TRACTORS



*Model T305
Shown*

These **"T" Series** tillers were designed for high horsepower tractors to produce a finished seedbed in a single pass. For crops such as vegetables, timing is everything. The basic plow, disc, cultivator tilling operation requires too many passes, wasted fuel, and causes excessive compaction. At a depth of 10 inches, the saber tines produce a uniform mixture of loose, textured soil that holds moisture and reduces erosion. There is no better tool for preparation of seedbeds and incorporating crop residue. The heavy duty rear rollers are available as an option for all models.



*Optional roller cleans, fills and
rolls orchard floor*



FEATURES:

- Cat. 2, 3-point hitch
- 10" Approximate tilling depth
- 4 Speed gearbox - 2 speeds @ 540 RPM & 2 speeds @ 1000 RPM
- For tractors up to a maximum of 160 HP
- Strong, smooth running, all gear final drive
- Slip clutch driveshaft to protect tractor and tiller drive system
- Curved, saber style heat treated, long wearing tines
- 6 Tines mounted on each rotor plate for maximum tilling action
- Tines staggered in scroll design for easy soil penetration
- Gearbox supported by full length tubes for added support
- Torque tube frame to absorb shock loads
- Tiller is balanced to eliminate vibration
- Chain with spring tailboard adjustment
- Large, oil bath, long wearing rotor bearings
- Powder coated, baked-on paint to reduce corrosion
- Side mounted skids for depth control

REAR ROLLER FEATURES:

- ~ 18" Dia. x ¼" thick wall steel tubing roller with spring loaded mud scraper
- ~ Turnbuckle roller adjustment to obtain exact required compaction
- ~ Easy to bolt up to standard T tillers
- ~ Roller is 8" wider than side plates to eliminate ridges
- ~ Thick bolt-on plate between tiller and tailboard to contain soil

Your Gearmore Dealer



**180 HORSEPOWER - 4
SPEED GEARBOX**



**ALL GEAR FINAL DRIVE & HEAVY
DUTY DEPTH SKIDS**



**MASSIVE CATEGORY 2
3-POINT HITCH**

SPECIFICATIONS:

MODEL #	TILLING WIDTH	OVERALL WIDTH	NO. OF TINES	APPROX. H.P.	WEIGHT
T230-CT	90"	97"	54	90 to 100 HP	2140#
T280-CT	110"	117"	66	100 to 120 HP	2205#
T305-CT	120"	127"	72	120 to 160 HP	2275#
T355-CT	140"	147"	84	120 to 160 HP	2850#