

FLAIL SHREDDERS TR SERIES

FIXED CENTER OR OFFSETABLE MOUNT



Our TR Series shredders feature a 90 horsepower gearbox, center mount with offsetable position, special lockable open tailboard with optional deflector brackets for spreading out shredded material, and adjustable foldaway gauge wheels.

The shredders have heavy duty swing Y type blades for heavy grasses and light weeds.

These units are excellent to achieve fine shredding of row crop residue, pastures and other types of farm usage.





13477 Benson Ave. • Chino, CA 91710 Ph: 909/548-4848 • Fax: 909/548-4747

www.gearmore.com • sales@gearmore.com



FLAIL SHREDDERS

FEATURES:

- Cat. II, 3-point ASAE quick hitch
- Heavy duty 90 HP, 540 RPM gearbox with overrunning clutch
- Center mount and offsettable 13 inches to the right
- Shreds material up to 2 inches
- Heavy tubing A-frame
- Heavy, replaceable clevis type lower hitch brackets
- Available with heavy duty Y blades
- Computer balanced vibration free rotor
- Internal re-cutter bar to increase the shredding of material
- 4 V-belts final drive, 5 belts on 255 and 280
- Closed or lockable open tailboard
- Adjustable foldaway gauge wheels
- Tires are 7:00 x 12 6-ply, tubeless
- Adjustable side skids
- Metal front safety flaps
- Class 6 driveshaft

OPTIONS:

- Deflector brackets mounted on the underside of the tailboard
- ~ Rear roller in lieu of gauge wheels

CAUTION: When operating the shredder with tailboard open, people should not be within 300 feet of the machine.





Heavy Duty 90 H.P. Gearbox



Gauge Wheels in Operating Position



Heavy Duty Y Blades

SPECIFICATIONS:

MODEL#	MOWING WIDTH	OVERALL WIDTH	NO. OF Y BLADES	APPROX. HP REQ'D	WEIGHT
TR200	79"	85"	44	65 HP	1515#
TR225	88"	94"	48	70 HP	1675#
TR255	100"	106"	56	75 HP	1830#
TR280	110"	117"	60	80 HP	1990#

Specifications Subject To Change Without Notice