



## LOADERS



These quick attach **Loaders** are removable from the tractor in less than 5 minutes without the use of loose parking stands. The loaders are computer designed and come in sizes to fit most popular tractors. Rugged, dependable, yet economical is the key to success of our loaders.

### FEATURES:

- 80% of loader removed from tractor when detached
- Durability for most moving and lifting jobs
- Low profile design maximizes operators visibility
- Bucket level indicator insures that you are in the correct bucket position
- Oil lines are plated steel tubing with JIC fittings to help prevent oil leaks

### SPECIFICATIONS:

MODELS:	2406	2408	2409	2491	2410
Horsepower rating:	10 - 20	15 - 35	30 - 45	35 - 55	35 - 60
Lift capacity at full height:	745 lbs.	1050 lbs.	1750 lbs.	2450 lbs.	2600 lbs.
Breakout force:	1120 lbs.	2100 lbs.	3500 lbs.	4245 lbs.	4900 lbs.
Shipping wt. with attachment:	625#	798#	898#	1312#	1520#
Maximum lift height:	72"	98"	108"	108"	120"
Clearance w/attachment dumped:	57"	77"	88"	79"	92"
Reach at maximum height:	22"	21"	22"	31"	varies
Attachment rollback angle:	22°	18°	20°	22°	23°
Digging depth:	4"	4.5"	4"	5"	4"
Overall height in carry position:	47"	51"	56"	60"	63"
Raising time to full height - seconds:	3.4 sec.	4 sec.	5.2 sec.	5.8 sec.	6 sec.
Lowering time - seconds:	2.2 sec.	3 sec.	3.5 sec.	3.9 sec.	5 sec.
Attachment rollback time - seconds:	3 sec.	2.2 sec.	2.2 sec.	3.4 sec.	3 sec.
Hydraulic system flow - U.S. gal:	5 GPM	8 GPM	9 GPM	12 GPM	15 GPM
System pressure at rated flow:	2000 PSI	2000 PSI	2500 PSI	2500 PSI	2500 PSI

