

Horizontal Dusting When Access Rows Are Limited



**S420-HC
Shown**

These horizontal cannon dusters were developed for maximum swath distance when access tractor rows are limited. Two models are available; one for up to 50 and one up to 90 feet of dusting distance. Our cannon dusters combine simple design with quality craftsmanship. The all gear drive provides maximum performance with low maintenance. Sulfur, diatomaceous earth, and other dust products are accurately applied with easy to set application rates.



FEATURES:

Duster -

- Cat. I, 3-point hitch - 540 RPM P.T.O.
- 300 or 400 lb. capacity polyethylene hopper with cover
- Maximum wind velocity is 150 or 180 miles per hour
- Wrap-A-Round tubular steel frame isolates and supports the hopper
- All gear drive for low maintenance
- Mechanical agitator for even flow
- Lever rate control to adjust dust flow

Cannon -

- Powers the dust out up to 50 or 90 feet
- Heavy steel tubing body
- Adjustable upper cannon for height
- Lower fishtail nozzle for closer coverage

Option -

- ~ Hydraulic or electric cylinder to operate cannon position from the tractor seat.

SPECIFICATIONS:

MODEL	MAXIMUM DISTANCE	HOPPER CAPACITY	MAX. WIND VELOCITY	FAN DIAMETER	WT.
S420-HC	50 Feet	300 lbs.	150 M.P.H.	15 3/4"	300#
S530-HC	90 Feet	400 lbs.	180 M.P.H.	19 3/4"	380#