

**Designed For Heavy Duty Usage**



## HIGH PRODUCTION BASKET RAKES

GENERATION 2 Twinstar Basket Rakes are designed for growers committed to producing superior quality hay. Twinstar Rakes produce consistent uniform windrows with less dirt, rocks, and debris than traditional wheel and rotary rakes. Twinstar models 2027 and 2030 are equipped with 7 tine bars which makes fluffier windrows, allows for increased raking time and higher ground speed. They are designed with double slide tubes for added strength. The baskets are now powered by heavy duty motors as standard equipment. The main hydraulic hoses fold and unfold in the unique Twinstar "Hose Trac" system. This clean, trouble free system gives total hose protection when extending and closing the double extension beams. Gauge wheels front and rear are optional equipment.

### SPECIFICATIONS:

MODEL:	2024-G2	2027-G2	2030-G2
Maximum Raking Width:	Up to 24'	Up to 27'	Up to 30'
Transport Width:	11' - 3"	10' - 9"	10' - 9"
Transport Depth:	18'	20' - 2"	20' - 2"
Basket Sizes:	24" Diameter x 10 1/2' Long	30" Diameter x 10 1/2' Long	30" Diameter x 12' Long
Basket Reel Speed:	Maximum 90 RPM	Maximum 90 RPM	Maximum 90 RPM
Tine Bars:	5 Bars	7 Bars	7 Bars
Rubber Mounted Tines:	Std: 100 per basket - Option: 150	Std: 154 per basket - Option: 224	Std: 175 per basket - Option: 259
Operating Speed:	Up to 8 MPH	Up to 10 MPH	Up to 10 MPH
Hydraulic Requirements:	12 GPM @ 2000 PSI	12 GPM @ 2000 PSI	12 GPM @ 2000 PSI
Tire Size:	(4) ST205/75R15	(4) LT235/75R15	(4) LT235/75R15
Clevis Hitch:	Standard	Standard	Standard
Gauge Wheels:	Front and Rear - Optional	Front and Rear - Optional	Front and Rear - Optional
Ball Hitch 2 5/16":	Optional	Optional	Optional
Weight:	3500#	5100#	5600#