

**3 Sizes Available For Up To 25, 50, & 75 Horsepower Tractors**

CAT II  
A.S.A.E.  
QUICK  
HITCH  
COMPATIBLE



**GR100**

Great for cutting narrow trenches for irrigation pipe. The optional 12" furrower shovel digs a smooth trench for water flow.

**GR200**

This unit is recommended for breaking up compacted soil to increase root growth and yields.

**GR300**

Designed for heavier duty use, thus the ripper can be used for high horsepower tractors. Recommend when deep ripping is required.

## SPECIFICATIONS:

MODELS:	GR100	GR200	GR300
Horsepower Rating:	Up to 25	Up to 50	Up to 75
Frame Tube Size:	3" x 3"	4" x 4"	4" x 8"
Shank Length:	19"	23"	27"
Shank Size:	1" x 4"	1" x 6"	1" Parabolic
Hitch:	Cat. 1	Cat. 1	Cat. 2
Shear Bolt Protection:	Yes	Yes	Yes
Weight:	85#	130#	240#
Optional 12" Furrower:	Yes	No	No
Parking Stands:	No	No	Optional

**Narrow Widths For Vineyards And Berries - Wider Widths For General Farm Use**

## V-RIPPERS CAT. 1 - 30 TO 50 HP

The "V" design main beam and curved shanks reduce horsepower requirements. The deep ripping obtains excellent soil aeration, which allows greater water penetration and absorption. Also increases root growth and penetration. All this adds up to better crops and higher profits.

### FEATURES:

- Heavy 4" x 6" beam construction to insure long life
- 1" x 6" x 20" Shanks
- Shanks adjustable with shear bolt protection
- Replaceable high carbon, heat-treated points
- Parking stands that store in frame



### SPECIFICATIONS:

MODEL NO.	NO. OF SHANKS	BEAM WIDTH	WEIGHT
R3-50	3	50"	420#
R3-60	3	60"	435#
R5-60	5	60"	550#
R3-70	3	70"	450#
R5-70	5	70"	570#

## V-RIPPERS



The "V" design main beam and curved shanks reduce horsepower requirements. The deep ripping aids in excellent soil aeration, which allows greater water penetration and absorption. Ripping increases root growth and penetration. All this adds up to better crops and higher profits.

### FEATURES:

- "V" design & curved shanks reduce HP requirements
- Fixed and adjustable shanks available
- Shear bolt protection
- Replaceable high carbon, heat-treated points
- Parking stands that store in frame
- Optional gauge wheels for VR7F only

### SPECIFICATIONS:

MODEL NO.	NO. OF SHANKS	HITCH CATEGORY	SHANK SIZE	MAX. H.P.	SHANK SPACING	BEAM SIZE	WEIGHT
VR3F	3	II	1" x 27"	80 HP	Fixed 30"	4" x 6" x 70"	675#
VR3	3	II	1" x 27"	80 HP	Adjustable	4" x 6" x 84"	715#
VR5F	5	II & III	1 1/4" x 34"	140 HP	Fixed 20"	6" x 8" x 90"	1300#
VR7F	7	II & III	1 1/4" x 34"	195 HP	Fixed 20"	6" x 8" x 130"	1525#

**For Extreme Duty Sub Soiling**

## RIPPERS - GE SERIES



**MODEL No.  
GE36-24 SHOWN**

### FEATURES:

- ❑ Cat. III & IVN 3-point A.S.A.E. quick hitch
- ❑ Frame made of 6" x 8" x 3/8" structural tubing
- ❑ "L" style shanks are 1 1/2" thick x 36" long
- ❑ 1" Thick "plow steel" lower hitch brackets
- ❑ Double dual steel wheels, 8" wide x 30" dia. (Optional on 5 shank rippers)
- ❑ Chrome shin guards on shanks - replaceable
- ❑ Heavy duty chrome chisel points - replaceable
- ❑ 1 1/4" Grade 8 swing shank bolts
- ❑ 1 1/4" Grade 5 shear shank bolts

### OPTIONS:

- SW30 - Set of steel wheels for 5 shank ripper
- WW16 - Set of dual 11L x 16 rubber tires for 5 shank ripper
- WW16-7 - Set of dual 11L x 16 rubber tires in lieu of steel wheels for 7 shank ripper

### SPECIFICATIONS:

MODEL NO.	NO. OF SHANKS	SHANK SPACING	FRAME WIDTH	WEIGHT
GE536-24	5	24"	8 Feet	3600#
GE536-30	5	30"	10 Feet	3820#
GE736-24	7	24"	12 Feet	4920#
GE736-30	7	30"	15 Feet	5050#

## CRUMBLER ATTACHMENT GTC SERIES

### FEATURES:

- ❑ Available in widths of 14, 15, 16, & 17 feet
- ❑ 5 Spiral crumbler paddles - 5/8" x 6"
- ❑ 8" Diameter center tubing
- ❑ 2 7/16" Ball bearings
- ❑ 2 7/16" Full length shaft
- ❑ Autolift no-shock arms
- ❑ 5" x 5" x 3/8" tubing main frame beam
- ❑ Mounting brackets are included
- ❑ Drop "S" from model no. for 7 straight paddles crumbler



### SPECIFICATIONS:

MODEL NO.	DESCRIPTION	WIDTH	WT.
GTC-168-S	Crumbler Only	14 Foot	2600#
GTC-175-S	Crumbler Only	15 Foot	2760#
GTC-192-S	Crumbler Only	16 Foot	2920#
GTC-204-S	Crumbler Only	17 Foot	3080#

## Deep And Shallow Ripping Tools

### HEAVY DUTY "V" RIPPERS - RS SERIES

#### FEATURES:

- ❑ V frame is constructed with 6" x 8" x 3/8" tubing
- ❑ Standard curved design shanks - 1 1/4" x 31" long
- ❑ Shanks also available 1 1/4" x 34" in standard and parabolic design
- ❑ Chrome shin guards and points
- ❑ Shank pockets are available as fixed or adjustable
- ❑ Horsepower required is 25 HP per shank
- ❑ Gauge wheels available as single or dual - 9.5L x 15
- ❑ Cat. II or III, 3-point hitch (please specify)



7 SHANK WITH OPTIONAL SINGLE GAUGE WHEELS & PARABOLIC SHANKS SHOWN

The "V" design of the shanks are available in standard curved or parabolic style. Both types of shanks obtain excellent soil aeration, which gives maximum soil aeration, which allows greater water penetration and absorption. The rippers are very effective for first pass soil preparation for easier discing and other finish tilling implements.

#### SPECIFICATIONS:

MODEL NO.	DESCRIPTION	WIDTH	WT.
RS-30HD	3 Shank V Ripper	5' - 3"	1200#
RS-50HD	5 Shank V Ripper	8' - 2"	2200#
RS-70HD	7 Shank V Ripper	13' - 8"	2800#
RS-90HD	9 Shank V Ripper	15' - 6"	3500#

### RIPPING CHISELS - GRC SERIES



21' MODEL SHOWN WITH SINGLE GAUGE WHEELS AND OPTIONAL REAR HITCH AND POINTS

#### FEATURES:

- ❑ Cat. III & IV narrow, 3-pt. quick hitch compatible
- ❑ Frame 5" x 5" x 3/8" wall steel tube
- ❑ 3 Shank beams on 36" center
- ❑ Beam cross braces 2" x 4" x 1/4" wall
- ❑ 4 Tubing braces to support top mast
- ❑ 1 1/4" x 30" Long rigid plow steel shanks w/shear bolt protection

Our 3 bar finishing Ripper Chisel is an effective implement for loosening soil up to 15 inches deep. The rigid shank design insures consistent depth. The narrow 12" shank spacing is excellent for breaking up and incorporating of residue. These ripping chisels are the perfect tool for opening up heavy soils for aeration. The shear bolt shanks allow for higher speeds than most tillage implements.

- ❑ Welded plow steel shank pockets
- ❑ Shanks are on 12" centers
- ❑ Single gauge wheels - 9.5L x 15

#### OPTIONS:

- ❑ 3/4" x 15" Reversible spike points
- ❑ Rear clevis hitch
- ❑ Dual gauge wheels (in lieu of single)

#### SPECIFICATIONS:

MODEL NO.	WIDTH	DESCRIPTION	NO. OF SHANKS	WEIGHT
GRC-15	15 ft.	Ripper Complete	15	4450#
GRC-17	17 ft.	Ripper Complete	17	4750#
GRC-19	19 ft.	Ripper Complete	19	5050#
GRC-21	21 ft.	Ripper Complete	21	5350#

Other Widths Available Upon Request