



SINGLE SHANK RIPPERS

GR100, GR200, & GR300

PRECISION YOU CAN COUNT ON.

The GR100 is for tractors up to 25 H.P. These Rippers are great for cutting narrow trenches for irrigation pipe. The optional 15" furrower shovel digs a smooth trench for water flow. The GR200 is for tractors up to 50 H.P. This unit is recommended for breaking up compacted soil to increase root growth and yields. The GR300 is for tractors up to 75 H.P. and was designed for heavier duty use. Thus, the ripper can be used for high horsepower tractors. This ripper is recommended when deep ripping required.

GR100 FEATURES

- 3" x 3" x 3/8" tube frame
- 1" x 4" shank
- 2 position shank length, 15" & 19"
- Shear bolt protection
- 2" wide hard faced point
- Optional - 15" furrowing shovel for building beds

SPECIFICATIONS

| Model # | H.P. Rating | Frame Tube Size | Shank Length | Shank Size | Hitch | Shear Bolt Protection | Optional 12" Furrower | Parking Stands | Weight |
|---------|-------------|-----------------|--------------|------------|---------|-----------------------|-----------------------|----------------|----------|
| GR100 | Up to 25 | 3" x 3" | 19" | 1" x 4" | Cat. I | Yes | Yes | No | 85 lbs. |
| GR200* | Up to 50 | 4" x 4" | 22" | 1" x 6" | Cat. I | Yes | No | Standard | 100 lbs. |
| GR300* | Up to 75 | 4" x 8" | 27" | 1 x 10" | Cat. II | Yes | No | Standard | 240 lbs. |

* Also available with hard faced shanks and points.



GR200 FEATURES

- 4" x 4" x 3/8" tube frame
- 1" x 6" curved shank 20" long
- Replaceable point
- Shear bolt protection
- Optional - hardfaced shank & point

GR300 FEATURES

- 4" x 8" x 3/8" tube frame
- 1" x 6" curved shank 24" long
- Shear bolt protection
- Replaceable point
- Optional - hardfaced shank & point