

DISCOVER MORE OF OUR PRODUCTS HERE→



## SINGLE SHANK RIPPERS

GR100, GR200, & GR300

## PRECISION YOU CAN COUNT ON.

The GR100 is for tractors up to 25 H.P. These Rippers are great for cutting narrow trenches for irrigation pipe. The optional 15" furrower shovel digs a smooth trench for water flow. The GR200 is for tractors up to 50 H.P. This unit is recommended for breaking up compacted soil to increase root growth and yields. The GR300 is for tractors up to 75 H.P. and was designed for heavier duty use. Thus, the ripper can be used for high horsepower tractors. This riper is recommended when deep ripping required.



- 3" x 3" x ¾<sub>6</sub>" tube frame
- 1" x 4" shank
- 2 position shank length, 15" & 19"
- Shear bolt protection
- 2" wide hard faced point
- Optional 15" furrowing shovel for building beds





## **GR200 FEATURES**

- 4" x 4" x ¾" tube frame
- 1" x 6" curved shank 20" long
- Replaceable point
- Shear bolt protection
- Optional hardfaced shank & point

## **GR300 FEATURES**

- 4" x 8" x ¾" tube frame
- 1" x 6" curved shank 24" long
- Shear bolt protection
- Replaceable point
- Optional hardfaced shank & point

Model #	H.P. Rating	Frame Tube Size	Shank Length	Shank Size	Hitch	Shear Bolt Protection	Optional 12" Furrower	Parking Stands	Weight
GR100	Up to 25	3" x 3"	19"	1" x 4"	Cat. I	Yes	Yes	No	85 lbs.
GR200*	Up to 50	4" x 4"	22"	1" x 6"	Cat. I	Yes	No	Standard	100 lbs.
GR300*	Up to 75	4" x 8"	27"	1 x 10"	Cat. II	Yes	No	Standard	240 lbs.

\* Also available with hard faced shanks and points.

