



Explore more of our products by clicking or scanning here!→

# V-RIPPERS

FOR TRACTORS FROM 40 TO 195 HORSEPOWER

## REVOLUTIONIZE YOUR SOIL WITH CUTTING-EDGE DEEP RIPPING.

The "V" design main beam curved shanks reduce horsepower requirements. The deep ripping obtains excellent soil aeration, which allows greater water penetration and absorption. Also increases root growth and penetration. All this adds up to better crops and higher profits.



### FEATURES

- Cat. I, ASAE quick hitch
- Heavy 4" x 6" beam construction to insure long life
- 1" x 6" x 20" shanks
- Shanks adjustable with shear bolt protection
- Replaceable high carbon, heat-treated points
- Parking stands that store in frame

### SPECIFICATIONS

Model #:	R3-50	R3-50	R5-60	R3-70	R5-70
No. of shanks	3	3	5	3	5
Beam Width:	50"	60"	60"	70"	70"
Weight:	420 lbs.	435 lbs.	550 lbs.	450 lbs.	570 lbs.

### FEATURES

- "V" design & curved shanks reduce H.P. requirements
- Fixed and adjustable shanks available
- Shear bolt protection
- Replaceable high carbon, heat-treated points
- Parking stands that store in frame
- Optional gauge wheels for VR7F only



### SPECIFICATIONS

Model #	No. of Shanks	Hitch Category	Shank Size	Max. H.P.	Shank Spacing	Beam Size	Weight
VR3F	3	Cat. II	1" x 27"	80	Fixed 30"	4" x 6" x 70"	675 lbs.
VR3	3	Cat. II	1" x 27"	80	Adjustable	4" x 6" x 84"	715 lbs.
VR5F	5	Cat. II & III	1 1/4" x 34"	140	Fixed 20"	6" x 8" x 90"	1,300 lbs.
VR7F	7	Cat. II & III	1 1/4" x 34"	195	Fixed 20"	6" x 8" x 130"	1,525 lbs.



FORM #BL0019-26

13477 Benson Ave. Chino, CA 91710 | 909/548-4848 | sales@gearmore.com