




DISCOVER MORE OF OUR PRODUCTS HERE→



RIPPERS

WITH 2 SHANKS

ELIMINATE HARDPAN, BOOST YOUR VINEYARD'S GROWTH.

Tractors have to make any passes through vineyards and orchards. This creates hard pan under the tractor tires. From time to time, it is recommended to rip that area to aerate the soil for better water penetration to increase root growth. The spread width of the ripping shanks can be set to the tractor tire centers and this then shatters the soil over the compacted area up to 18" deep. These rippers have two 4" x 6" beams for added strength. Models available for all popular vineyard row spacings.



FEATURES

- Cat. I & II, 3-point, ASAE quick hitch
- Two adjustable shanks for ripping soil up to 18" deep
- Adjustable bolt-on shank brackets so they can be set for different tractor tire tread widths
- Shear bolt design so shanks can swing up if hitting obstructions
- Shanks are made of 1" thick by 6 1/2" wide by 22" long steel
- Main beam 4" x 6" x 1/4" wall tubing
- Replaceable high carbon, heat treated points
- Clevis type hitch bracket
- Parking stand

OPTION

- Hard faced shanks & points

SPECIFICATIONS

Model #	Description	For Row Widths	Beam Width	Adj. Shank Centers	Weight
R2-55	3-pt. Ripper	6' (72")	55"	38" to 48"	320 lbs.
R2-67	3-pt. Ripper	7' (84")	67"	40" to 60"	350 lbs.
R2-72	3-pt. Ripper	8' (96")	72"	48" to 66"	360 lbs.
R2-96	3-pt. Ripper	10' (120")	96"	60" to 90"	390 lbs.



FORM #BL0026-25

13477 Benson Ave. Chino, CA 91710 | 909/548-4848 | sales@gearmore.com