

BWImplement

Explore more of our products by clicking or scanning here!→



# OFFSET DISCS 500 SERIES

**CUTTING WIDTHS OF 6' - 9" TO 12'** 

TACKLE THE TOUGHEST
SOIL WITH
GEARMORE
LOW PROFILE
OFFSET DISCS.

The Gearmore Low
Profile Offset Discs are of
rugged design for deep tilling
in all soil conditions. We offer the most popular
widths of 6' - 9" to 12'. The offset design
enables maximum penetration and even tillage

in all soil conditions. We offer the most popular widths of 6' - 9" to 12'. The offset design enables maximum penetration and even tillage of soil. Heavy construction with 1 ½" square gang axles, 24" diameter blades in notched or smooth, self-leveling hand crank and trunnion mounted sealed bearings. These offset discs are excellent for all types of discing operations. The narrow discs are especially effective for knocking down irrigation borders. Built in the West for tough, western conditions.



## **OFFSET DISCS 500 SERIES**

#### **FEATURES**

- Heavy tubing on frame and gangs
- Self-leveling spring hitch cushioned with hand crank
- 1½" square gang axles with greaseable trunnion mounted double seslaed brearing with bearing wear guards
- Gang angles are adjustable from 24 to 48 degrees
- 24" diameter x 6mm notched front and plain rear blades on 9" spacing
- Scrapers, adjustable individually or by gangs
- 6 bolt hub and spindle assembly, 9.5L x 15" 8-ply tires
- 3 ½" x 8" depth control cylinder with hoses

#### **OPTIONS**

- W extra heavy duty frames for extreme usuage like weed abatement
- RPH Rear Pull Hitch
- FF14 Furrow Filler with 20" diameter blades (pair)







tubing and bearing hangers

### **SPECIFICATIONS**

Model #	Width	No. of Blades	Frame	No. of Wheels	Tractor HP Req'd	Wt. Per Foot	Weight
G501	6' - 9"	18	4" x 4" x ¼"	2	40 to 65	325 lbs.	2,430 lbs.
G502	7' - 6"	20	4" x 4" x ¼"	2	45 to 70	330 lbs.	2,600 lbs.
G503	8' - 3"	22	4" x 4" x ¼"	2	50 to 80	335 lbs.	2,800 lbs.
G504	9' - 0"	24	4" x 4" x ¼"	2	55 to 85	345 lbs.	3,100 lbs.
G505	9' - 9"	26	4" x 4" x ¼"	2	60 to 90	370 lbs.	3,600 lbs.
G506	10' - 6"	28	4" x 4" x ¼"	4	65 to 100	390 lbs.	4,100 lbs.
G507	12'	32	4" x 4" x ¼"	4	75 to 120	400 lbs.	4,800 lbs.

