

Explore more of our products by clicking or scanning here!→

# OFFSET DISCS

"300" SERIES

## DELIVERS DURABLE PERFORMANCE.

The Gearmore 300 Series Offset Discs are ideal for light and medium tillage conditions. We offer sizes from 4'-6" to 9'-9"; for vineyards, berries, narrow row orchards, general field cultivation, etc. The offset design enables maximum penetration and even tillage of soil. Heavy construction with 22 inch diameter blades in notched or smooth, self leveling hand crank, and triple sealed bearings. Built in the West for tough, western conditions.





# OFFSET DISCS

## FEATURES

- Frames: heavy 4" x 3" x 1/4" wall tubing on frame and gangs
- Hitch: self leveling spring cushioned with hand crank
- Gangs & Bearings: 1 1/2" square gang axles with flange mount, triple sealed bearings
- Gang angles: adjustable from 24 to 48 degrees
- Blades: 22" diameter x 4.5 mm notched front and plain rear blades on 9" centers
- Wheels & Tires: 5 bolt hub and spindle assy. with 2ea 6.7 x 15 4-ply implement tires
- Hydraulics: 3 1/2" x 8" depth control cylinder with hoses

## OPTION


- Mud Scrapers - adjustable individually or by gangs

## SPECIFICATIONS

Model #	Width	No. of Blades	Tractor H.P. Required	Weight
G301	4' - 6"	12	35 - 40	1,300 lbs.
G302	5' - 3"	14	40 - 45	1,400 lbs.
G303	6' - 0"	16	45 - 50	1,500 lbs.
G304	6' - 9"	18	50 - 55	1,600 lbs.
G305	7' - 6"	20	55 - 60	1,700 lbs.
G306	8' - 3"	22	60 - 65	1,800 lbs.
G307	9' - 0"	24	65 - 70	1,900 lbs.
G308	9' - 9"	26	70 - 75	2,000 lbs.



Replaceable nylon bearings on wheel mounts



Heavy gang hanger with flange mounted triple sealed bearings



Self leveling spring cushioned with hand crank



FORM #BW0002-25

13477 Benson Ave. Chino, CA 91710 | 909/548-4848 | sales@gearmore.com