



Built By:
BWImplement

Explore more of our products by clicking or scanning here!→

TANDEM

"GT" SERIES - HEAVY DUTY - PULL TYPE

TACKLE TOUGH TERRAIN WITH EASE.

FEATURES

- 4" x 4" x ¼" structural tubing frames
- Self-leveling, spring cushioned hitch with hand crank
- 1 ½" square gang axles with greaseable trunnion mounted, double sealed bearings with wear guards
- Front gangs are adjustable 12 to 22 degrees
- Rear gangs are adjustable 9 to 21 degrees
- 24" diameter x 6 mm notched front and plain rear blades on 9" spacing
- Scrapers are standard, adjustable individually or by gang
- 2 wheels - 6 bolt hub and spindle assembly
- 2 - 9.5L x 15" 8-ply tires
- 3 ½" x 8" cylinder with depth control and hoses
- Rear hitch is standard equipment



1 ½" triple sealed bearing in cast trunnion mount housing



Self-leveling, spring cushioned hitch with hand crank

OPTIONS

- Pair of extensions 24" x 6 mm blades
- Pair of furrow filler w/20" blades

SPECIFICATIONS

Model #	No. of Blades	No. of Wheels	Cutting Width	Weight
GT-24T	24	2	9' - 2"	3,300 lbs.
GT-28T	28	2	10' - 6"	3,700 lbs.
GT-32T	32	4	12' - 0"	4,140 lbs.
GT-36T	36	4	13' - 8"	4,360 lbs.



FORM #BW0007-25

13477 Benson Ave. Chino, CA 91710 | 909/548-4848 | sales@gearmore.com