



**SUPERIOR SPREADING,
GUARANTEED.**



VIEW CATALOG

Explore more of our products by clicking or scanning here!→

SPINNER SPREADERS

SINGLE SPINNER

Our high capacity 3-point Spreader features a stainless steel spinner disc with 6 stainless steel vanes. Spreaders have a heavy duty stamped and ribbed frame. All metal hopper and frames have special phosphated undercoat, then epoxy powder painted and baked at 300 degrees to insure long life. The spreader can be set at 180°, 90° right or 90° left spreading pattern.



FEATURES

- Cat. II, 3-point hitch
- Low loading height
- Sturdy stamped and ribbed steel frame
- Levers control on and off
- 6 fins spreading disc for even spreading width
- Spreading width from 32' to 59'

SPECIFICATIONS

Model #	Capacity		Height	Width	Depth	Weight
	Lbs.	Cu. Ft.				
RT-800	1,700	28	40"	59"	53"	345 lbs.

DOUBLE SPINNER

Our two 3-point Spreaders feature dual stainless steel spinner discs, which are extremely accurate with only 6.7% variance across the spread pattern. The spreaders are supplied with manual lever controls with optional hydraulic controls when the tractor has a cab. The new 41" width model is for narrow row vineyards and other narrow row crops.



FEATURES

- Cat. I & II, 3-point hitch
- Hydraulic cylinder controls, off and on
- Stainless steel construction
- Two stainless steel discs with 3 vanes each
- Spreading width from 30 to 50 feet
- Easy on and off band spread attachment for exact material placement
- Two row band spreader attachment - 66" wide

SPECIFICATIONS

Model #	Capacity		Height	Width	Depth	Weight
	Lbs.	Cu. Ft.				
RE-F600	1,210	19	42"	41"	51"	375 lbs.
RE-1000	2,200	35	45"	59"	51"	450 lbs.



FORM #CO0007-26

13477 Benson Ave. Chino, CA 91710 | 909/548-4848 | sales@gearmore.com