




DISCOVER MORE OF OUR PRODUCTS HERE→



GRADING SCRAPERS

"INDUSTRIAL" SERIES

ONE TOOL, ENDLESS POSSIBILITIES.

The Gearmore Industrial Grading Scrapers, are engineered for both tractor 3-point hitch and skid steer/track loader mount applications. Ideal for road maintenance and repair, these scrapers feature a dual blade flow-through action that effortlessly cuts high spots, fills in holes, and redistributes material from the edges toward the center of the road, ensuring a smooth, finished surface. Additionally, their versatility shines through in general landscaping tasks—operating at reduced speeds allows users to carry ample soil in front of the blades, which can easily be deposited into low spots by lifting the hitch or loader. Perfect for spreading and leveling gravel, topsoil, and more, the Gearmore Grading Scraper is user-friendly and requires minimal time to master. Transform your road maintenance and landscaping projects with our scraper's robust design and unparalleled efficiency.

A. S. A. E.
QUICK
HITCH
COMPATIBLE



8' unit shown



7' skid steer unit shown



GRADING SCRAPERS

FEATURES

- 3-point hitch and skid steer mount quick hitch compatibility
- For tractors up to 100 horsepower
- Heavy 5" x 5" steel tubing with ¼" wall main front beam
- 3" x 3" steel tubing rear support beam
- Strong clevis type hitch points
- Top mast made of ⅝" plate
- Two ½" x 6" heat treated reversible beveled cutting edges
- Easy to adjust cutting edges with settings of 0 to 1 ½" below side panels (preset at ½")
- Front cutting blade is designed to adjust lower than the rear blade to compensate for additional wear
- 20" spacing between cutting edges to produce maximum mixing action when re-building gravel roads
- ¼" x 18" x 60" formed side panels capture and retain material
- ⅜" x 2 ½" replaceable skid plates on side panels
- No moving parts to maintain
- 10 & 12 foot units have three support braces from main beam/top mast to rear support beam



Cutting edge depth adjustment



Heavy hitch



Replaceable skid plate

SPECIFICATIONS

Model #	Hitch Type	Cutting Width	Overall Width	Minimum H.P.	Weight
GSI7-SS	Skid Steer	84"	89"	45	820 lbs.
GSI7	Cat. I & II	84"	89"	45	830 lbs.
GSI8	Cat. II	96"	101"	50	860 lbs.
GSI10	Cat. II	120"	125"	70	1,020 lbs.
GSI12	Cat. II	144"	149"	80	1,140 lbs.



FORM #EN0020-25

13477 Benson Ave. Chino, CA 91710 | 909/548-4848 | sales@gearmore.com