



Explore more of our products by clicking or scanning here!→



# ROTARY MOWERS

## "FH" SERIES

## MOW SMARTER, NOT HARDER.

Our Flex Hitch Series Mowers feature a Patent Pending "Flex Hitch" that allows the mower to roll up to 15° front-to-rear and side-to-side, providing exceptional flexibility and ground following. The floating hitch smoothly follows the contours of uneven terrain, helping maintain consistent cutting performance while reducing stress on both the mower and tractor.

Cat. I  
A.S.A.E.  
Quick Hitch  
Compatible

60" w/standard  
chain shielding shown



## FEATURES

- Sloped, domed deck sheds water & debris
- No stitch welds, all fully welded seams
- Heavy round dished spindle pan for gearbox protection
- Two full length rails for deck support
- Slip clutch drive shafts to prevent damage
- Safety chains front & rear

|               |             |
|---------------|-------------|
| Side Rails:   | 6" I Beams  |
| Top Deck:     | 11 Gauge    |
| Hitch:        | Cat. I      |
| Gearbox RPM:  | 540         |
| Tailwheel:    | Laminated   |
| Blade Holder: | Spindle Pan |
| Blade Size:   | ½" x 3"     |
| Driveshaft:   | Slip Clutch |

## SPECIFICATIONS

| Model #    | Cutting Width | Overall Width | Overall Length | Blade Tip Speed | Weight   |
|------------|---------------|---------------|----------------|-----------------|----------|
| L-48-40-FH | 48"           | 51"           | 82"            | 11,500          | 430 lbs. |
| L-60-40-FH | 60"           | 63"           | 95"            | 12,500          | 535 lbs. |
| L-72-40-FH | 72"           | 75"           | 107"           | 15,000          | 710 lbs. |



FORM #KK0012-26

13477 Benson Ave. Chino, CA 91710 | 909/548-4848 | sales@gearmore.com