



Explore more of our products by clicking or scanning here!→



ROTARY TILLERS

"E" SERIES

UNLOCK THE POTENTIAL OF YOUR LAND.

Agricultural & Horticultural

Ideal for preparation of seedbeds, renovation of pastures, orchards, vineyards and mulching-in cover crops and stubble. Provides uniform mixture throughout cultivated depth.

Produces loose textured soil that holds moisture, reduces erosion.

Light Industrial

Clears and cleans up land. Eliminates fire hazards by tilling in dried grass. Mixes and blends soils and aggregates for soil stabilization in roads, driveways, parking areas, sidewalks and pathways. Rental yards match it up with compact tractor for big profits. Perfect for land preparation prior to landscaping.





ROTARY TILLERS

FEATURES

- Connects to 3-point, Cat. I 540 R.P.M. tractors
- Available in forward and reverse rotation
- All gear, final drive
- Rugged construction for long life
- Strong, balanced rotorshaft
- Large bearings with protective seals
- Oversize shafts and gears
- Heat treated, long wearing tines
- 6 - L shaped tines per flange
- Well balanced to eliminate vibration
- Adjustable skids for depth control
- Tailboard with chain adjustments
- Torque tube frame to absorb shock loads
- Driveshaft with slip clutch
- 50 H.P. gearbox on E48, 60 & 72
- E84 can be operated on tractors up to 70 H.P. and is Cat. I & II
- Front rubber guard on reverse rotation models

SPECIFICATIONS

Model #	Tilling Width	Overall Width	No. of Tines	Approx. H.P.	Weight
E48	48"	53"	36	20 to 35	600 lbs.
E60	60"	65"	42	25 to 40	690 lbs.
E72	72"	77"	54	35 to 50	780 lbs.
E84	84"	89"	66	50 to 65	805 lbs.
E60R Rev. Rotation	60"	65"	42	40 to 45	710 lbs.
E72R Rev. Rotation	72"	77"	54	45 to 50	800 lbs.



Produces loose textured soil



Gear driven, final drive



Reverse rotation models bury clods & debris



FORM #KK0014-26

13477 Benson Ave. Chino, CA 91710 | 909/548-4848 | sales@gearmore.com