



DISCOVER MORE OF OUR PRODUCTS HERE→



ROTARY MOWER

DESIGNED FOR COMPACT TRACTORS TO OBTAIN MAXIMUM STABILITY

POWER AND RELIABILITY, BUILT INTO ONE.

Our Rotary Mowers were developed to obtain maximum strength and stability. The strength was obtained by using the same gearbox, spindle assembly, blades and driveshaft that are used on our standard mowers. The stability was obtained by mounting the mower closer to the tractor and the addition of twin rubber tailwheels. This combination of strength and stability allows the operator to mow in rough terrain with maximum control off the tractor and mower. We recommend this rotary mower for tractors under 35 horsepower.





ROTARY MOWER

FEATURES

- Cat. I, 3-point hitch
- Available in mowing width of 48"
- Heavy duty 40 H.P. gearbox
- Bolt-on replaceable side plates
- Floating hitch design follows the contour of the terrain
- External front to rear ribbing for added strength
- Adjustable dual pneumatic rubber tailwheels for added stability
- Adjustable cutting heights from 1 to 6 inches
- Heat treated ½" thick x 3" wide blades
- Shear pin protected driveshaft
- Heavy round dished spindle pan
- Front rubber safety shielding is standard equipment
- Standard color yellow - also available in tractor colors



Dual tailwheels



Spindle pan



Floating hitch

SPECIFICATIONS

Model #	Cutting Width	Overall Width	Overall Depth	Weight
L-48-40-XB	48"	51"	62"	400 lbs.



FORM #KK0016-25

13477 Benson Ave. Chino, CA 91710 | 909/548-4848 | sales@gearmore.com