

DISCOVER MORE OF OUR PRODUCTS HERE->



MINIFORST CL MULCHERS

HYDRAULIC DRIVEN SKID STEER MOUNT

BUILT TO TACKLE FOREST WORK AND THE MOST DEMANDING LANDSCAPING AND AREA-MAINTENANCE TASKS.

These forestry mulchers are suitable for forest work as well as the most demanding applications in landscaping and maintaining areas in which prunings, stumps, and wood that must be eliminated. Mulchers have a heavy mounting receiver plate for Skid Steer/Trackloaders. The powerful hydraulic system on the MINIFORST is compatible with tractors with flow rates of 20 to 45 gallons per minute. The powerful efficient hydraulic M-BOOST™ motor, delivers 40% more torque than standard motors.







MINIFORST CL MULCHERS

FEATURES

- Mounted on standard skid steer mounting bracket
- Mulches wood up to 8 inches (20 cm)
- Operating speed up to 3 miles per hour (5km/h)
- Variable displacement hydraulic motor with relief valve
- Required hydraulic flow 20 to 45 gallons per minute
- Hydraulic pressure 2,175 to 5,000 PSI
- Fixed rotor hammers with dual tungsten carbide tipped tools
- Five rows of heat treated recutter bars for finer mulch
- Hydraulically operated front door when closed produces finer mulch
- "Patented" blade holder, wraps around rotor dump for added strength
- Hood made of S420 high tinsel steel
- Adjustable safety guard frame to aid when cutting down trees and tractor protection
- Replaceable side skids for added depth control
- Belts for final drive
- Pressure gauge
- Rear safety chain protection
- Hydraulic hoses included

OPTIONS

- Cutting blades with built-in depth plates to limit cuts of approximately one inch, excellent for shredding standing trees
- Less hood



Wrap around rotor blade holder & tungsten carbide tips



Cutting blades are excellent for shredding standing trees



Mulcher shredding brush piles

SPECIFICATIONS

Model #	Working Width	Overall Width	Depth	Number of Blades	Weight
CL150	59"	71"	39"	30	2,325 lbs.
CL175	69"	81"	39"	33	2,515 lbs.
CL200	79"	91"	39"	36	2,790 lbs.

Note: These mulchers are also available for tractor 3-point hitch mounted, PTO driven. Impact resistant windshield required.

