Explore more of our products by clicking or scanning here!→

VIEW CATALOG

ROTARY TILLERS


"B' SERIES

CAT I & II
A. S. A. E.
QUICK
HITCH
COMPATIBLE

UPGRADE YOUR FIELDWORK WITH A TILLER THAT COMBINES POWER AND EFFICIENCY.



These medium duty tillers feature a smooth running, all gear drive system. Powered through a heavy 70 horsepower gearbox to an all gear final drive. The tilling action provides a uniform mixture throughout the cultivated depth. Producing loose textured soil that holds moisture and reduces erosion. These are the ideal tillers for farm, vineyard, orchards, landscapers, nurseries, etc.




ROTARY TILLERS

FEATURES

- Cat. I, 3-point hitch
- ASAE quick hitch compatibility for easy hook up
- 7" approximate tilling depth
- One speed gearbox, 540 R.P.M.
- For tractors up to maximum of 50 horsepower
- 82 lb. heavy duty roller chain
- Slip clutch driveshaft to protect tractor and tiller drive system
- Curved, saber style heat treated, long wearing tines
- 6 tines mounted on each rotor plate for maximum tilling action
- Tines staggered in scroll design for easy solid penetration
- Adjustable clevis style lower hitch brackets
- Torque tube frame to absorb shock loads
- Tiller is balanced to eliminate vibration
- Chain with spring tailboard adjustment
- Large, greaseable, long wearing rotor bearings
- Powder coated, baked-on paint to reduce corrosion
- Side mounted skids for depth control
- Plated retractable parking stand



Adjustable clevis lower hitch brackets



Slip clutch driveshaft



Adjustable depth control side skids & parking stand

SPECIFICATIONS

Model #	Tilling Width	Overall Width	No. of Tines	Approx. H.P.	Weight
B100	40"	44"	30	20	300 lbs.
B120	48"	52"	36	25	335 lbs.

13477 Benson Ave. Chino, CA 91710 | 909/548-4848 | sales@gearmore.com