Explore more of our products by clicking or scanning here!→

VIEW CATALOG

ROTARY TILLERS

"T" SERIES

UPGRADE YOUR FIELDWORK WITH A TILLER THAT COMBINES POWER AND EFFICIENCY.



These "T" Series Tillers were designed for high horsepower tractors to produce a finished seedbed in a single pass. For crops such as vegetables, timing is everything. The basic plow, disc, cultivator tilling operation requires too many passes, wasted fuel, and causes excessive compaction. At a depth of 10 inches, the saber tines produce a uniform mixture of loose, textured soil that holds moisture and reduces erosion. Now featuring a heavy duty cast iron final drive cover, which greatly strengthens the whole side transmission. There is no better tool for preparation of seedbeds and incorporating crop residue. The heavy duty rear rollers are available as an option for all models.



Optional roller cleans, fills and rolls orchard floor

ROTARY TILLERS

FEATURES

- Cat. II, 3-point hitch
- 10" approximate tilling depth
- 4 speed gearbox - 2 speeds @ 540 R.P.M. & 2 speeds @ 1,000 R.P.M.
- For tractors up to a maximum of 160 H.P.
- Cast iron cover for the strong smooth running all gear final drive
- Slip clutch driveshaft to protect tractor and tiller drive system
- Curved, saber style heat treated, long wearing tines
- 6 tines mounted on each rotor plate for maximum tilling action
- Tines staggered in scroll design for easy soil penetration
- Gearbox supported by full length tubes for added support
- Torque tube frame to absorb vibration
- Tiller is balanced to eliminate vibration
- Chain with spring tailboard adjustment
- Large, oil bath, long wearing rotor bearings
- Powder coaster, baked-on paint to reduce corrosion
- Side mounted skids for depth control



160 horsepower - 4 speed gearbox



Cast iron cover - strengthens the side transmission



Massive category II, 3-point hitch

SPECIAL TINES FEATURES



- Super alloy tungsten carbide tines
- Bonded coating is placed exactly on the areas of normal tine wear
- The "Rockwell" harness of 70, which is the maximum hardness for tine wear.

SPECIFICATIONS

Model #	Tilling Width	Overall Width	No. of Tines	Approx. H.P.	Weight
T230-CT	7' - 6" (90")	8' - 1" (97")	54	90 to 100	2,140 lbs.
T280-CT	9' - 2" (110")	9' - 9" (117")	66	100 to 120	2,205 lbs.
T305-CT	10' (120")	10' - 7" (127")	72	110 to 160	2,275 lbs.
T355-CT	11' - 8" (140")	12' - 3" (147")	84	120 to 160	2,415 lbs.

13477 Benson Ave. Chino, CA 91710 | 909/548-4848 | sales@gearmore.com