Explore more of our products by clicking or scanning here!→

VIEW CATALOG

ROTARY TILLERS

"C" SERIES

UPGRADE YOUR FIELDWORK WITH A TILLER THAT COMBINES POWER AND EFFICIENCY.

This series of tillers have heavy 50 horsepower gearboxes and yet are available in tilling widths as low as 34" up to 72". A number of special features are standard at no added cost, such as; slip clutch, all gear final drive, 6 tines per rotor plate, and heavy A.S.A.E. quick hitch A-frame. Excellent tiller for vegetable growers landscapers, nurseries, vineyards, and general maintenance operations.




ROTARY TILLERS

FEATURES

- Cat. I, 3-point hitch
- ASAE quick hitch compatibility for easy hook up
- 8" approximate tilling depth
- One speed gearbox, 540 R.P.M.
- For tractors up to maximum of 50 horsepower
- Strong, smooth runnings, all gear final drive
- Slip clutch driveshaft to protect tractor and tiller drive system
- Curved, saber style heat treated, long wearing tines
- 6 tines mounted on each rotor plate for maximum tilling action
- Tines staggered in scroll design for easy solid penetration
- Adjustable clevis system lower hitch bracket
- Torque tube frame to absorb shock loads
- Tiller is balanced to eliminate vibration
- Chain with spring tailboard adjustment
- Large, greaseable, long wearing rotor bearings
- Powder coated, baked-on to reduce corrosion
- Side mount skids for depth control
- Plated retractable parking stand



All gear final drive



Slip clutch driveshaft



Adjustable depth control side skids & parking stand

SPECIFICATIONS

Model #	Tilling Width	Overall Width	No. of Tines	Approx. H.P.	Weight
C85	34"	38"	30	20	460 lbs.
C105	42"	46"	30	25	485 lbs.
C125	50"	54"	36	30	510 lbs.
C145	56"	60"	36	35	545 lbs.
C165	65"	69"	42	40	590 lbs.
C185	72"	76"	4820	45	640 lbs.

13477 Benson Ave. Chino, CA 91710 | 909/548-4848 | sales@gearmore.com