



Explore more of our products by clicking or scanning here!→



ROTARY TILLERS

"S" SERIES

UPGRADE YOUR FIELDWORK WITH A TILLER THAT COMBINES POWER AND EFFICIENCY.

These "S" Series Tillers were designed for high usage in agricultural and industrial applications. The saber shaped tines produce a uniform mixture of loose, textured soil that holds moisture and reduces erosion. There is no better tool for preparation of seedbeds. We feature the longest-wearing tines in the industry with our special tungsten carbide coated tines. The "S" Series Tiller is also available with a smooth rear roller to bury wood chips and then to slightly compact and smooth out the orchard floor.



CAT II
A. S. A. E.
QUICK
HITCH
COMPATIBLE

Double plated deck for added strength





ROTARY TILLERS

FEATURES

- Cat. II, 3-point hitch center mount
- ASAE quick hitch compatibility
- For tractors up to maximum of 120 horsepower
- Double plated deck for added strength
- Gearbox 540 R.P.M. with 4 speeds
- All gear final drive for smooth running
- Gearbox supported by full length tubes
- 6 tines mounted on each rotor plate for maximum tilling action
- Rotor shaft is computer balanced to eliminate vibration
- Torque tubing frame to absorb shock loads
- Chains for tailboard adjustment
- Large oil bath, long wearing rotor bearings
- Adjustable side skids for depth control
- Grade 8 driveshaft with slip clutch
- Retractable parking stand



4 speed gearbox



Depth control skids w/final drive protection



Heavy duty clevis style lower hitch brackets

OPTION

- "Orchard Package" smooth rear roller 16" diameter

SPECIAL TINES FEATURES



- Super alloy coated tungsten carbide
- Coating bonded on areas of normal wear
- Guaranteed to double the life of standard heat treated tines
- In some soils the life can be 3 to 4 times longer wearing

SPECIFICATIONS

Model #	Tilling Width	Overall Width	No. of Tines	Approx. H.P.	Weight
S160-CT	5' - 3" (63")	5' - 7" (67")	36	60 to 120	1,300 lbs.
S180-CT	6' - 0" (72")	6' - 5" (77")	42	70 to 120	1,400 lbs.
S205-CT	6' - 9" (81")	7' - 3" (87")	48	80 to 120	1,510 lbs.
S230-CT	7' - 7" (91")	8' - 1" (97")	54	90 to 120	1,635 lbs.
S255-CT	8' - 6" (102")	9' - 1" (109")	60	100 to 120	1,745 lbs.



FORM #SI0006-26

13477 Benson Ave. Chino, CA 91710 | 909/548-4848 | sales@gearmore.com